and 453/2010



DuPont[™] ISCEON[®] 39TC[®] (R-423A) refrigerant

Version 3.0

Revision Date 22.11.2012 Ref. 130000027358

This SDS adheres to the standards and regulatory requirements of Great Britain and may not meet the regulatory requirements in other countries.

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name : DuPont[™] ISCEON[®] 39TC[®] (R-423A) refrigerant

Types : ASHRAE Refrigerant number designation: R-423A

Synonyms : R-423A

ISCEON® 39TC®

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the Substance/Mixture Refrigerant

1.3. Details of the supplier of the safety data sheet

Company : Du Pont de Nemours (Nederland) B.V.

Baanhoekweg 22 NL-3313 LA Dordrecht

Netherlands

Telephone : +31-78-630.1011

E-mail address : sds-support@che.dupont.com

1.4. Emergency telephone number

Emergency telephone number : +44-(0)8456-006.640

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Not a hazardous substance or mixture according to EC-directives 67/548/EEC or 1999/45/EC.

2.2. Label elements

Special labelling of certain substances and mixtures Contains: 1,1,1,2-Tetrafluoroethane, 1,1,1,2,3,3,3-Heptafluoropropane / Contains fluorinated greenhouse gas covered by the Kyoto Protocol., HFC-

134a, HFC-227ea

Not a hazardous substance or mixture according to EC-directives 67/548/EEC or 1999/45/EC.

2.3. Other hazards

and 453/2010



DuPont[™] ISCEON[®] 39TC[®] (R-423A) refrigerant

Version 3.0

Revision Date 22.11.2012 Ref. 130000027358

Vapours are heavier than air and can cause suffocation by reducing oxygen available for breathing.

Rapid evaporation of the liquid may cause frostbite.

Misuse or intentional inhalation abuse may cause death without warning symptoms, due to cardiac effects.

Misuse or intentional inhalation abuse may cause death without warning symptoms, due to cardiac effects. May cause cardiac arrhythmia.

SECTION 3: Composition/information on ingredients

3.1. Substances

not applicable

3.2. Mixtures

Classification according Directive 67/548/EEC	Classification according Regulation 1272/2008 (CLP)	Concentration
(CAS-No.811-97-2) (EC-No	o.212-377-0)	
	Press. Gas H280	52.5 %
ronano (CAS-No /31-89-0)	(EC-No 207-079-2)	
Opane (CAS-NO.431-69-0)		47 F 0/
	Press. Gas H280	47.5 %
	according Directive 67/548/EEC (CAS-No.811-97-2) (EC-No.	according Directive 67/548/EEC (CAS-No.811-97-2) (EC-No.212-377-0) Press. Gas H280 ropane (CAS-No.431-89-0) (EC-No.207-079-2)

The above products are REACH compliant; Registration number(s) may not be provided because substance(s) are exempted, not yet registered under REACH or are registered under another regulatory process (biocide uses, plant protection products), etc.

For the full text of the H-Statements mentioned in this Section, see Section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

General advice : If unconscious place in recovery position and seek medical advice. Never give

anything by mouth to an unconscious person. If breathing is irregular or

stopped, administer artificial respiration.

: First aider needs to protect himself.

If symptoms persist, call a physician.

Inhalation : Remove from exposure, lie down. Move to fresh air. Keep patient warm and at

rest. Artificial respiration and/or oxygen may be necessary. Consult a

physician.

Skin contact : Take off contaminated clothing and shoes immediately. Flush area with

lukewarm water. Do not use hot water. If frostbite has occurred, call a

physician.

Eye contact : Hold eyelids apart and flush eyes with plenty of water for at least 15 minutes.

Get medical attention.

2/13

and 453/2010



DuPont[™] ISCEON[®] 39TC[®] (R-423A) refrigerant

Version 3.0

Revision Date 22.11.2012 Ref. 130000027358

Ingestion : Is not considered a potential route of exposure.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms : Misuse or intentional inhalation abuse may cause death without warning

symptoms, due to cardiac effects., Other symptoms potentially related to misuse or inhalation abuse are:, Anaesthetic effects, Light-headedness,

dizziness, confusion, incoordination, drowsiness, or unconsciousness, irregular heartbeat with a strange sensation in the chest, heart thumping, apprehension,

feeling of fainting, dizziness or weakness

: Skin contact may provoke the following symptoms:, Frostbite, Irritation,

Discomfort, Itching, Redness, Swelling of tissue

Eye contact may provoke the following symptoms:, Frostbite, Irritation, Tearing,

redness, or discomfort.

4.3. Indication of any immediate medical attention and special treatment needed

Treatment : Do not give adrenaline or similar drugs.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media : Use extinguishing measures that are appropriate to local circumstances and the

surrounding environment.

: Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.

5.2. Special hazards arising from the substance or mixture

Specific hazards during

firefighting

: Pressure build-up. Fire or intense heat may cause violent rupture of packages.

: Hazardous thermal decomposition products:

: Carbon oxides

: Hydrogen fluoride

: Fluorinated compounds

: Exposure to decomposition products may be a hazard to health.

5.3. Advice for firefighters

Special protective equipment

for firefighters

: In the event of fire, wear self-contained breathing apparatus. Use personal protective equipment. Wear neoprene gloves during cleaning up work after a

fire

Further information : Cool containers / tanks with water spray.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions : Evacuate personnel to safe areas. Ventilate area, especially low or enclosed

and 453/2010



DuPont[™] ISCEON[®] 39TC[®] (R-423A) refrigerant

Version 3.0

Revision Date 22.11.2012 Ref. 130000027358

places where heavy vapours might collect. Refer to protective measures listed

in sections 7 and 8.

6.2. Environmental precautions

Environmental precautions : Should not be released into the environment.

In accordance with local and national regulations.

6.3. Methods and materials for containment and cleaning up

Methods for cleaning up : Evaporates.

6.4. Reference to other sections

For disposal instructions see section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling : Avoid breathing vapours or mist. Avoid contact with skin, eyes and clothing.

Provide sufficient air exchange and/or exhaust in work rooms. For personal

protection see section 8.

Vapours are heavier than air and may spread along floors.

Advice on protection against fire and explosion

The product is not flammable in air under ambient conditions of temperature and pressure. When pressurised with air or oxygen, the mixture may become flammable. Certain mixtures of HCFCs or HFCs with chlorine may become

flammable or reactive under certain conditions.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers

: Do not drag, slide or roll cylinders. Never attempt to lift cylinder by its cap. Use a check valve or trap in the discharge line to prevent hazardous back flow into the cylinder. Keep at temperature not exceeding 52 °C. Keep containers tightly closed in a dry, cool and well-ventilated place. Protect from contamination. Protect cylinders from damage. Keep away from direct sunlight. Store only in

approved containers.

Advice on common storage : No materials to be especially mentioned.

For further information see Section 10 of the safety data sheet.

Storage temperature : < 52 ℃

7.3. Specific end use(s)

no data available

SECTION 8: Exposure controls/personal protection

and 453/2010



DuPont[™] ISCEON[®] 39TC[®] (R-423A) refrigerant

Version 3.0

Revision Date 22.11.2012 Ref. 130000027358

8.1. Control parameters

If sub-section is empty then no values are applicable.

Components with workplace control parameters

oompononto mun mon	.p.acc cc	, a. a		
Туре	Control	Update	Basis	Remarks
Form of exposure	parameters			

1,1,1,2-Tetrafluoroethane (CAS-No. 811-97-2)

TWA	4,240 mg/m3	2007	EH40 WEL
	1,000 ppm		

Derived No Effect Level (DNEL)

• 1,1,1,2-Tetrafluoroethane : Type of Application (Use): Workers

Exposure routes: Inhalation

Health Effect: Chronic effects, Systemic toxicity

Value: 13936 mg/m3

: Type of Application (Use): Consumers

Exposure routes: Inhalation

Health Effect: Chronic effects, Systemic toxicity

Value: 2476 mg/m3

• 1,1,1,2,3,3,3- : Type of Application (Use): Workers

Heptafluoropropane Exposure routes: Inhalation

Health Effect: Chronic effects, Systemic toxicity

Value: 61279 mg/m3

: Type of Application (Use): Consumers

Exposure routes: Inhalation

Health Effect: Chronic effects, Systemic toxicity

Value: 6533 mg/m3

Predicted No Effect Concentration (PNEC)

1,1,1,2-Tetrafluoroethane : Value: 0.1 mg/l

Compartment: Fresh water

: Value: 0.01 mg/l

Compartment: Marine water

: Value: 1 mg/l

Compartment: Water

Remarks: Intermittent use/release

: Value: 0.75 mg/kg dry weight (d.w.) Compartment: Fresh water sediment

: Value: 73 mg/l Compartment: Water

Remarks: Sewage treatment plants

and 453/2010



DuPont[™] ISCEON[®] 39TC[®] (R-423A) refrigerant

Version 3.0

П

Revision Date 22.11.2012 Ref. 130000027358

• 1,1,1,2,3,3,3- : Value: 0.1 mg/l

Heptafluoropropane Compartment: Fresh water

: Value: 1 mg/l

Compartment: Water

Remarks: Intermittent use/release

: Value: 1.3 mg/kg

Compartment: Fresh water sediment

: Value: 1.73 mg/kg Compartment: Water

Remarks: Sewage treatment plants

8.2. Exposure controls

Engineering measures : Ensure adequate ventilation, especially in confined areas. Local exhaust should

be used when large amounts are released.

Eye protection : Wear safety glasses or coverall chemical splash goggles.

Eye protection complying with EN 166.

or

ANSI Z87.1

Additionally wear a face shield where the possibility exists for face contact due

to splashing, spraying or airborne contact with this material.

Hand protection : Material: Leather gloves

The suitability for a specific workplace should be discussed with the producers

of the protective gloves.

: Material: Low temperature resistant gloves

:

Protective gloves complying with EN 374. or US OSHA guidelines

.

The choice of an appropriate glove does not only depend on its material but also on other quality features and is different from one producer to the other. Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of

cuts, abrasion, and the contact time.

Skin and body protection : Wear suitable protective equipment. Wear as appropriate: impervious clothing

Protective measures : Self-contained breathing apparatus (SCBA) is required if a large release occurs.

The type of protective equipment must be selected according to the concentration and amount of the substance at the specific workplace.

Hygiene measures : Handle in accordance with good industrial hygiene and safety practice.

Respiratory protection : For rescue and maintenance work in storage tanks use self-contained breathing apparatus. Vapours are heavier than air and can cause suffocation by reducing

oxygen available for breathing. Respiratory protection complying with EN 137.

and 453/2010



DuPont[™] ISCEON[®] 39TC[®] (R-423A) refrigerant

Revision Date 22.11.2012 Ref. 130000027358

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Form : Liquefied gas

Colour : colourless

Odour : slight, ether-like

рН : neutral

Boiling point/boiling range : ca. -25 °C at 1,013 hPa

Flash point : does not flash

Upper explosion limit/ upper

flammability limit

: not applicable

Vapour pressure : ca. 6,400 hPa at 25 ℃

Relative density : 1.28 at 25 ℃

9.2. Other information no data available

SECTION 10: Stability and reactivity

10.1. Reactivity : Decomposes on heating.

10.2. Chemical stability : The product is chemically stable.

10.3. Possibility of hazardous reactions : Polymerization will not occur. Stable under recommended storage conditions.

10.4. Conditions to avoid : Avoid open flames and high temperatures. The product is not flammable in air

> under ambient conditions of temperature and pressure. When pressurised with air or oxygen, the mixture may become flammable. Certain mixtures of HCFCs or HFCs with chlorine may become flammable or reactive under certain

> conditions. Pressurized container: Do not pierce or burn, even after use. Keep

at temperature not exceeding 52°C.

10.5. Incompatible materials : Alkali metals

> Alkaline earth metals Powdered metals Powdered metal salts

10.6. Hazardous

decomposition products

Hazardous thermal decomposition products may include:

Hydrogen fluoride Carbon oxides Fluorocarbons Carbonyl fluoride

7/13

and 453/2010



DuPont[™] ISCEON[®] 39TC[®] (R-423A) refrigerant

Version 3.0

Revision Date 22.11.2012

Ref. 130000027358

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute oral toxicity

 1,1,1,2,3,3,3-Heptafluoropropane not applicable

Acute inhalation toxicity

1,1,1,2-Tetrafluoroethane
 LC50 / 4 h rat :567000 ppm

Low Observed Adverse Effect Concentration (LOAEC) / dog :75000 ppm Cardiac sensitization

No Observed Adverse Effect Concentration (NOAEC) / dog :50000 ppm Cardiac sensitization

 1,1,1,2,3,3,3-Heptafluoropropane LC50 / 4 h rat :> 788698 ppm

Low Observed Adverse Effect Concentration (LOAEC) / dog :105000 ppm Cardiac sensitization

No Observed Adverse Effect Concentration (NOAEC) / dog :90000 ppm

Acute dermal toxicity

• 1,1,1,2,3,3,3-Heptafluoropropane not applicable

Skin irritation

• 1,1,1,2-Tetrafluoroethane

rabbit

Classification: Not classified as irritant

Result: slight irritation

Not expected to cause skin irritation based on expert review of the properties of the substance.

human

Classification: Not classified as irritant

Result: No skin irritation

• 1,1,1,2,3,3,3-Heptafluoropropane

Not tested on animals

Classification: Not classified as irritant

Result: No skin irritation

Not expected to cause skin irritation based on expert review of the properties of the substance.

Eye irritation

and 453/2010



DuPont[™] ISCEON[®] 39TC[®] (R-423A) refrigerant

Version 3.0

Revision Date 22.11.2012

Ref. 130000027358

• 1,1,1,2-Tetrafluoroethane

rabbit

Classification: Not classified as irritant

Result: slight irritation

Not expected to cause eye irritation based on expert review of the properties of the substance.

human

Classification: Not classified as irritant

Result: No eye irritation

• 1,1,1,2,3,3,3-Heptafluoropropane

Not tested on animals

Classification: Not classified as irritant

Result: No eye irritation

Not expected to cause eye irritation based on expert review of the properties of the substance.

Sensitisation

• 1,1,1,2-Tetrafluoroethane

guinea pig

Classification: Not a skin sensitizer.

Result: Did not cause sensitization on laboratory animals.

Not expected to cause sensitization based on expert review of the properties of the substance.

Did not cause sensitization on laboratory animals. There are no reports of human respiratory sensitization.

• 1,1,1,2,3,3,3-Heptafluoropropane

Not tested on animals

Classification: Not a skin sensitizer. Result: Does not cause skin sensitization.

Not expected to cause sensitization based on expert review of the properties of the substance.

Did not cause sensitization on laboratory animals. There are no reports of human respiratory sensitization.

Repeated dose toxicity

• 1,1,1,2-Tetrafluoroethane

Inhalation rat

No toxicologically significant effects were found.

• 1,1,1,2,3,3,3-Heptafluoropropane

Inhalation rat

No toxicologically significant effects were found.

Mutagenicity assessment

• 1,1,1,2-Tetrafluoroethane

Animal testing did not show any mutagenic effects. Tests on bacterial or mammalian cell cultures did not show mutagenic effects.

• 1,1,1,2,3,3,3-Heptafluoropropane

Animal testing did not show any mutagenic effects. Tests on bacterial or mammalian cell cultures did not show mutagenic effects.

and 453/2010



DuPont[™] ISCEON[®] 39TC[®] (R-423A) refrigerant

Version 3.0 Revision Date 22.11.2012

Ref. 130000027358

Carcinogenicity assessment

- 1,1,1,2-Tetrafluoroethane
 Not classifiable as a human carcinogen.
- 1,1,1,2,3,3,3-Heptafluoropropane

 Not classifiable as a human carcinogen.

Toxicity to reproduction assessment

- 1,1,1,2-Tetrafluoroethane No toxicity to reproduction
- 1,1,1,2,3,3,3-Heptafluoropropane
 No toxicity to reproduction

Further information

Avoid skin contact with leaking liquid (danger of frostbite).

SECTION 12: Ecological information

12.1. Toxicity

Toxicity to fish

- 1,1,1,2-Tetrafluoroethane
 LC50 / 96 h / Oncorhynchus mykiss (rainbow trout): 450 mg/l
- 1,1,1,2,3,3,3-Heptafluoropropane
 LC50 / 96 h / Danio rerio (zebra fish): > 200 mg/l
 Information given is based on data obtained from similar substances.

LC50 / 96 h / Oncorhynchus mykiss (rainbow trout): > 81.8 mg/l Information given is based on data obtained from similar substances.

Toxicity to aquatic plants

- 1,1,1,2-Tetrafluoroethane
 EC50 / 72 h / Algae: > 118 mg/l
 Information given is based on data obtained from similar substances.
- 1,1,1,2,3,3,3-Heptafluoropropane
 EC50 / 72 h / Pseudokirchneriella subcapitata: > 114 mg/l
 Information given is based on data obtained from similar substances.

Toxicity to aquatic invertebrates

- 1,1,1,2-Tetrafluoroethane EC50 / 48 h / Daphnia magna (Water flea): 980 mg/l
- 1,1,1,2,3,3,3-Heptafluoropropane
 EC50 / 48 h / Daphnia magna (Water flea): > 200 mg/l
 Information given is based on data obtained from similar substances.

and 453/2010



DuPont[™] ISCEON[®] 39TC[®] (R-423A) refrigerant

Revision Date 22.11.2012

Ref. 130000027358

12.2. Persistence and degradability

Biodegradability

• 1,1,1,2-Tetrafluoroethane / 28 d Biodegradation: 3 %

Not readily biodegradable.

• 1,1,1,2,3,3,3-Heptafluoropropane aerobic 8.49 mg/l / 28 d Biodegradation: 1 % Method: OECD Test Guideline 301 Not readily biodegradable. aerobic 17.4 mg/l / 28 d Biodegradation: 5 % Method: OECD Test Guideline 301

Not readily biodegradable.

12.3. Bioaccumulative potential

Bioaccumulation

• 1,1,1,2-Tetrafluoroethane Bioaccumulation is unlikely.

12.4. Mobility in soil

no data available

12.5. Results of PBT and vPvB assessment

no data available

12.6. Other adverse effects

Ozone depletion potential

0

Global warming potential (GWP)

2280

Additional ecological information

IPCC - AR4 (Fourth Assessment Report of the Intergovernmental Panel on Climate Change) - 2007

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Product : Can be used after re-conditioning. If re-conditioning is not practicable, dispose

of in compliance with local regulations.

and 453/2010



DuPont[™] ISCEON[®] 39TC[®] (R-423A) refrigerant

Version 3.0

Revision Date 22.11.2012 Ref. 130000027358

Contaminated packaging : Empty pressure vessels should be returned to the supplier.

If recycling is not practicable, dispose of in compliance with local regulations.

SECTION 14: Transport information

ΔDR

14.1. UN number: 1078

14.2. UN proper shipping name: Refrigerant gas, n.o.s. (1,1,1,2-Tetrafluoroethane, 1,1,1,2,3,3,3-

Heptafluoropropane)

14.3. Transport hazard class(es):

14.4. Packing group: not applicable

14.5. Environmental hazards: For further information see Section 12.

14.6. Special precautions for user:

Tunnel restriction code: (C/E)

IATA C

14.1. UN number: 1078

14.2. UN proper shipping name: Refrigerant gas, n.o.s. (1,1,1,2-Tetrafluoroethane, 1,1,1,2,3,3,3-

Heptafluoropropane)

14.3. Transport hazard class(es): 2.2

14.4. Packing group: not applicable

14.5. Environmental hazards: For further information see Section 12.

14.6. Special precautions for user:

no data available

IMDG

14.1. UN number: 1078

14.2. UN proper shipping name: Refrigerant gas, n.o.s. (1,1,1,2-Tetrafluoroethane, 1,1,1,2,3,3,3-

Heptafluoropropane)

14.3. Transport hazard class(es): 2.2

14.4. Packing group: not applicable

14.5. Environmental hazards: For further information see Section 12.

14.6. Special precautions for user:

no data available

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Other regulations : Take note of Directive 98/24/EC on the protection of the health and safety of

workers from the risks related to chemical agents at work.

15.2. Chemical Safety Assessment

Chemical Safety Assessments have been carried out for these substances.

SECTION 16: Other information

Full text of H-Statements referred to under section 3.

H280 Contains gas under pressure; may explode if heated.

12/13

and 453/2010

DuPont[™] ISCEON[®] 39TC[®] (R-423A) refrigerant

Revision Date 22.11.2012 Ref. 130000027358

Further information

[®] DuPont's registered trademark, Before use read DuPont's safety information., For further information contact the local DuPont office or DuPont's nominated distributors.

Significant change from previous version is denoted with a double bar.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guide for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The above information relates only to the specific material(s) designated herein and may not be valid for such material(s) used in combination with any other materials or in any process or if the material is altered or processed, unless specified in the text.