

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



Opteon™ XP40 (R-449A) Refrigerant

Version 4.12 Revision Date: 26.03.2019 SDS Number: 1349448-00043 Date of last issue: 18.09.2018
Date of first issue: 27.02.2017

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : Opteon™ XP40 (R-449A) Refrigerant
Product code : D15262174
SDS-Identcode : 130000133420

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Sub-stance/Mixture : Refrigerant
Recommended restrictions : For professional and industrial installation and use only.
on use

1.3 Details of the supplier of the safety data sheet

Company : Chemours Netherlands B.V.
Baanhoekweg 22
3313 LA Dordrecht Netherlands
Telephone : +31-(0)-78-630-1011
Telefax : +31-78-6163737
E-mail address of person responsible for the SDS : sds-support@chemours.com

1.4 Emergency telephone number

+(44)-870-8200418 (CHEMTREC - Recommended)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Gases under pressure, Liquefied gas H280: Contains gas under pressure; may explode if heated.

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms :



Signal word : Warning

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



Opteon™ XP40 (R-449A) Refrigerant

Version 4.12 Revision Date: 26.03.2019 SDS Number: 1349448-00043 Date of last issue: 18.09.2018
Date of first issue: 27.02.2017

Hazard statements : H280 Contains gas under pressure; may explode if heated.

Precautionary statements : **Storage:**
P410 + P403 Protect from sunlight. Store in a well-ventilated place.

Additional Labelling

Contains fluorinated greenhouse gases. (HFC-134a, HFC-125, HFC-32)

2.3 Other hazards

This mixture contains no substance considered to be persistent, bioaccumulating and toxic (PBT).
This mixture contains no substance considered to be very persistent and very bioaccumulating (vPvB).

Vapours are heavier than air and can cause suffocation by reducing oxygen available for breathing.

Misuse or intentional inhalation abuse may cause death without warning symptoms, due to cardiac effects.

Rapid evaporation of the product may cause frostbite.

May displace oxygen and cause rapid suffocation.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Chemical nature : Fluorinated hydrocarbons

Components

Chemical name	CAS-No. EC-No. Index-No. Registration number	Classification	Concentration (% w/w)
1,1,1,2-Tetrafluoroethane*	811-97-2 212-377-0 01-2119459374-33	Press. Gas Liquefied gas; H280	25.7
2,3,3,3-Tetrafluoropropene*	754-12-1 468-710-7 01-0000019665-61	Flam. Gas 1; H220 Press. Gas Liquefied gas; H280	25.3
Pentafluoroethane*	354-33-6 206-557-8 01-2119485636-25	Press. Gas Liquefied gas; H280	24.7
Difluoromethane*	75-10-5 200-839-4 01-2119471312-47	Flam. Gas 1; H220 Press. Gas Liquefied gas; H280	24.3

* Voluntarily-disclosed non-hazardous substance

For explanation of abbreviations see section 16.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



Opteon™ XP40 (R-449A) Refrigerant

Version	Revision Date:	SDS Number:	Date of last issue: 18.09.2018
4.12	26.03.2019	1349448-00043	Date of first issue: 27.02.2017

SECTION 4: First aid measures

4.1 Description of first aid measures

- General advice : In the case of accident or if you feel unwell, seek medical advice immediately.
When symptoms persist or in all cases of doubt seek medical advice.
- Protection of first-aiders : No special precautions are necessary for first aid responders.
- If inhaled : If inhaled, remove to fresh air.
Get medical attention if symptoms occur.
- In case of skin contact : Thaw frosted parts with lukewarm water. Do not rub affected area.
Get medical attention immediately.
- In case of eye contact : Get medical attention immediately.
- If swallowed : Ingestion is not considered a potential route of exposure.

4.2 Most important symptoms and effects, both acute and delayed

- Symptoms : May cause cardiac arrhythmia.
- Other symptoms potentially related to misuse or inhalation abuse are
Cardiac sensitisation
Anaesthetic effects
Light-headedness
Dizziness
confusion
Lack of coordination
Drowsiness
Unconsciousness
- Skin contact may provoke the following symptoms:
Irritation
Swelling of tissue
Itching
Discomfort
Redness
- Eye contact may provoke the following symptoms
tearing
Redness
Discomfort
- Risks : Contact with liquid or refrigerated gas can cause cold burns and frostbite.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



Opteon™ XP40 (R-449A) Refrigerant

Version	Revision Date:	SDS Number:	Date of last issue: 18.09.2018
4.12	26.03.2019	1349448-00043	Date of first issue: 27.02.2017

4.3 Indication of any immediate medical attention and special treatment needed

Treatment : Treat symptomatically and supportively.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media : Not applicable
Will not burn

Unsuitable extinguishing media : Not applicable
Will not burn

5.2 Special hazards arising from the substance or mixture

Specific hazards during fire-fighting : Exposure to combustion products may be a hazard to health. If the temperature rises there is danger of the vessels bursting due to the high vapor pressure.

Hazardous combustion products : Hydrogen fluoride
carbonyl fluoride
Carbon oxides
Fluorine compounds

5.3 Advice for firefighters

Special protective equipment for firefighters : Wear self-contained breathing apparatus for firefighting if necessary. Use personal protective equipment.

Specific extinguishing methods : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment. Fight fire remotely due to the risk of explosion. Use water spray to cool unopened containers. Remove undamaged containers from fire area if it is safe to do so. Evacuate area.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Evacuate personnel to safe areas. Avoid skin contact with leaking liquid (danger of frostbite). Ventilate the area. Follow safe handling advice and personal protective equipment recommendations.

6.2 Environmental precautions

Environmental precautions : Prevent further leakage or spillage if safe to do so. Retain and dispose of contaminated wash water.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



Opteon™ XP40 (R-449A) Refrigerant

Version	Revision Date:	SDS Number:	Date of last issue: 18.09.2018
4.12	26.03.2019	1349448-00043	Date of first issue: 27.02.2017

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Ventilate the area.
Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which regulations are applicable.
Sections 13 and 15 of this SDS provide information regarding certain local or national requirements.

6.4 Reference to other sections

See sections: 7, 8, 11, 12 and 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Technical measures : Use equipment rated for cylinder pressure. Use a backflow preventative device in piping. Close valve after each use and when empty.

Local/Total ventilation : Use only with adequate ventilation.

Advice on safe handling : Handle in accordance with good industrial hygiene and safety practice, based on the results of the workplace exposure assessment
Wear cold insulating gloves/ face shield/ eye protection.
Prevent backflow into the gas tank.
Open the valves slowly to prevent pressure surges.
Close valve after each use and when empty. Do NOT change or force fit connections.
Prevent the intrusion of water into the gas tank.
Keep away from heat and sources of ignition.
Take precautionary measures against static discharges.
Take care to prevent spills, waste and minimize release to the environment.

Avoid breathing gas.
Valve protection caps and valve outlet threaded plugs must remain in place unless container is secured with valve outlet piped to use point.
Use a check valve or trap in the discharge line to prevent hazardous back flow into the cylinder.
Use a pressure reducing regulator when connecting cylinder to lower pressure (<3000 psig) piping or systems.
Never attempt to lift cylinder by its cap.
Do not drag, slide or roll cylinders.
Use a suitable hand truck for cylinder movement.

Hygiene measures : Ensure that eye flushing systems and safety showers are located close to the working place. When using do not eat, drink or smoke. Wash contaminated clothing before re-use.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



Opteon™ XP40 (R-449A) Refrigerant

Version 4.12 Revision Date: 26.03.2019 SDS Number: 1349448-00043 Date of last issue: 18.09.2018
Date of first issue: 27.02.2017

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers : Cylinders should be stored upright and firmly secured to prevent falling or being knocked over. Separate full containers from empty containers. Do not store near combustible materials. Avoid area where salt or other corrosive materials are present. Keep in properly labelled containers. Keep in a cool, well-ventilated place. Keep away from direct sunlight. Store in accordance with the particular national regulations.

Advice on common storage : Do not store with the following product types:
Self-reactive substances and mixtures
Organic peroxides
Oxidizing agents
Flammable liquids
Flammable solids
Pyrophoric liquids
Pyrophoric solids
Self-heating substances and mixtures
Substances and mixtures, which in contact with water, emit flammable gases
Explosives
Acutely toxic substances and mixtures
Substances and mixtures with chronic toxicity

Storage period : > 10 yr

Recommended storage temperature : < 52 °C

Further information on storage stability : The product has an indefinite shelf life when stored properly.

7.3 Specific end use(s)

Specific use(s) : No data available

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
1,1,1,2-Tetrafluoroethane	811-97-2	TWA	1,000 ppm 4,240 mg/m ³	GB EH40
Further information	Where no specific short-term exposure limit is listed, a figure three times the long-term exposure should be used			

Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

Substance name	End Use	Exposure routes	Potential health effects	Value
----------------	---------	-----------------	--------------------------	-------

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



Opteon™ XP40 (R-449A) Refrigerant

Version 4.12 Revision Date: 26.03.2019 SDS Number: 1349448-00043 Date of last issue: 18.09.2018
Date of first issue: 27.02.2017

1,1,1,2-Tetrafluoroethane	Workers	Inhalation	Long-term systemic effects	13936 mg/m ³
	Consumers	Inhalation	Long-term systemic effects	2476 mg/m ³
2,3,3,3-Tetrafluoropropene	Workers	Inhalation	Long-term systemic effects	950 mg/m ³
Pentafluoroethane	Workers	Inhalation	Long-term systemic effects	16444 mg/m ³
	Consumers	Inhalation	Long-term systemic effects	1753 mg/m ³
Difluoromethane	Workers	Inhalation	Long-term systemic effects	7035 mg/m ³
	Consumers	Inhalation	Long-term systemic effects	750 mg/m ³

Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

Substance name	Environmental Compartment	Value
1,1,1,2-Tetrafluoroethane	Fresh water	0.1 mg/l
	Marine water	0.01 mg/l
	Intermittent use/release	1 mg/l
	Fresh water sediment	0.75 mg/kg dry weight (d.w.)
	Sewage treatment plant	73 mg/l
2,3,3,3-Tetrafluoropropene	Fresh water	0.1 mg/l
	Intermittent use/release	1 mg/l
	Fresh water sediment	1.77 mg/kg dry weight (d.w.)
	Soil	1.54 mg/kg dry weight (d.w.)
	Marine water	0.01 mg/l
Pentafluoroethane	Marine sediment	0.178 mg/kg dry weight (d.w.)
	Fresh water	0.1 mg/l
	Intermittent use/release	1 mg/l
Difluoromethane	Fresh water sediment	0.6 mg/kg
	Fresh water	0.142 mg/l
	Intermittent use/release	1.42 mg/l
	Fresh water sediment	0.534 mg/kg

8.2 Exposure controls

Engineering measures

Ensure adequate ventilation, especially in confined areas.
Minimize workplace exposure concentrations.

Personal protective equipment

Eye protection : Wear the following personal protective equipment:
Chemical resistant goggles must be worn.
Face-shield
Equipment should conform to BS EN 166

Hand protection
Material : Low temperature resistant gloves

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



Opteon™ XP40 (R-449A) Refrigerant

Version	Revision Date:	SDS Number:	Date of last issue: 18.09.2018
4.12	26.03.2019	1349448-00043	Date of first issue: 27.02.2017

- Remarks : Choose gloves to protect hands against chemicals depending on the concentration and quantity of the hazardous substance and specific to place of work. For special applications, we recommend clarifying the resistance to chemicals of the aforementioned protective gloves with the glove manufacturer. Wash hands before breaks and at the end of workday. Breakthrough time is not determined for the product. Change gloves often!
- Skin and body protection : Skin should be washed after contact.
- Respiratory protection : Use respiratory protection unless adequate local exhaust ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines.
- Filter type : Organic gas and low boiling vapour type (AX)
- Protective measures : Wear cold insulating gloves/ face shield/ eye protection.
-

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

- Appearance : Liquefied gas
- Colour : clear
- Odour : slight, ether-like
- Odour Threshold : No data available
- pH : No data available
- Melting point/freezing point : No data available
- Initial boiling point and boiling range : -46 °C
- Flash point : Not applicable
- Evaporation rate : > 1
(CCL4=1.0)
- Flammability (solid, gas) : Will not burn
- Upper explosion limit / Upper flammability limit : Upper flammability limit
Method: ASTM E681
None.
- Lower explosion limit / Lower flammability limit : Lower flammability limit
Method: ASTM E681
None.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



Opteon™ XP40 (R-449A) Refrigerant

Version	Revision Date:	SDS Number:	Date of last issue: 18.09.2018
4.12	26.03.2019	1349448-00043	Date of first issue: 27.02.2017

Vapour pressure	:	12,748 hPa (25 °C)
Relative vapour density	:	3.07 (Air = 1.0)
Relative density	:	1.10 (25 °C)
Solubility(ies)	:	
Water solubility	:	No data available
Partition coefficient: n-octanol/water	:	Not applicable
Auto-ignition temperature	:	No data available
Decomposition temperature	:	No data available
Viscosity	:	
Viscosity, kinematic	:	Not applicable
Explosive properties	:	Not explosive
Oxidizing properties	:	The substance or mixture is not classified as oxidizing.

9.2 Other information

Particle size	:	Not applicable
---------------	---	----------------

SECTION 10: Stability and reactivity

10.1 Reactivity

Not classified as a reactivity hazard.

10.2 Chemical stability

Stable if used as directed. Follow precautionary advice and avoid incompatible materials and conditions.

10.3 Possibility of hazardous reactions

Hazardous reactions	:	Can react with strong oxidizing agents.
---------------------	---	---

10.4 Conditions to avoid

Conditions to avoid	:	Heat, flames and sparks.
---------------------	---	--------------------------

10.5 Incompatible materials

Materials to avoid	:	Oxidizing agents
--------------------	---	------------------

10.6 Hazardous decomposition products

No hazardous decomposition products are known.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



Opteon™ XP40 (R-449A) Refrigerant

Version 4.12 Revision Date: 26.03.2019 SDS Number: 1349448-00043 Date of last issue: 18.09.2018
Date of first issue: 27.02.2017

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Information on likely routes of exposure : Inhalation
Skin contact
Eye contact

Acute toxicity

Not classified based on available information.

Components:

1,1,1,2-Tetrafluoroethane:

Acute inhalation toxicity : LC50 (Rat): > 567000 ppm
Exposure time: 4 h
Test atmosphere: gas

No observed adverse effect concentration (Dog): 40000 ppm
Test atmosphere: gas
Symptoms: Cardiac sensitisation

Lowest observed adverse effect concentration (Dog): 80000 ppm
Test atmosphere: gas
Symptoms: Cardiac sensitisation

Cardiac sensitisation threshold limit (Dog): 334,000 mg/m³
Test atmosphere: gas
Symptoms: Cardiac sensitisation

2,3,3,3-Tetrafluoropropene:

Acute inhalation toxicity : LC50 (Rat): > 405000 ppm
Exposure time: 4 h
Test atmosphere: gas

Lowest observed adverse effect concentration (Dog): > 120000 ppm
Test atmosphere: gas
Symptoms: Cardiac sensitisation

No observed adverse effect concentration (Dog): 120000 ppm
Test atmosphere: gas
Symptoms: Cardiac sensitisation

Cardiac sensitisation threshold limit (Dog): > 559,509 mg/m³
Test atmosphere: gas
Symptoms: Cardiac sensitisation

Pentafluoroethane:

Acute inhalation toxicity : LC0 (Rat): > 800000 ppm
Exposure time: 4 h

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



Opteon™ XP40 (R-449A) Refrigerant

Version 4.12 Revision Date: 26.03.2019 SDS Number: 1349448-00043 Date of last issue: 18.09.2018
Date of first issue: 27.02.2017

Test atmosphere: gas
Method: OECD Test Guideline 403

Difluoromethane:

Acute inhalation toxicity : LC50 (Rat): > 520000 ppm
Exposure time: 4 h
Test atmosphere: gas

Lowest observed adverse effect concentration (Dog): > 350000 ppm
Symptoms: Cardiac sensitisation

No observed adverse effect concentration (Dog): 350000 ppm
Symptoms: Cardiac sensitisation

Cardiac sensitisation threshold limit (Dog): > 735,000 mg/m³
Symptoms: Cardiac sensitisation

Skin corrosion/irritation

Not classified based on available information.

Components:

1,1,1,2-Tetrafluoroethane:

Species : Rabbit
Result : No skin irritation

2,3,3,3-Tetrafluoropropene:

Species : Not tested on animals
Result : No skin irritation

Difluoromethane:

Species : Not tested on animals
Result : No skin irritation

Serious eye damage/eye irritation

Not classified based on available information.

Components:

1,1,1,2-Tetrafluoroethane:

Species : Rabbit
Result : No eye irritation

2,3,3,3-Tetrafluoropropene:

Species : Not tested on animals
Result : No eye irritation

Difluoromethane:

Species : Not tested on animals

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



Opteon™ XP40 (R-449A) Refrigerant

Version 4.12 Revision Date: 26.03.2019 SDS Number: 1349448-00043 Date of last issue: 18.09.2018
Date of first issue: 27.02.2017

Result : No eye irritation

Respiratory or skin sensitisation

Skin sensitisation

Not classified based on available information.

Respiratory sensitisation

Not classified based on available information.

Components:

1,1,1,2-Tetrafluoroethane:

Exposure routes : Skin contact
Species : Guinea pig
Result : negative

Species : Rat
Result : negative

2,3,3,3-Tetrafluoropropene:

Exposure routes : Skin contact
Species : Not tested on animals
Result : negative

Difluoromethane:

Exposure routes : Skin contact
Species : Not tested on animals
Result : negative

Species : Not tested on animals
Result : negative

Germ cell mutagenicity

Not classified based on available information.

Components:

1,1,1,2-Tetrafluoroethane:

Germ cell mutagenicity- Assessment : Weight of evidence does not support classification as a germ cell mutagen.

2,3,3,3-Tetrafluoropropene:

Germ cell mutagenicity- Assessment : Weight of evidence does not support classification as a germ cell mutagen.

Pentafluoroethane:

Genotoxicity in vitro : Test Type: Chromosome aberration test in vitro
Method: OECD Test Guideline 473
Result: negative

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



Opteon™ XP40 (R-449A) Refrigerant

Version	Revision Date:	SDS Number:	Date of last issue: 18.09.2018
4.12	26.03.2019	1349448-00043	Date of first issue: 27.02.2017

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay)
Species: Mouse
Application Route: inhalation (gas)
Method: OECD Test Guideline 474
Result: negative

Difluoromethane:

Germ cell mutagenicity- Assessment : Weight of evidence does not support classification as a germ cell mutagen.

Carcinogenicity

Not classified based on available information.

Components:

1,1,1,2-Tetrafluoroethane:

Carcinogenicity - Assessment : Weight of evidence does not support classification as a carcinogen

2,3,3,3-Tetrafluoropropene:

Carcinogenicity - Assessment : Weight of evidence does not support classification as a carcinogen

Reproductive toxicity

Not classified based on available information.

Components:

1,1,1,2-Tetrafluoroethane:

Reproductive toxicity - Assessment : Weight of evidence does not support classification for reproductive toxicity

2,3,3,3-Tetrafluoropropene:

Reproductive toxicity - Assessment : Weight of evidence does not support classification for reproductive toxicity

Pentafluoroethane:

Effects on fertility : Test Type: One-generation reproduction toxicity study
Species: Rat
Application Route: inhalation (vapour)
Result: negative
Remarks: Based on data from similar materials

Effects on foetal development : Test Type: Embryo-foetal development
Species: Rat
Application Route: inhalation (gas)
Method: OECD Test Guideline 414
Result: negative

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



Opteon™ XP40 (R-449A) Refrigerant

Version 4.12 Revision Date: 26.03.2019 SDS Number: 1349448-00043 Date of last issue: 18.09.2018
Date of first issue: 27.02.2017

Difluoromethane:

Reproductive toxicity - Assessment : Weight of evidence does not support classification for reproductive toxicity, Based on data from similar materials

STOT - single exposure

Not classified based on available information.

STOT - repeated exposure

Not classified based on available information.

Components:

1,1,1,2-Tetrafluoroethane:

Assessment : No significant health effects observed in animals at concentrations of 250 ppmV/6h/d or less.

2,3,3,3-Tetrafluoropropene:

Assessment : No significant health effects observed in animals at concentrations of 250 ppmV/6h/d or less.

Difluoromethane:

Assessment : No significant health effects observed in animals at concentrations of 250 ppmV/6h/d or less.

Repeated dose toxicity

Components:

1,1,1,2-Tetrafluoroethane:

Species : Rat
NOAEL : 50000 ppm
LOAEL : > 50000 ppm
Application Route : inhalation (gas)
Exposure time : 90 d
Method : OECD Test Guideline 413
Remarks : No significant adverse effects were reported

2,3,3,3-Tetrafluoropropene:

Species : Rat
NOAEL : 50000 ppm
LOAEL : >50000 ppm
Application Route : inhalation (gas)
Exposure time : 90 d
Method : OECD Test Guideline 413
Remarks : No significant adverse effects were reported

Pentafluoroethane:

Species : Rat
NOAEL : >= 50000 ppm
Application Route : inhalation (gas)

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



Opteon™ XP40 (R-449A) Refrigerant

Version 4.12 Revision Date: 26.03.2019 SDS Number: 1349448-00043 Date of last issue: 18.09.2018
Date of first issue: 27.02.2017

Exposure time : 13 Weeks
Method : OECD Test Guideline 413

Difluoromethane:

Species : Rat
NOAEL : 49100 ppm
Application Route : inhalation (gas)
Exposure time : 90 d
Remarks : No significant adverse effects were reported

Aspiration toxicity

Not classified based on available information.

SECTION 12: Ecological information

12.1 Toxicity

Components:

1,1,1,2-Tetrafluoroethane:

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 450 mg/l
Exposure time: 96 h

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 980 mg/l
Exposure time: 48 h

Toxicity to algae/aquatic plants : ErC50 (algae): 142 mg/l
Exposure time: 96 h
Remarks: Based on data from similar materials

NOEC (Pseudokirchneriella subcapitata (green algae)): 13.2 mg/l
Exposure time: 72 h
Remarks: Based on data from similar materials

2,3,3,3-Tetrafluoropropene:

Toxicity to fish : LC50 (Cyprinus carpio (Carp)): > 197 mg/l
Exposure time: 96 h

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 100 mg/l
Exposure time: 48 h

Toxicity to algae/aquatic plants : NOEC (algae): > 100 mg/l
Exposure time: 72 h

Pentafluoroethane:

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 450 mg/l
Exposure time: 96 h
Method: Directive 67/548/EEC, Annex V, C.1.
Remarks: Based on data from similar materials

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



Opteon™ XP40 (R-449A) Refrigerant

Version 4.12 Revision Date: 26.03.2019 SDS Number: 1349448-00043 Date of last issue: 18.09.2018
Date of first issue: 27.02.2017

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 980 mg/l
Exposure time: 48 h
Method: Directive 67/548/EEC, Annex V, C.2.
Remarks: Based on data from similar materials

Toxicity to algae/aquatic plants : EC50 (Pseudokirchneriella subcapitata (green algae)): > 114 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201
Remarks: Based on data from similar materials

NOEC (Pseudokirchneriella subcapitata (green algae)): 13.2 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201
Remarks: Based on data from similar materials

Difluoromethane:

Toxicity to fish : LC50 (Fish): 1,507 mg/l
Exposure time: 96 h

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia (water flea)): 652 mg/l
Exposure time: 48 h

Toxicity to algae/aquatic plants : EC50 (algae): 142 mg/l
Exposure time: 96 h

Toxicity to fish (Chronic toxicity) : NOEC: 65.8 mg/l
Exposure time: 30 d
Species: Fish

12.2 Persistence and degradability

Components:

1,1,1,2-Tetrafluoroethane:

Biodegradability : Result: Not readily biodegradable.

2,3,3,3-Tetrafluoropropene:

Biodegradability : Result: Not readily biodegradable.
Method: OECD Test Guideline 301F

Pentafluoroethane:

Biodegradability : Result: Not readily biodegradable.
Biodegradation: 5 %
Exposure time: 28 d
Method: OECD Test Guideline 301D

Difluoromethane:

Biodegradability : Result: Not readily biodegradable.
Biodegradation: 5 %

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



Opteon™ XP40 (R-449A) Refrigerant

Version	Revision Date:	SDS Number:	Date of last issue: 18.09.2018
4.12	26.03.2019	1349448-00043	Date of first issue: 27.02.2017

Exposure time: 28 d
Method: OECD Test Guideline 301D

12.3 Bioaccumulative potential

Components:

1,1,1,2-Tetrafluoroethane:

Partition coefficient: n-octanol/water : log Pow: 1.06

2,3,3,3-Tetrafluoropropene:

Bioaccumulation : Remarks: No bioaccumulation is to be expected (log Pow <= 4).

Pentafluoroethane:

Partition coefficient: n-octanol/water : Pow: 1.48 (25 °C)

Difluoromethane:

Partition coefficient: n-octanol/water : log Pow: 0.714

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

Product:

Assessment : This mixture contains no substance considered to be persistent, bioaccumulating and toxic (PBT).. This mixture contains no substance considered to be very persistent and very bioaccumulating (vPvB)..

12.6 Other adverse effects

Global warming potential

Regulation (EU) No 517/2014 on fluorinated greenhouse gases

Product:

100-year global warming potential: 1,397

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product : Dispose of in accordance with local regulations. According to the European Waste Catalogue, Waste Codes are not product specific, but application specific. Waste codes should be assigned by the user, preferably in

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



Opteon™ XP40 (R-449A) Refrigerant

Version	Revision Date:	SDS Number:	Date of last issue: 18.09.2018
4.12	26.03.2019	1349448-00043	Date of first issue: 27.02.2017

discussion with the waste disposal authorities.

Contaminated packaging : Empty containers should be taken to an approved waste handling site for recycling or disposal.
Empty pressure vessels should be returned to the supplier.
If not otherwise specified: Dispose of as unused product.

SECTION 14: Transport information

14.1 UN number

ADN : UN 1078
ADR : UN 1078
RID : UN 1078
IMDG : UN 1078
IATA : UN 1078

14.2 UN proper shipping name

ADN : REFRIGERANT GAS, N.O.S.
(1,1,1,2-Tetrafluoroethane, 2,3,3,3-Tetrafluoropropene)
ADR : REFRIGERANT GAS, N.O.S.
(1,1,1,2-Tetrafluoroethane, 2,3,3,3-Tetrafluoropropene)
RID : REFRIGERANT GAS, N.O.S.
(1,1,1,2-Tetrafluoroethane, 2,3,3,3-Tetrafluoropropene)
IMDG : REFRIGERANT GAS, N.O.S.
(1,1,1,2-Tetrafluoroethane, 2,3,3,3-Tetrafluoropropene)
IATA : Refrigerant gas, n.o.s.
(1,1,1,2-Tetrafluoroethane, 2,3,3,3-Tetrafluoropropene)

14.3 Transport hazard class(es)

ADN : 2
ADR : 2
RID : 2
IMDG : 2.2
IATA : 2.2

14.4 Packing group

ADN
Packing group : Not assigned by regulation
Classification Code : 2A
Hazard Identification Number : 20
Labels : 2.2
ADR
Packing group : Not assigned by regulation
Classification Code : 2A

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



Opteon™ XP40 (R-449A) Refrigerant

Version 4.12 Revision Date: 26.03.2019 SDS Number: 1349448-00043 Date of last issue: 18.09.2018
Date of first issue: 27.02.2017

Hazard Identification Number : 20
Labels : 2.2
Tunnel restriction code : (C/E)

RID

Packing group : Not assigned by regulation
Classification Code : 2A
Hazard Identification Number : 20
Labels : 2.2 ((13))

IMDG

Packing group : Not assigned by regulation
Labels : 2.2
EmS Code : F-C, S-V

IATA (Cargo)

Packing instruction (cargo aircraft) : 200
Packing group : Not assigned by regulation
Labels : Non-flammable, non-toxic Gas

IATA (Passenger)

Packing instruction (passenger aircraft) : 200
Packing group : Not assigned by regulation
Labels : Non-flammable, non-toxic Gas

14.5 Environmental hazards

ADN

Environmentally hazardous : no

ADR

Environmentally hazardous : no

RID

Environmentally hazardous : no

IMDG

Marine pollutant : no

14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

14.7 Transport in bulk according to IMO instruments

Remarks : Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59) : Not applicable

REACH - List of substances subject to authorisation : Not applicable

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



Opteon™ XP40 (R-449A) Refrigerant

Version	Revision Date:	SDS Number:	Date of last issue: 18.09.2018
4.12	26.03.2019	1349448-00043	Date of first issue: 27.02.2017

(Annex XIV)

Regulation (EC) No 1005/2009 on substances that deplete the ozone layer : Not applicable

Regulation (EC) No 850/2004 on persistent organic pollutants : Not applicable

Regulation (EC) No 649/2012 of the European Parliament and the Council concerning the export and import of dangerous chemicals : Not applicable

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, preparations and articles (Annex XVII) : Not applicable

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.
Not applicable

15.2 Chemical safety assessment

Chemical Safety Assessments have been carried out for these substances.

SECTION 16: Other information

Other information : Opteon™ and any associated logos are trademarks or copyrights of The Chemours Company FC, LLC. Chemours™ and the Chemours Logo are trademarks of The Chemours Company. Before use read Chemours safety information. For further information contact the local Chemours office or nominated distributors.

Items where changes have been made to the previous version are highlighted in the body of this document by two vertical lines.

Full text of H-Statements

H220 : Extremely flammable gas.
H280 : Contains gas under pressure; may explode if heated.

Full text of other abbreviations

Flam. Gas : Flammable gases
Press. Gas : Gases under pressure
GB EH40 : UK. EH40 WEL - Workplace Exposure Limits
GB EH40 / TWA : Long-term exposure limit (8-hour TWA reference period)

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - European Agreement concerning the International Carriage of Dangerous Goods by Road; AICS - Australian Inventory of Chemical Substances; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



Opteon™ XP40 (R-449A) Refrigerant

Version	Revision Date:	SDS Number:	Date of last issue: 18.09.2018
4.12	26.03.2019	1349448-00043	Date of first issue: 27.02.2017

- Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

Further information

Sources of key data used to compile the Safety Data Sheet : Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agency, <http://echa.europa.eu/>

Classification of the mixture:

Press. Gas Liquefied gas H280

Classification procedure:

Based on product data or assessment

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

GB / EN