according to Regulation (EC) No. 1907/2006



Opteon™ XP44 (R-452A) Refrigerant

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 24.04.2018

 4.9
 21.09.2018
 1348613-00040
 Date of first issue: 27.02.2017

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : Opteon™ XP44 (R-452A) Refrigerant

SDS-Identcode : 130000132272

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Sub- : Refrigerant

stance/Mixture

Recommended restrictions

on use

1.3 Details of the supplier of the safety data sheet

Company : Chemours Netherlands B.V.

Baanhoekweg 22

3313 LA Dordrecht Netherlands

For professional and industrial installation and use only.

Telephone : +31-(0)-78-630-1011

Telefax : +31-78-6163737

E-mail address of person responsible for the SDS

: sds-support@chemours.com

1.4 Emergency telephone number

+(44)-870-8200418 (CHEMTREC - Recommended)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Gases under pressure, Liquefied gas H280: Contains gas under pressure; may explode if

heated.

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms

 \Diamond

Signal word : Warning

Hazard statements : H280 Contains gas under pressure; may explode if heated.

according to Regulation (EC) No. 1907/2006



Opteon™ XP44 (R-452A) Refrigerant

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 24.04.2018

 4.9
 21.09.2018
 1348613-00040
 Date of first issue: 27.02.2017

Precautionary statements : Storage:

P410 + P403 Protect from sunlight. Store in a well-ventilated

place.

Additional Labelling

Contains fluorinated greenhouse gases. (HFC-125, HFC-32)

2.3 Other hazards

This mixture contains no substance considered to be persistent, bioaccumulating and toxic (PBT). This mixture contains no substance considered to be very persistent and very bioaccumulating (vPvB).

Vapours are heavier than air and can cause suffocation by reducing oxygen available for breathing.

Misuse or intentional inhalation abuse may cause death without warning symptoms, due to cardiac effects.

Rapid evaporation of the product may cause frostbite.

May displace oxygen and cause rapid suffocation.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Chemical nature : Fluorinated hydrocarbons

Components

| Chemical name | CAS-No. | Classification | Concentration |
|-----------------------------|---------------------|----------------------|---------------|
| | EC-No. | | (% w/w) |
| | Index-No. | | |
| | Registration number | | |
| Pentafluoroethane* | 354-33-6 | Press. Gas Liquefied | 59 |
| | 206-557-8 | gas; H280 | |
| | 01-2119485636-25 | | |
| 2,3,3,3-Tetrafluoropropene* | 754-12-1 | Flam. Gas 1; H220 | 30 |
| | 468-710-7 | Press. Gas Liquefied | |
| | 01-0000019665-61 | gas; H280 | |
| Difluoromethane* | 75-10-5 | Flam. Gas 1; H220 | 11 |
| | 200-839-4 | Press. Gas Liquefied | |
| | 01-2119471312-47 | gas; H280 | |

^{*} Voluntarily-disclosed non-hazardous substance For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General advice : In the case of accident or if you feel unwell, seek medical ad-

vice immediately.

When symptoms persist or in all cases of doubt seek medical

advice.

according to Regulation (EC) No. 1907/2006



Opteon™ XP44 (R-452A) Refrigerant

Version Revision Date: SDS Number: Date of last issue: 24.04.2018 4.9 21.09.2018 1348613-00040 Date of first issue: 27.02.2017

Protection of first-aiders : No special precautions are necessary for first aid responders.

If inhaled : If inhaled, remove to fresh air.

Get medical attention if symptoms occur.

In case of skin contact : Thaw frosted parts with lukewarm water. Do not rub affected

area

Get medical attention immediately.

In case of eye contact : Get medical attention immediately.

If swallowed : Ingestion is not considered a potential route of exposure.

4.2 Most important symptoms and effects, both acute and delayed

Symptoms : May cause cardiac arrhythmia.

Other symptoms potentially related to misuse or inhalation

abuse are

Cardiac sensitisation Anaesthetic effects Light-headedness

Dizziness confusion

Lack of coordination

Drowsiness Unconsciousness

Risks : Contact with liquid or refrigerated gas can cause cold burns

and frostbite.

4.3 Indication of any immediate medical attention and special treatment needed

Treatment : Treat symptomatically and supportively.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media : Not applicable

Will not burn

Not applicable

Unsuitable extinguishing

media Will not burn

5.2 Special hazards arising from the substance or mixture

Specific hazards during fire-

fighting

Exposure to combustion products may be a hazard to health.

If the temperature rises there is danger of the vessels bursting

due to the high vapor pressure.

Hazardous combustion prod: :

ucts

Fluorine compounds Carbon oxides

3/19

according to Regulation (EC) No. 1907/2006



Opteon™ XP44 (R-452A) Refrigerant

Version Revision Date: SDS Number: Date of last issue: 24.04.2018 4.9 21.09.2018 1348613-00040 Date of first issue: 27.02.2017

Hydrogen fluoride carbonyl fluoride

5.3 Advice for firefighters

Special protective equipment :

for firefighters

Wear self-contained breathing apparatus for firefighting if nec-

essary. Use personal protective equipment.

Specific extinguishing meth-

ods

Use extinguishing measures that are appropriate to local cir-

cumstances and the surrounding environment. Fight fire remotely due to the risk of explosion. Use water spray to cool unopened containers.

Remove undamaged containers from fire area if it is safe to do

SO.

Evacuate area.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Evacuate personnel to safe areas.

Avoid skin contact with leaking liquid (danger of frostbite).

Ventilate the area.

Follow safe handling advice and personal protective equip-

ment recommendations.

6.2 Environmental precautions

Environmental precautions : Prevent further leakage or spillage if safe to do so.

Retain and dispose of contaminated wash water.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Ventilate the area.

Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to deter-

mine which regulations are applicable.

Sections 13 and 15 of this SDS provide information regarding

certain local or national requirements.

6.4 Reference to other sections

See sections: 7, 8, 11, 12 and 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Technical measures : Use equipment rated for cylinder pressure. Use a backflow

preventative device in piping. Close valve after each use and

when empty.

Local/Total ventilation : Use only with adequate ventilation.

according to Regulation (EC) No. 1907/2006



Opteon™ XP44 (R-452A) Refrigerant

Version Revision Date: SDS Number: Date of last issue: 24.04.2018 4.9 21.09.2018 1348613-00040 Date of first issue: 27.02.2017

Advice on safe handling

: Handle in accordance with good industrial hygiene and safety practice, based on the results of the workplace exposure assessment

Wear cold insulating gloves/ face shield/ eye protection.

Prevent backflow into the gas tank.

Open the valves slowly to prevent pressure surges.

Close valve after each use and when empty. Do NOT change

or force fit connections.

Prevent the intrusion of water into the gas tank. Keep away from heat and sources of ignition.

Take precautionary measures against static discharges.

Take care to prevent spills, waste and minimize release to the

environment.

Avoid breathing gas.

Valve protection caps and valve outlet threaded plugs must remain in place unless container is secured with valve outlet piped to use point.

Use a check valve or trap in the discharge line to prevent haz-

ardous back flow into the cylinder.

Use a pressure reducing regulator when connecting cylinder

to lower pressure (<3000 psig) piping or systems.

Never attempt to lift cylinder by its cap. Do not drag, slide or roll cylinders.

Use a suitable hand truck for cylinder movement.

Hygiene measures

Ensure that eye flushing systems and safety showers are located close to the working place. When using do not eat, drink or smoke. Wash contaminated clothing before re-use.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers

Cylinders should be stored upright and firmly secured to prevent falling or being knocked over. Separate full containers from empty containers. Do not store near combustible materials. Avoid area where salt or other corrosive materials are present. Keep in properly labelled containers. Keep in a cool, well-ventilated place. Keep away from direct sunlight. Store in accordance with the particular national regulations.

Advice on common storage

Do not store with the following product types:

Self-reactive substances and mixtures

Organic peroxides Oxidizing agents Flammable liquids Flammable solids Pyrophoric liquids Pyrophoric solids

Self-heating substances and mixtures

Substances and mixtures, which in contact with water, emit

flammable gases

Explosives

Acutely toxic substances and mixtures

Substances and mixtures with chronic toxicity

according to Regulation (EC) No. 1907/2006



Opteon™ XP44 (R-452A) Refrigerant

Version Revision Date: SDS Number: Date of last issue: 24.04.2018 21.09.2018 1348613-00040 Date of first issue: 27.02.2017 4.9

Storage period : > 10 yr

Recommended storage tem- : < 52 °C

perature

age stability

Further information on stor- : The product has an indefinite shelf life when stored properly.

7.3 Specific end use(s)

Specific use(s) : No data available

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

| Substance name | End Use | Exposure routes | Potential health effects | Value |
|--------------------------------|-----------|-----------------|----------------------------|-------------|
| Pentafluoroethane | Workers | Inhalation | Long-term systemic effects | 16444 mg/m3 |
| | Consumers | Inhalation | Long-term systemic effects | 1753 mg/m3 |
| 2,3,3,3- Tetrafluoropropene | Workers | Inhalation | Long-term systemic effects | 950 mg/m3 |
| Difluoromethane | Workers | Inhalation | Long-term systemic effects | 7035 mg/m3 |
| | Consumers | Inhalation | Long-term systemic effects | 750 mg/m3 |

Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

| Substance name | Environmental Compartment | Value |
|----------------------------|---------------------------|-----------------|
| Pentafluoroethane | Fresh water | 0.1 mg/l |
| | Intermittent use/release | 1 mg/l |
| | Fresh water sediment | 0.6 mg/kg |
| 2,3,3,3-Tetrafluoropropene | Fresh water | 0.1 mg/l |
| | Intermittent use/release | 1 mg/l |
| | Fresh water sediment | 1.77 mg/kg dry |
| | | weight (d.w.) |
| | Soil | 1.54 mg/kg dry |
| | | weight (d.w.) |
| | Marine water | 0.01 mg/l |
| | Marine sediment | 0.178 mg/kg dry |
| | | weight (d.w.) |
| Difluoromethane | Fresh water | 0.142 mg/l |
| | Intermittent use/release | 1.42 mg/l |
| | Fresh water sediment | 0.534 mg/kg |

according to Regulation (EC) No. 1907/2006



Opteon™ XP44 (R-452A) Refrigerant

Version Revision Date: SDS Number: Date of last issue: 24.04.2018 4.9 21.09.2018 1348613-00040 Date of first issue: 27.02.2017

8.2 Exposure controls

Engineering measures

Ensure adequate ventilation, especially in confined areas. Minimize workplace exposure concentrations.

Personal protective equipment

Eye protection : Wear the following personal protective equipment:

Chemical resistant goggles must be worn.

Face-shield

Hand protection

Material : Low temperature resistant gloves

Remarks : Choose gloves to protect hands against chemicals depending

on the concentration and quantity of the hazardous substance and specific to place of work. For special applications, we recommend clarifying the resistance to chemicals of the aforementioned protective gloves with the glove manufacturer. Wash hands before breaks and at the end of workday. Breakthrough time is not determined for the product. Change

gloves often!

Skin and body protection : Skin should be washed after contact.

Respiratory protection : Use respiratory protection unless adequate local exhaust

ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines.

Filter type : Organic gas and low boiling vapour type (AX)

Protective measures : Wear cold insulating gloves/ face shield/ eye protection.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance : Liquefied gas

Colour : clear, colourless

Odour : slight, ether-like

Odour Threshold : No data available

pH : No data available

Melting point/freezing point : No data available

Initial boiling point and boiling :

range

< -47.00 °C

Flash point : Not applicable

according to Regulation (EC) No. 1907/2006



Opteon™ XP44 (R-452A) Refrigerant

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 24.04.2018

 4.9
 21.09.2018
 1348613-00040
 Date of first issue: 27.02.2017

Evaporation rate : > 1

(CCL4=1.0)

Flammability (solid, gas) : Will not burn

Upper explosion limit / Upper

flammability limit

Upper flammability limit Method: ASTM E681

None.

Lower explosion limit / Lower

flammability limit

Lower flammability limit Method: ASTM E681

None.

Vapour pressure : 13,159 hPa (25 °C)

Relative vapour density : 3.64

(Air = 1.0)

Relative density : 1.13 (25 °C)

Solubility(ies)

Water solubility : No data available

Partition coefficient: n-

octanol/water

: Not applicable

Auto-ignition temperature : No data available

Decomposition temperature : No data available

Viscosity

Viscosity, kinematic : Not applicable

Explosive properties : Not explosive

Oxidizing properties : The substance or mixture is not classified as oxidizing.

9.2 Other information

Particle size : Not applicable

SECTION 10: Stability and reactivity

10.1 Reactivity

Not classified as a reactivity hazard.

10.2 Chemical stability

Stable if used as directed. Follow precautionary advice and avoid incompatible materials and conditions.

10.3 Possibility of hazardous reactions

Hazardous reactions : Can react with strong oxidizing agents.

according to Regulation (EC) No. 1907/2006



Opteon™ XP44 (R-452A) Refrigerant

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 24.04.2018

 4.9
 21.09.2018
 1348613-00040
 Date of first issue: 27.02.2017

10.4 Conditions to avoid

Conditions to avoid : Heat, flames and sparks.

10.5 Incompatible materials

Materials to avoid : Oxidizing agents

10.6 Hazardous decomposition products

No hazardous decomposition products are known.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Information on likely routes of : Inhalation

exposure Skin contact

Eye contact

Acute toxicity

Not classified based on available information.

Components:

Pentafluoroethane:

Acute inhalation toxicity : LC0 (Rat): > 800000 ppm

Exposure time: 4 h Test atmosphere: gas

Method: OECD Test Guideline 403

2,3,3,3-Tetrafluoropropene:

Acute inhalation toxicity : LC50 (Rat): > 405000 ppm

Exposure time: 4 h Test atmosphere: gas

Lowest observed adverse effect concentration (Dog): >

120000 ppm

Test atmosphere: gas

Symptoms: Cardiac sensitisation

No observed adverse effect concentration (Dog): 120000 ppm

Test atmosphere: gas

Symptoms: Cardiac sensitisation

Cardiac sensitisation threshold limit (Dog): > 559,509 mg/m3

Test atmosphere: gas

Symptoms: Cardiac sensitisation

Difluoromethane:

Acute inhalation toxicity : LC50 (Rat): > 520000 ppm

Exposure time: 4 h

according to Regulation (EC) No. 1907/2006



Opteon™ XP44 (R-452A) Refrigerant

Version Revision Date: SDS Number: Date of last issue: 24.04.2018 4.9 21.09.2018 1348613-00040 Date of first issue: 27.02.2017

Test atmosphere: gas

Lowest observed adverse effect concentration (Dog): >

350000 ppm

Symptoms: Cardiac sensitisation

No observed adverse effect concentration (Dog): 350000 ppm

Symptoms: Cardiac sensitisation

Cardiac sensitisation threshold limit (Dog): > 735,000 mg/m3

Symptoms: Cardiac sensitisation

Skin corrosion/irritation

Not classified based on available information.

Components:

2,3,3,3-Tetrafluoropropene:

Species : Not tested on animals Result : No skin irritation

Difluoromethane:

Species : Not tested on animals Result : No skin irritation

Serious eye damage/eye irritation

Not classified based on available information.

Components:

2,3,3,3-Tetrafluoropropene:

Species : Not tested on animals Result : No eye irritation

Difluoromethane:

Species : Not tested on animals Result : No eye irritation

Respiratory or skin sensitisation

Skin sensitisation

Not classified based on available information.

Respiratory sensitisation

Not classified based on available information.

Components:

2,3,3,3-Tetrafluoropropene:

Exposure routes : Skin contact

Species : Not tested on animals

Result : negative

according to Regulation (EC) No. 1907/2006



Opteon™ XP44 (R-452A) Refrigerant

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 24.04.2018

 4.9
 21.09.2018
 1348613-00040
 Date of first issue: 27.02.2017

Difluoromethane:

Exposure routes : Skin contact

Species : Not tested on animals

Result : negative

Species : Not tested on animals

Result : negative

Germ cell mutagenicity

Not classified based on available information.

Components:

Pentafluoroethane:

Genotoxicity in vitro : Test Type: Chromosome aberration test in vitro

Method: OECD Test Guideline 473

Result: negative

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo

cytogenetic assay) Species: Mouse

Application Route: inhalation (gas) Method: OECD Test Guideline 474

Result: negative

2,3,3,3-Tetrafluoropropene:

Germ cell mutagenicity- As-

sessment

Weight of evidence does not support classification as a germ

cell mutagen.

Difluoromethane:

Germ cell mutagenicity- As-

sessment

Weight of evidence does not support classification as a germ

cell mutagen.

Carcinogenicity

Not classified based on available information.

Components:

2,3,3,3-Tetrafluoropropene:

Carcinogenicity - Assess-

Weight of evidence does not support classification as a car-

ment cinogen

Reproductive toxicity

Not classified based on available information.

Components:

Pentafluoroethane:

Effects on fertility : Test Type: One-generation reproduction toxicity study

Species: Rat

according to Regulation (EC) No. 1907/2006



Opteon™ XP44 (R-452A) Refrigerant

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 24.04.2018

 4.9
 21.09.2018
 1348613-00040
 Date of first issue: 27.02.2017

Application Route: inhalation (vapour)

Result: negative

Remarks: Based on data from similar materials

Effects on foetal develop-

ment

Test Type: Embryo-foetal development

Species: Rat

Application Route: inhalation (gas) Method: OECD Test Guideline 414

Result: negative

2,3,3,3-Tetrafluoropropene:

Reproductive toxicity - As-

sessment

Weight of evidence does not support classification for repro-

ductive toxicity

Difluoromethane:

Reproductive toxicity - As-

sessment

Weight of evidence does not support classification for repro-

ductive toxicity, Based on data from similar materials

STOT - single exposure

Not classified based on available information.

STOT - repeated exposure

Not classified based on available information.

Components:

2,3,3,3-Tetrafluoropropene:

Assessment : No significant health effects observed in animals at concentra-

tions of 250 ppmV/6h/d or less.

Difluoromethane:

Assessment : No significant health effects observed in animals at concentra-

tions of 250 ppmV/6h/d or less.

Repeated dose toxicity

Components:

Pentafluoroethane:

Species : Rat

NOAEL : >= 50000 ppm Application Route : inhalation (gas) Exposure time : 13 Weeks

Method : OECD Test Guideline 413

2,3,3,3-Tetrafluoropropene:

Species : Rat

NOAEL : 50000 ppm LOAEL : >50000 ppm Application Route : inhalation (gas)

Exposure time : 90 d

according to Regulation (EC) No. 1907/2006



Opteon™ XP44 (R-452A) Refrigerant

Version Revision Date: SDS Number: Date of last issue: 24.04.2018 4.9 21.09.2018 1348613-00040 Date of first issue: 27.02.2017

Method : OECD Test Guideline 413

Remarks : No significant adverse effects were reported

Difluoromethane:

Species : Rat

NOAEL : 49100 ppm Application Route : inhalation (gas)

Exposure time : 90 d

Remarks : No significant adverse effects were reported

Aspiration toxicity

Not classified based on available information.

SECTION 12: Ecological information

12.1 Toxicity

Components:

Pentafluoroethane:

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 450 mg/l

Exposure time: 96 h

Method: Directive 67/548/EEC, Annex V, C.1. Remarks: Based on data from similar materials

Toxicity to daphnia and other :

aquatic invertebrates

EC50 (Daphnia magna (Water flea)): 980 mg/l

Exposure time: 48 h

Method: Directive 67/548/EEC, Annex V, C.2. Remarks: Based on data from similar materials

Toxicity to algae : EC50 (Pseudokirchneriella subcapitata (green algae)): > 114

mg/l

Exposure time: 72 h

Method: OECD Test Guideline 201

Remarks: Based on data from similar materials

NOEC (Pseudokirchneriella subcapitata (green algae)): 13.2

mg/l

Exposure time: 72 h

Method: OECD Test Guideline 201

Remarks: Based on data from similar materials

2,3,3,3-Tetrafluoropropene:

Toxicity to fish : LC50 (Cyprinus carpio (Carp)): > 197 mg/l

Exposure time: 96 h

Toxicity to daphnia and other :

aquatic invertebrates

EC50 (Daphnia magna (Water flea)): > 100 mg/l

Exposure time: 48 h

Toxicity to algae : NOEC (algae): > 100 mg/l

Exposure time: 72 h

according to Regulation (EC) No. 1907/2006



Opteon™ XP44 (R-452A) Refrigerant

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 24.04.2018

 4.9
 21.09.2018
 1348613-00040
 Date of first issue: 27.02.2017

Difluoromethane:

Toxicity to fish : LC50 (Fish): 1,507 mg/l

Exposure time: 96 h

Toxicity to daphnia and other :

aquatic invertebrates

EC50 (Daphnia (water flea)): 652 mg/l

Exposure time: 48 h

Toxicity to algae : EC50 (algae): 142 mg/l

Exposure time: 96 h

Toxicity to fish (Chronic tox-

icity)

NOEC: 65.8 mg/l Exposure time: 30 d

Species: Fish

12.2 Persistence and degradability

Components:

Pentafluoroethane:

Biodegradability : Result: Not readily biodegradable.

Biodegradation: 5 % Exposure time: 28 d

Method: OECD Test Guideline 301D

2,3,3,3-Tetrafluoropropene:

Biodegradability : Result: Not readily biodegradable.

Method: OECD Test Guideline 301F

Difluoromethane:

Biodegradability : Result: Not readily biodegradable.

Biodegradation: 5 % Exposure time: 28 d

Method: OECD Test Guideline 301D

12.3 Bioaccumulative potential

Components:

Pentafluoroethane:

Partition coefficient: n-

octanol/water

Pow: 1.48 (25 °C)

2,3,3,3-Tetrafluoropropene:

Bioaccumulation : Remarks: No bioaccumulation is to be expected (log Pow <=

4).

Difluoromethane:

Partition coefficient: n-

octanol/water

log Pow: 0.714

according to Regulation (EC) No. 1907/2006



Opteon™ XP44 (R-452A) Refrigerant

Version Revision Date: SDS Number: Date of last issue: 24.04.2018 4.9 21.09.2018 1348613-00040 Date of first issue: 27.02.2017

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

Product:

Assessment : This mixture contains no substance considered to be persis-

tent, bioaccumulating and toxic (PBT).. This mixture contains no substance considered to be very persistent and very bio-

accumulating (vPvB)..

12.6 Other adverse effects

Global warming potential

Regulation (EU) No 517/2014 on fluorinated greenhouse gases

Product:

100-year global warming potential: 2,140

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product : Dispose of in accordance with local regulations.

According to the European Waste Catalogue, Waste Codes

are not product specific, but application specific.

Waste codes should be assigned by the user, preferably in

discussion with the waste disposal authorities.

Contaminated packaging : Empty containers should be taken to an approved waste han-

dling site for recycling or disposal.

Empty pressure vessels should be returned to the supplier. If not otherwise specified: Dispose of as unused product.

SECTION 14: Transport information

14.1 UN number

ADN : UN 1078
ADR : UN 1078
RID : UN 1078
IMDG : UN 1078
IATA : UN 1078

14.2 UN proper shipping name

ADN : REFRIGERANT GAS, N.O.S.

(Pentafluoroethane, 2,3,3,3-Tetrafluoropropene)

ADR : REFRIGERANT GAS, N.O.S.

(Pentafluoroethane, 2,3,3,3-Tetrafluoropropene)

according to Regulation (EC) No. 1907/2006



Opteon™ XP44 (R-452A) Refrigerant

Version Revision Date: SDS Number: Date of last issue: 24.04.2018 4.9 21.09.2018 1348613-00040 Date of first issue: 27.02.2017

RID : REFRIGERANT GAS, N.O.S.

(Pentafluoroethane, 2,3,3,3-Tetrafluoropropene)

IMDG : REFRIGERANT GAS, N.O.S.

(Pentafluoroethane, 2,3,3,3-Tetrafluoropropene)

IATA : Refrigerant gas, n.o.s.

(Pentafluoroethane, 2,3,3,3-Tetrafluoropropene)

14.3 Transport hazard class(es)

ADN : 2
ADR : 2
RID : 2
IMDG : 2.2
IATA : 2.2

14.4 Packing group

ADN

Packing group : Not assigned by regulation

Classification Code : 2A Hazard Identification Number : 20 Labels : 2.2

ADR

Packing group : Not assigned by regulation

Classification Code : 2A
Hazard Identification Number : 20
Labels : 2.2
Tunnel restriction code : (C/E)

RID

Packing group : Not assigned by regulation

Classification Code : 2A Hazard Identification Number : 20 Labels : 2.2 ((13))

IMDG

Packing group : Not assigned by regulation

Labels : 2.2 EmS Code : F-C, S-V

IATA (Cargo)

Packing instruction (cargo : 200

aircraft)

Packing group : Not assigned by regulation Labels : Non-flammable, non-toxic Gas

IATA (Passenger)

Packing instruction (passen- : 200

ger aircraft)

Packing group : Not assigned by regulation
Labels : Non-flammable, non-toxic Gas

14.5 Environmental hazards

according to Regulation (EC) No. 1907/2006



Opteon™ XP44 (R-452A) Refrigerant

Version Revision Date: SDS Number: Date of last issue: 24.04.2018 4.9 21.09.2018 1348613-00040 Date of first issue: 27.02.2017

ADN

Environmentally hazardous : no

ADR

Environmentally hazardous : no

RID

Environmentally hazardous : no

IMDG

Marine pollutant : no

14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Remarks : Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Not applicable

Not applicable

REACH - Candidate List of Substances of Very High

REACH - List of substances subject to authorisation

Concern for Authorisation (Article 59).

(Annex XIV)

Regulation (EC) No 1005/2009 on substances that de- : Not applicable

plete the ozone layer

Regulation (EC) No 850/2004 on persistent organic pol- : Not applicable

lutants

Regulation (EC) No 649/2012 of the European Parlia- : Not applicable

Regulation (EC) No 649/2012 of the European Parliament and the Council concerning the export and import

of dangerous chemicals

EACH - Restrictions on the manufacture, placing on : Not applicable

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances,

preparations and articles (Annex XVII)

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.

Not applicable

15.2 Chemical safety assessment

Chemical Safety Assessments have been carried out for these substances.

SECTION 16: Other information

according to Regulation (EC) No. 1907/2006



Opteon™ XP44 (R-452A) Refrigerant

Version Revision Date: SDS Number: Date of last issue: 24.04.2018 4.9 21.09.2018 1348613-00040 Date of first issue: 27.02.2017

Other information : Opteon™ and any associated logos are trademarks or copy-

rights of The Chemours Company FC, LLC.

Chemours™ and the Chemours Logo are trademarks of The

Chemours Company.

Before use read Chemours safety information.

For further information contact the local Chemours office or

nominated distributors.

Items where changes have been made to the previous version are highlighted in the body of this document by two vertical

lines.

Full text of H-Statements

H220 : Extremely flammable gas.

H280 : Contains gas under pressure; may explode if heated.

Full text of other abbreviations

Flam. Gas : Flammable gases
Press. Gas : Gases under pressure

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - European Agreement concerning the International Carriage of Dangerous Goods by Road; AICS - Australian Inventory of Chemical Substances; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx -Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx -Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

according to Regulation (EC) No. 1907/2006



Opteon™ XP44 (R-452A) Refrigerant

Version Revision Date: SDS Number: Date of last issue: 24.04.2018 4.9 21.09.2018 1348613-00040 Date of first issue: 27.02.2017

Further information

Sources of key data used to compile the Safety Data

Sheet

Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agen-

cy, http://echa.europa.eu/

Classification of the mixture: Classification procedure:

Press. Gas Liquefied gas H280 Based on product data or assessment

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

GB/EN