

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture
 Name : ACITEST UNIPRO WW
 Product code : 100502100
 Type of product : Detergent

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Use of the substance/mixture : Acidity test for refrigeration oils

1.2.2. Uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet

Supplier

Dehon Service SAS
 26 Avenue du Petit Parc
 94683 VINCENNES Cedex - France
 T 01 43 98 75 00 - F 01 43 98 21 51
ContactFDS@climalife.dehon.com

Other

Climalife Kft Budepesta sucursală Bucuresti Romania
 Bulevardul Hristo Botev, Nr. 28,
 Biroul NR 4, Modulul I
 Bucuresti Sectorul 3 - Romania
ContactFDS@climalife.dehon.com

Other

Dehon Kälte-Fachvertriebs GmbH
 Robert-Bosch-Strasse 14
 40668 MEERBUSCH - Germany
 T 00 49 2150 7073 0 - F 00 49 2150 7073 17
ContactFDS@climalife.dehon.com

Other

Dehon Service Belgium s.a./n.v.
 Avenue Carton de Wiart, 79
 1090 Bruxelles - Belgium
 T 00 32 2 421 01 70 - F 00 32 2 426 96 62
ContactFDS@climalife.dehon.com

Other

Dehon Service Nerderland B.V.
 Van Konijnenburgweg 84
 NL-4612 PL Bergen Op Zoom - Netherlands
 T 00 31 164 212 830 - F 00 31 164 212 831
ContactFDS@climalife.dehon.com

Other

Galco s.a./n.v.
 Avenue Carton de Wiart, 79
 1090 BRUSSELS - Belgium
 T 00 32 2 421 01 84 - F 00 32 2 421 01 84 / 00 32 2 425 38 12
ContactFDS@climalife.dehon.com

Other

Climalife Hongrie Kft
 Villányi út 47
 1118 Budaörs - Hungary
 T (36) 23 431 660 - F (36) 23 431 661
ContactFDS@climalife.dehon.com

Other

Climalife Supplied by Inventec Performance Chemicals Italia SRL
 Via del Lavoro, 10/G
 20874 Busnago MB - Italia
 T +39 39-5973480 - F +39 39-5973490
ContactFDS@climalife.dehon.com

Other

Dehon nordic service
 Östra Hamngatan 50B 3tr
 41109 GÖTEBORG - Sweden
 T 00 46 44 21 58 80 - F 00 46 44 21 58 80
ContactFDS@climalife.dehon.com

Other

Dehon Service Nerderland B.V.
 Van Konijnenburgweg 84
 NL-4612 PL Bergen Op Zoom - Netherlands
 T 00 31 164 212 830 - F 00 31 164 212 831
ContactFDS@climalife.dehon.com

Other

Friogas sa
 Poligono Industrial SEPES
 Parcela 10
 46500 SAGUNTO (Valencia) - Spain
 T 00 34 9 6 266 36 32 - F 00 34 9 6 266 50 25
ContactFDS@climalife.dehon.com

Other

IDS Refrigeration Limited
 22 Apex Court, Woodlands, Bradley Stoke
 BS32 4JT Bristol - United Kingdom
 T 00 44 1179 802520 - F 00 44 1179 802521
ContactFDS@climalife.dehon.com

1.4. Emergency telephone number

Emergency number : +33 (0) 1 72 11 00 03

ACITEST UNIPRO WW

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Country	Organisation/Company	Address	Emergency number	Comment
United Kingdom	National Poisons Information Service (Birmingham Centre) City Hospital	Dudley Road B18 7QH Birmingham	0344 892 0111	

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Eye Dam. 1 H318

Full text of hazard classes and H-statements : see section 16

Adverse physicochemical, human health and environmental effects

Causes skin irritation. May cause an allergic skin reaction. Causes serious eye damage.

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP)



GHS05

Signal word (CLP)

: Danger

Contains

: butan-1-ol; n-butanol

Hazard statements (CLP)

: H318 - Causes serious eye damage.

Precautionary statements (CLP)

: P280 - Wear eye protection, face protection.

P305+P351+P338+P310 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a doctor, a POISON CENTER.

2.3. Other hazards

No additional information available

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
butan-1-ol; n-butanol	(CAS-No.) 71-36-3 (EC-No.) 200-751-6 (EC Index-No.) 603-004-00-6	1 – 5	Flam. Liq. 3, H226 Acute Tox. 4 (Oral), H302 STOT SE 3, H335 Skin Irrit. 2, H315 Eye Dam. 1, H318 STOT SE 3, H336
potassium hydroxide substance with national workplace exposure limit(s) (FR, GB)	(CAS-No.) 1310-58-3 (EC-No.) 215-181-3 (EC Index-No.) 019-002-00-8 (REACH-no) 01-2119487136-33	≤ 0.1	Met. Corr. 1, H290 Acute Tox. 4 (Oral), H302 Skin Corr. 1A, H314 Eye Dam. 1, H318

ACITEST UNIPRO WW

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

ethanol; ethyl alcohol substance with national workplace exposure limit(s) (FR, GB)	(CAS-No.) 64-17-5 (EC-No.) 200-578-6 (EC Index-No.) 603-002-00-5 (REACH-no) 01-2119457610-43	< 0.1	Flam. Liq. 2, H225 Eye Irrit. 2, H319
---	---	-------	--

Specific concentration limits:

Name	Product identifier	Specific concentration limits
potassium hydroxide	(CAS-No.) 1310-58-3 (EC-No.) 215-181-3 (EC Index-No.) 019-002-00-8 (REACH-no) 01-2119487136-33	(0.5 ≤C < 2) Eye Irrit. 2, H319 (0.5 ≤C < 2) Skin Irrit. 2, H315 (2 ≤C < 5) Skin Corr. 1B, H314 (5 ≤C < 100) Skin Corr. 1A, H314

Full text of H-statements: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures after inhalation	: Allow affected person to breathe fresh air. Seek medical attention if ill effect develops.
First-aid measures after skin contact	: Take off contaminated clothing. Immediately rinse with plenty of water. If case of redness or irritation, call a doctor.
First-aid measures after eye contact	: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Consult an eye specialist immediately.
First-aid measures after ingestion	: Do not give the affected person anything to drink, even if he is fully conscious. Do NOT induce vomiting. Immediately call a POISON CENTER/doctor. If possible show him this sheet. Failing this, show him the packaging or label.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects after eye contact	: Serious damage to eyes.
------------------------------------	---------------------------

4.3. Indication of any immediate medical attention and special treatment needed

No additional information available

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media	: Water spray. Dry powder. Foam. Carbon dioxide.
Unsuitable extinguishing media	: Strong water jet.

5.2. Special hazards arising from the substance or mixture

Hazardous decomposition products in case of fire	: Toxic fumes may be released.
--	--------------------------------

5.3. Advice for firefighters

Protection during firefighting	: Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.
--------------------------------	--

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures	: Avoid contact with skin and eyes.
------------------	-------------------------------------

6.1.1. For non-emergency personnel

Emergency procedures	: Evacuate area. Evacuate the danger area.
----------------------	--

6.1.2. For emergency responders

Protective equipment	: Do not attempt to take action without suitable protective equipment.
----------------------	--

ACITEST UNIPRO WW

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Emergency procedures : Stop leak if safe to do so. Contain the spilled material by bunding.

6.2. Environmental precautions

Contain the spilled material by bunding. Avoid release to the environment. Prevent entry to sewers and public waters.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up : Take up liquid spill into absorbent material.
Other information : Dispose of materials or solid residues at an authorized site.

6.4. Reference to other sections

For further information refer to section 8: "Exposure controls/personal protection". For disposal of solid materials or residues refer to section 13 : "Disposal considerations".

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Ensure good ventilation of the work station. Avoid contact with skin and eyes. Wear personal protective equipment. Avoid breathing spray, mist, fume, gas, dust, vapours.
Hygiene measures : Always wash your hands immediately after handling this product, and once again before leaving the workplace. Do not eat, drink or smoke when using this product. Wash contaminated clothing before reuse. Contaminated work clothing should not be allowed out of the workplace.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Keep container tightly closed.
Storage conditions : Store in a well-ventilated place. Keep cool.
Incompatible materials : Strong acids. Strong bases. Strong oxidizing agents.
Special rules on packaging : Keep only in original container.
Packaging materials : Recommended materials Mild steel, Stainless steel. Unsuitable materials: Mild steel, Aluminium, copper, Metals.

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

8.1.1 National occupational exposure and biological limit values

ethanol; ethyl alcohol (64-17-5)	
France - Occupational Exposure Limits	
Local name	Alcool éthylique
VME (OEL TWA)	1900 mg/m ³
VME (OEL TWA) [ppm]	1000 ppm
VLE (OEL Ceiling/STEL)	9500 mg/m ³
VLE (OEL Ceiling/STEL) [ppm]	5000 ppm
Note (FR)	Valeurs recommandées/admises
Regulatory reference	Circulaire du Ministère du travail (réf.: INRS ED 984, 2016)
United Kingdom - Occupational Exposure Limits	
Local name	Ethanol
WEL TWA [1]	1920 mg/m ³

ACITEST UNIPRO WW

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

ethanol; ethyl alcohol (64-17-5)	
WEL TWA [2]	1000 ppm
Regulatory reference	EH40. HSE

potassium hydroxide (1310-58-3)	
France - Occupational Exposure Limits	
Local name	Potassium (hydroxyde de)
VLE (OEL Ceiling/STEL)	2 mg/m ³
United Kingdom - Occupational Exposure Limits	
Local name	Potassium hydroxide
WEL STEL	2 mg/m ³

8.1.2. Recommended monitoring procedures

No additional information available

8.1.3. Air contaminants formed

No additional information available

8.1.4. DNEL and PNEC

No additional information available

8.1.5. Control banding

No additional information available

8.2. Exposure controls

8.2.1. Appropriate engineering controls

Appropriate engineering controls:

Ensure good ventilation of the work station.

8.2.2. Personal protection equipment

8.2.2.1. Eye and face protection

Eye protection:
Safety glasses with side shields

8.2.2.2. Skin protection

Skin and body protection:
Wear suitable protective clothing. Safety foot-wear

Hand protection:
Chemical resistant gloves (according to European standard NF EN 374 or equivalent)

8.2.2.3. Respiratory protection

Respiratory protection:
No special respiratory protection equipment is recommended under normal conditions of use with adequate ventilation

8.2.2.4. Thermal hazards

No additional information available

ACITEST UNIPRO WW

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

8.2.3. Environmental exposure controls

Environmental exposure controls:

Avoid release to the environment.

Other information:

Safety shower. Eye fountain.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Appearance	: Clear.
Colour	: Blue.
Odour	: No data available
Odour threshold	: No data available
pH	: Not applicable
pH solution	: (1%)
Relative evaporation rate (butylacetate=1)	: No data available
Melting point	: No data available
Freezing point	: No data available
Boiling point	: > 100 °C
Flash point	: 73 °C
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Flammability (solid, gas)	: Not applicable
Vapour pressure	: No data available
Relative vapour density at 20 °C	: No data available
Relative density	: No data available
Density	: ≈ 0.91 g/cm ³ (20°C)
Solubility	: In water, material soluble.
Partition coefficient n-octanol/water (Log Pow)	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosive properties	: Not explosive material according to EC criteria.
Oxidising properties	: Non oxidizing material according to EC criteria.
Explosive limits	: No data available

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

High temperature.

10.5. Incompatible materials

Strong acids. Strong bases. Strong oxidizing agents.

ACITEST UNIPRO WW

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

10.6. Hazardous decomposition products

Thermal decomposition generates : Aldehydes, Ketones, Carbon oxides (CO, CO₂).

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity (oral)	: Not classified
Acute toxicity (dermal)	: Not classified
Acute toxicity (inhalation)	: Not classified
Skin corrosion/irritation	: Not classified pH: Not applicable
Serious eye damage/irritation	: Causes serious eye damage. pH: Not applicable
Respiratory or skin sensitisation	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified
Reproductive toxicity	: Not classified
STOT-single exposure	: Not classified

butan-1-ol; n-butanol (71-36-3)

STOT-single exposure	May cause respiratory irritation. May cause drowsiness or dizziness.
----------------------	--

STOT-repeated exposure : Not classified

Aspiration hazard : Not classified

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general	: The product is not considered harmful to aquatic organisms nor to cause long-term adverse effects in the environment.
Hazardous to the aquatic environment, short-term (acute)	: Not classified
Hazardous to the aquatic environment, long-term (chronic)	: Not classified

potassium hydroxide (1310-58-3)

LC50 - Fish [1]	80 mg/l <i>Gambusia affinis</i> (Mosquito fish)
LC50 - Fish [2]	165 mg/l <i>Poecilia reticulata</i>
EC50 - Crustacea [1]	40 – 240 mg/l 48 Hours (<i>Daphnia magna</i>)

12.2. Persistence and degradability

No additional information available

12.3. Bioaccumulative potential

No additional information available

12.4. Mobility in soil

No additional information available

ACITEST UNIPRO WW

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

12.5. Results of PBT and vPvB assessment

Component	
potassium hydroxide (1310-58-3)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII

12.6. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.
Dispose in a safe manner in accordance with local/national regulations.

SECTION 14: Transport information

In accordance with ADR / IMDG / IATA

ADR	IMDG	IATA
14.1. UN number		
Not applicable	Not applicable	Not applicable
14.2. UN proper shipping name		
Not applicable	Not applicable	Not applicable
14.3. Transport hazard class(es)		
Not applicable	Not applicable	Not applicable
14.4. Packing group		
Not applicable	Not applicable	Not applicable
14.5. Environmental hazards		
Not applicable	Not applicable	Not applicable
No supplementary information available		

14.6. Special precautions for user

Overland transport

Not applicable

Transport by sea

Not applicable

Air transport

Not applicable

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

Contains no REACH substances with Annex XVII restrictions

Contains no substance on the REACH candidate list

Contains no REACH Annex XIV substances

ACITEST UNIPRO WW

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Contains no substance subject to Regulation (EU) No 649/2012 of the European Parliament and of the Council of 4 July 2012 concerning the export and import of hazardous chemicals.

Contains no substance subject to Regulation (EU) No 2019/1021 of the European Parliament and of the Council of 20 June 2019 on persistent organic pollutants

15.1.2. National regulations

France

Occupational diseases

Code	Description
RG 84	Conditions caused by liquid organic solvents for professional use: saturated or unsaturated aliphatic or cyclic liquid hydrocarbons and mixtures thereof; liquid halogenated hydrocarbons; nitrated derivatives of aliphatic hydrocarbons; alcohols; glycols, glycol ethers; ketones; aldehydes; aliphatic and cyclic ethers, including tetrahydrofuran; esters; dimethylformamide and dimethylacetamine; acetonitrile and propionitrile; pyridine; dimethylsulfone and dimethylsulfoxide

15.2. Chemical safety assessment

No chemical safety assessment has been carried out

SECTION 16: Other information

Full text of H- and EUH-statements:	
Acute Tox. 4 (Oral)	Acute toxicity (oral), Category 4
Eye Dam. 1	Serious eye damage/eye irritation, Category 1
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2
Flam. Liq. 2	Flammable liquids, Category 2
Flam. Liq. 3	Flammable liquids, Category 3
Met. Corr. 1	Corrosive to metals, Category 1
Skin Corr. 1A	Skin corrosion/irritation, Category 1, Sub-Category 1A
Skin Corr. 1B	Skin corrosion/irritation, Category 1, Sub-Category 1B
Skin Irrit. 2	Skin corrosion/irritation, Category 2
STOT SE 3	Specific target organ toxicity — Single exposure, Category 3, Respiratory tract irritation
STOT SE 3	Specific target organ toxicity — Single exposure, Category 3, Narcosis
H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H290	May be corrosive to metals.
H302	Harmful if swallowed.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.

Safety Data Sheet (SDS), EU

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.