

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Product form : Mixture  
 Name : R-407F (PERFORMAX LT)  
 Product code : 100049400

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

##### 1.2.1. Relevant identified uses

Use of the substance/mixture : Refrigerant

##### 1.2.2. Uses advised against

No additional information available

#### 1.3. Details of the supplier of the safety data sheet

##### Supplier

Dehon Service SAS  
 26 Avenue du Petit Parc  
 94683 VINCENNES Cedex - France  
 T 01 43 98 75 00 - F 01 43 98 21 51  
[ContactFDS@climalife.dehon.com](mailto:ContactFDS@climalife.dehon.com)

##### Other

Climalife Kft Budepesta sucursală Bucuresti Romania  
 Bulevardul Hristo Botev, Nr. 28,  
 Biroul NR 4, Modulul I  
 Bucuresti Sectorul 3 - Romania  
[ContactFDS@climalife.dehon.com](mailto:ContactFDS@climalife.dehon.com)

##### Other

Dehon Kälte-Fachvertriebs GmbH  
 Robert-Bosch-Strasse 14  
 40668 MEERBUSCH - Germany  
 T 00 49 2150 7073 0 - F 00 49 2150 7073 17  
[ContactFDS@climalife.dehon.com](mailto:ContactFDS@climalife.dehon.com)

##### Other

Dehon Service Belgium s.a/n.v.  
 Avenue Carton de Wiart, 79  
 1090 Bruxelles - Belgium  
 T 00 32 2 421 01 70 - F 00 32 2 426 96 62  
[ContactFDS@climalife.dehon.com](mailto:ContactFDS@climalife.dehon.com)

##### Other

Friogas sa  
 Poligono Industrial SEPES  
 Parcela 10  
 46500 SAGUNTO (Valencia) - Spain  
 T 00 34 9 6 266 36 32 - F 00 34 9 6 266 50 25  
[ContactFDS@climalife.dehon.com](mailto:ContactFDS@climalife.dehon.com)

##### Other

Prochimac SA  
 ZI Petits Champs 15  
 CH-1400 Yverdon-les-Bains - Switzerland  
 T 00 41 32 727 36 00 - F 00 41 32 727 36 19  
[ContactFDS@climalife.dehon.com](mailto:ContactFDS@climalife.dehon.com)

##### Other

Climalife Hongrie Kft  
 Villányi út 47  
 1118 Budaörs - Hungary  
 T (36) 23 431 660 - F (36) 23 431 661  
[ContactFDS@climalife.dehon.com](mailto:ContactFDS@climalife.dehon.com)

##### Other

Climalife Supplied by Inventec Performance Chemicals Italia SRL  
 Via del Lavoro, 10/G  
 20874 Busnago MB - Italia  
 T +39 39-5973480 - F +39 39-5973490  
[ContactFDS@climalife.dehon.com](mailto:ContactFDS@climalife.dehon.com)

##### Other

Dehon nordic service  
 Östra Hamngatan 50B 3tr  
 41109 GÖTEBORG - Sweden  
 T 00 46 44 21 58 80 - F 00 46 44 21 58 80  
[ContactFDS@climalife.dehon.com](mailto:ContactFDS@climalife.dehon.com)

##### Other

Dehon Service Nerderland B.V.  
 Van Konijnenburgweg 84  
 NL-4612 PL Bergen Op Zoom - Netherlands  
 T 00 31 164 212 830 - F 00 31 164 212 831  
[ContactFDS@climalife.dehon.com](mailto:ContactFDS@climalife.dehon.com)

##### Other

IDS Refrigeration Limited  
 22 Apex Court, Woodlands, Bradley Stoke  
 BS32 4JT Bristol - United Kingdom  
 T 00 44 1179 802520 - F 00 44 1179 802521  
[ContactFDS@climalife.dehon.com](mailto:ContactFDS@climalife.dehon.com)

##### Other

Galco s.a/n.v.  
 Avenue Carton de Wiart, 79  
 1090 BRUSSELS - Belgium  
 T 00 32 2 421 01 84 - F 00 32 2 421 01 84 / 00 32 2 425 38 12  
[ContactFDS@climalife.dehon.com](mailto:ContactFDS@climalife.dehon.com)

#### 1.4. Emergency telephone number

Emergency number : +33 (0) 1 72 11 00 03

# R-407F (PERFORMAX LT)

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Country	Organisation/Company	Address	Emergency number	Comment
United Kingdom	National Poisons Information Service (Birmingham Centre) City Hospital	Dudley Road B18 7QH Birmingham	0344 892 0111	

## SECTION 2: Hazards identification

### 2.1. Classification of the substance or mixture

#### Classification according to Regulation (EC) No. 1272/2008 [CLP]

Press. Gas (Liq.) H280

Full text of hazard classes and H-statements : see section 16

#### Adverse physicochemical, human health and environmental effects

Vapours are heavier than air and can cause suffocation by reducing oxygen available for breathing. Contact with the liquid may cause frostbite and serious damage to eyes.

### 2.2. Label elements

#### Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP) :



GHS04

Signal word (CLP) : Warning  
Hazard statements (CLP) : H280 - Contains gas under pressure; may explode if heated.  
Precautionary statements (CLP) : P410+P403 - Protect from sunlight. Store in a well-ventilated place.  
Extra phrases : Greenhouse fluorinated gas falling within Kyoto Protocol (GWP=1825).

### 2.3. Other hazards

No additional information available

## SECTION 3: Composition/information on ingredients

### 3.1. Substances

Not applicable

### 3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
1,1,1,2-Tetrafluoroethane	CAS-No.: 811-97-2 EC-No.: 212-377-0 REACH-no: 01-2119459374-33	40	Press. Gas (Liq.), H280
Pentafluoroethane	CAS-No.: 354-33-6 EC-No.: 206-557-8 REACH-no: 01-2119485636-25	30	Press. Gas (Liq.), H280
Difluoromethane	CAS-No.: 75-10-5 EC-No.: 200-839-4 REACH-no: 01-2119471312-47	30	Flam. Gas 1B, H221 Press. Gas (Liq.), H280

Full text of H-statements: see section 16

# R-407F (PERFORMAX LT)

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

### SECTION 4: First aid measures

#### 4.1. Description of first aid measures

First-aid measures after inhalation	: Move the affected person away from the contaminated area and into the fresh air. If you feel unwell, seek medical advice.
First-aid measures after skin contact	: In the event of contact with the liquid: treat resulting frostbite as a burn. Immediately remove contaminated clothing or footwear. Immediately rinse with plenty of water. If skin burns appear, call a doctor immediately.
First-aid measures after eye contact	: Rinse immediately and thoroughly, pulling the eyelids well away from the eye (15 minutes minimum). Consult an eye specialist immediately.
First-aid measures after ingestion	: Not specifically applicable (gas).

#### 4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects	: CNS depression. Narcosis. Cardiac disorders. Lack of oxygen: risk of death.
------------------	---

#### 4.3. Indication of any immediate medical attention and special treatment needed

No additional information available

### SECTION 5: Firefighting measures

#### 5.1. Extinguishing media

Suitable extinguishing media	: All extinguishing agents can be used.
Unsuitable extinguishing media	: None to our knowledge. If there is a fire close by, use suitable extinguishing agents.

#### 5.2. Special hazards arising from the substance or mixture

Explosion hazard	: pressure rise and possible bursting of container. On heating : Toxic and corrosive vapours are released.
------------------	--

#### 5.3. Advice for firefighters

Firefighting instructions	: Use water spray or fog for cooling exposed containers.
Protection during firefighting	: Self-contained breathing apparatus. Complete protective clothing.

### SECTION 6: Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

General measures	: Avoid contact with skin and eyes. Remove all sources of ignition. Do not smoke. Evacuate the danger area. Do not breathe smoke. Stop the leak.
------------------	--

##### 6.1.1. For non-emergency personnel

Emergency procedures	: Evacuate area.
----------------------	------------------

##### 6.1.2. For emergency responders

Emergency procedures	: Evacuate the danger area.
----------------------	-----------------------------

#### 6.2. Environmental precautions

No additional information available

#### 6.3. Methods and material for containment and cleaning up

Other information	: Mechanically ventilate the spillage area.
-------------------	---

#### 6.4. Reference to other sections

For further information refer to section 8: "Exposure controls/personal protection". For disposal of solid materials or residues refer to section 13 : "Disposal considerations".

# R-407F (PERFORMAX LT)

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

### SECTION 7: Handling and storage

#### 7.1. Precautions for safe handling

- Precautions for safe handling : Avoid breathing mist, vapours. Do not get in eyes, on skin, or on clothing. Ventilation. Vapours are heavier than air and may spread along floors. Under certain temperature and pressure conditions may form a flammable mixture in the presence of air.
- Hygiene measures : Do not drink, eat or smoke in the workplace.

#### 7.2. Conditions for safe storage, including any incompatibilities

- Storage conditions : Store : in a cool, well-ventilated area, away from any source of heat, away from any source of ignition.
- Incompatible materials : Strong oxidizing agents. Alkaline hydroxide. Alkaline earth metals. Finely divided metals (Al, Mg, Zn).
- Packaging materials : Recommended materials Stainless steel, Carbon steel. Do not use : Alloys containing more than 2% magnesium, Plastic materials.

#### 7.3. Specific end use(s)

No additional information available

### SECTION 8: Exposure controls/personal protection

#### 8.1. Control parameters

##### 8.1.1. National occupational exposure and biological limit values

Pentafluoroethane (354-33-6)	
EU - Indicative Occupational Exposure Limit (IOEL)	
IOEL TWA	4900 mg/m <sup>3</sup> (recommended)
IOEL TWA [ppm]	1000 ppm (recommended)
Difluoromethane (75-10-5)	
EU - Indicative Occupational Exposure Limit (IOEL)	
IOEL TWA	2200 (recommended)
IOEL TWA [ppm]	1000 ppm (recommended)
1,1,1,2-Tetrafluoroethane (811-97-2)	
United Kingdom - Occupational Exposure Limits	
Local name	1,1,1,2-Tetrafluoroethane (HFC 134a)
WEL TWA (OEL TWA) [1]	4240 mg/m <sup>3</sup>
WEL TWA (OEL TWA) [2]	1000 ppm
Regulatory reference	EH40. HSE

##### 8.1.2. Recommended monitoring procedures

No additional information available

##### 8.1.3. Air contaminants formed

No additional information available

##### 8.1.4. DNEL and PNEC

Pentafluoroethane (354-33-6)	
DNEL/DMEL (Workers)	
Long-term - systemic effects, inhalation	16444 mg/m <sup>3</sup>

# R-407F (PERFORMAX LT)

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Pentafluoroethane (354-33-6)	
<b>DNEL/DMEL (General population)</b>	
Long-term - systemic effects, inhalation	1753 mg/m <sup>3</sup>
<b>PNEC (Water)</b>	
PNEC aqua (freshwater)	0.1 mg/l
PNEC aqua (intermittent, freshwater)	1 mg/l
<b>PNEC (Sediment)</b>	
PNEC sediment (freshwater)	0.6 mg/kg dwt

### 8.1.5. Control banding

No additional information available

## 8.2. Exposure controls

### 8.2.1. Appropriate engineering controls

No additional information available

### 8.2.2. Personal protection equipment

#### 8.2.2.1. Eye and face protection

##### Eye protection:

Safety glasses with side shields

#### 8.2.2.2. Skin protection

##### Skin and body protection:

Majority cotton protective clothing

##### Hand protection:

Leather protective gloves. Nitrile-rubber protective gloves. VITON gloves

#### 8.2.2.3. Respiratory protection

##### Respiratory protection:

In the event of insufficient ventilation: Gas mask with filter type AX. In a confined area : Self-contained breathing apparatus

#### 8.2.2.4. Thermal hazards

No additional information available

### 8.2.3. Environmental exposure controls

No additional information available

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state	: Gas
Appearance	: Liquefied gas.
Colour	: Colourless.
Odour	: slightly ethereal.
Odour threshold	: No data available
pH	: Not applicable
Relative evaporation rate (butylacetate=1)	: No data available
Melting point	: No data available
Freezing point	: No data available
Boiling point	: -45.5 °C
Flash point	: Not applicable
Critical temperature	: 86.05 °C
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available

# R-407F (PERFORMAX LT)

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Flammability (solid, gas)	: Non flammable.
Vapour pressure	: 11.4 bar (20°C)
Vapour pressure at 50 °C	: 24.3 bar (50°C)
Relative vapour density at 20 °C	: No data available
Relative density	: No data available
Density	: 1.139 g/cm <sup>3</sup> (20°C)
Solubility	: Insoluble in water.
Partition coefficient n-octanol/water (Log Pow)	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosive properties	: Not explosive material according to EC criteria.
Oxidising properties	: Non oxidizing material according to EC criteria.
Explosive limits	: No data available

### 9.2. Other information

No additional information available

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

Decomposes on exposure to temperature rise.

### 10.2. Chemical stability

Stable at ambient temperature and under normal conditions of use.

### 10.3. Possibility of hazardous reactions

No information available. No polymerization.

### 10.4. Conditions to avoid

Avoid high temperatures. Avoid naked flame. Heating will cause a rise in pressure with a risk of bursting.

### 10.5. Incompatible materials

Alkalis and caustic products. alkali metals. Alkaline earth metals. Finely divided metals (Al, Mg, Zn). Strong oxidizing agents.

### 10.6. Hazardous decomposition products

On thermal decomposition (pyrolysis), releases : Hydrogen fluoride, Carbon oxides (CO, CO<sub>2</sub>), Fluorinated hydrocarbons, Carbonyl halogenides.

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

Acute toxicity (oral)	: Not classified
Acute toxicity (dermal)	: Not classified
Acute toxicity (inhalation)	: Not classified

#### Pentafluoroethane (354-33-6)

LC50 Inhalation - Rat [ppm]	800000 ppm/4h
-----------------------------	---------------

#### Difluoromethane (75-10-5)

LC50 Inhalation - Rat [ppm]	> 520000 ppm/4h
-----------------------------	-----------------

#### 1,1,1,2-Tetrafluoroethane (811-97-2)

LC50 Inhalation - Rat [ppm]	> 500000 ppm/4h
-----------------------------	-----------------

Skin corrosion/irritation	: Not classified
	pH: Not applicable
Additional information	: Contact with the liquid causes frostbite

# R-407F (PERFORMAX LT)

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Serious eye damage/irritation	: Not classified pH: Not applicable
Additional information	: Contact with the liquefied gas may cause severe ocular lesions
Respiratory or skin sensitisation	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified

### 1,1,1,2-Tetrafluoroethane (811-97-2)

NOAEL (chronic, oral, animal/male, 2 years)	300 mg/kg bodyweight rat
---	--------------------------

Reproductive toxicity	: Not classified
STOT-single exposure	: Not classified
STOT-repeated exposure	: Not classified

### Difluoromethane (75-10-5)

NOAEC (inhalation, rat, gas, 90 days)	50000 ppmv/6h/day
---------------------------------------	-------------------

Aspiration hazard	: Not classified
-------------------	------------------

## SECTION 12: Ecological information

### 12.1. Toxicity

Hazardous to the aquatic environment, short-term (acute)	: Not classified
Hazardous to the aquatic environment, long-term (chronic)	: Not classified

### Pentafluoroethane (354-33-6)

LC50 - Fish [1]	> 100 mg/l 96 Hours (Oncorhynchus mykiss)
EC50 - Crustacea [1]	> 100 mg/l 48 Hours (Daphnia magna)
EC50 72h - Algae [1]	> 114 mg/l 72 Hours (Pseudokirchneriella subcapitata)

### 1,1,1,2-Tetrafluoroethane (811-97-2)

LC50 - Fish [1]	450 mg/l 96 Hours (Oncorhynchus mykiss)
EC50 - Crustacea [1]	980 mg/l 48 Hours (Daphnia magna)
EC50 72h - Algae [1]	> 118 mg/l (Selenastrum capricornutum)

### 12.2. Persistence and degradability

#### Pentafluoroethane (354-33-6)

Persistence and degradability	5 % biodegradation after 28 days.
-------------------------------	-----------------------------------

#### 1,1,1,2-Tetrafluoroethane (811-97-2)

Persistence and degradability	Photodegradation in the air : Half-life in air : 9,7 y. 3 % biodegradation after 28 days.
-------------------------------	---

### 12.3. Bioaccumulative potential

#### Pentafluoroethane (354-33-6)

Partition coefficient n-octanol/water (Log Pow)	1.48
---	------

#### Difluoromethane (75-10-5)

Partition coefficient n-octanol/water (Log Pow)	0.21
---	------

#### 1,1,1,2-Tetrafluoroethane (811-97-2)

Partition coefficient n-octanol/water (Log Pow)	1.06
---	------

# R-407F (PERFORMAX LT)

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

### 12.4. Mobility in soil

#### Pentafluoroethane (354-33-6)

Partition coefficient n-octanol/water (Log Koc) 1.3 – 1.7

#### 1,1,1,2-Tetrafluoroethane (811-97-2)

Partition coefficient n-octanol/water (Log Koc) 1.5

### 12.5. Results of PBT and vPvB assessment

#### Component

1,1,1,2-Tetrafluoroethane (811-97-2)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII
Pentafluoroethane (354-33-6)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII

### 12.6. Other adverse effects

Other adverse effects : Ozone depletion factor ODP (R-11=1) = 0. Total global warming potential (GWP) : 1774.

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

Product/Packaging disposal recommendations : Methods of disposal of packaging. Reuse or recycle following decontamination. Destroy at an authorised site.

Additional information : The user's attention is drawn to the possible existence of specific european, national or local regulations regarding disposal.

## SECTION 14: Transport information

In accordance with ADR / IMDG / IATA / RID

ADR	IMDG	IATA	RID
<b>14.1. UN number</b>			
UN 3163	UN 3163	UN 3163	UN 3163
<b>14.2. UN proper shipping name</b>			
LIQUEFIED GAS, N.O.S. (1,1,1,2-Tetrafluoroethane ; Pentafluoroethane ; Difluoromethane)	LIQUEFIED GAS, N.O.S. (1,1,1,2-Tetrafluoroethane ; Pentafluoroethane ; Difluoromethane)	Liquefied gas, n.o.s. (1,1,1,2-Tetrafluoroethane ; Pentafluoroethane ; Difluoromethane)	LIQUEFIED GAS, N.O.S. (1,1,1,2-Tetrafluoroethane ; Pentafluoroethane ; Difluoromethane)
<b>Transport document description</b>			
UN 3163 LIQUEFIED GAS, N.O.S. (1,1,1,2-Tetrafluoroethane ; Pentafluoroethane ; Difluoromethane), 2.2, (C/E)	UN 3163 LIQUEFIED GAS, N.O.S. (1,1,1,2-Tetrafluoroethane ; Pentafluoroethane ; Difluoromethane), 2.2	UN 3163 Liquefied gas, n.o.s. (1,1,1,2-Tetrafluoroethane ; Pentafluoroethane ; Difluoromethane), 2.2	UN 3163 LIQUEFIED GAS, N.O.S. (1,1,1,2-Tetrafluoroethane ; Pentafluoroethane ; Difluoromethane), 2.2
<b>14.3. Transport hazard class(es)</b>			
2.2	2.2	2.2	2.2



# R-407F (PERFORMAX LT)

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

ADR	IMDG	IATA	RID
			

### 14.4. Packing group

Not applicable	Not applicable	Not applicable	Not applicable
----------------	----------------	----------------	----------------

### 14.5. Environmental hazards


Dangerous for the environment: No	Dangerous for the environment: No Marine pollutant: No	Dangerous for the environment: No	Dangerous for the environment: No
-----------------------------------	---	-----------------------------------	-----------------------------------

No supplementary information available

### 14.6. Special precautions for user

#### Overland transport

Classification code (ADR)	: 2A
Special provisions (ADR)	: 274, 660, 662
Limited quantities (ADR)	: 120ml
Tank code (ADR)	: PxBN(M)
Transport category (ADR)	: 3
Hazard identification number (Kemler No.)	: 20
Orange plates	:



Tunnel restriction code (ADR)	: C/E
EAC code	: 2TE

#### Transport by sea

Special provisions (IMDG)	: 274
Limited quantities (IMDG)	: 120 ml
EmS-No. (Fire)	: F-C
EmS-No. (Spillage)	: S-V

#### Air transport

PCA Limited quantities (IATA)	: Forbidden
PCA limited quantity max net quantity (IATA)	: Forbidden
PCA packing instructions (IATA)	: 200
PCA max net quantity (IATA)	: 75kg
CAO packing instructions (IATA)	: 200
CAO max net quantity (IATA)	: 150kg

#### Rail transport

Classification code (RID)	: 2A
Special provisions (RID)	: 274, 660, 662
Limited quantities (RID)	: 120ml
Tank codes for RID tanks (RID)	: PxBN(M)
Transport category (RID)	: 3
Colis express (express parcels) (RID)	: CE3
Hazard identification number (RID)	: 20

### 14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable

# R-407F (PERFORMAX LT)

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

### SECTION 15: Regulatory information

#### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

##### 15.1.1. EU-Regulations

Contains no REACH substances with Annex XVII restrictions

Contains no substance on the REACH candidate list

Contains no REACH Annex XIV substances

Contains no substance subject to Regulation (EU) No 649/2012 of the European Parliament and of the Council of 4 July 2012 concerning the export and import of hazardous chemicals.

Contains no substance subject to Regulation (EU) No 2019/1021 of the European Parliament and of the Council of 20 June 2019 on persistent organic pollutants

Other information, restriction and prohibition : \* Regulation (EC) No 517/2014 : Greenhouse fluorinated gas falling within Kyoto Protocol. regulations

##### 15.1.2. National regulations

Ensure all national/local regulations are observed.

#### 15.2. Chemical safety assessment

No additional information available

### SECTION 16: Other information

#### Indication of changes:

All chapters have been modified since the previous version.

Other information : For more information regarding the use of this product, please refer to our technical information or contact the sales department in your region.

#### Full text of H- and EUH-statements

Flam. Gas 1B	Flammable gases, Category 1B
Press. Gas (Liq.)	Gases under pressure : Liquefied gas
H221	Flammable gas.
H280	Contains gas under pressure; may explode if heated.

Safety Data Sheet (SDS), EU

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.