



Refrigerants

FREON® MO89

GUARANTEED COMMERCIAL SPECIFICATIONS

STANDARD SPECIFICATIONS LIMIT VALUE	STANDARD SPECIFICATIONS LIMIT VALUE	
Composition	Composition	
R-125	R-125	
R-218	R-218	
R-290	R-290	
86% (-1.5% +1.5%)	86% (-1.5% +1.5%)	
9 % (-1.0% +1.0%)	9 % (-1.0% +1.0%)	

MAIN APPLICATIONS

FREON® MO89 is a HFC type zeotropic mixture, intended for "drop-in" replacement of R-13B1, used in very low temperatures direct expansion setups.

It can also be used in new setups.

OILS

Use an alkylbenzene (AB) or polyol ester (POE) oil.

Check with Climalife regarding the viscosity of the oil selected for your application, and the miscibility with the fluid under consideration.

PRECAUTIONS OF USE

Refer to the Safety Data Sheet*.

REGULATION

Use, implementation and recovery are governed by European regulation no. 2024/573. It is also important to refer to the regulations in force in each country in Europe and outside Europe. *Find Safety Data Sheets (SDS) directly on our website www.climalife.com





Refrigerants

PHYSICO-CHEMICAL PROPERTIES OF FREON® MO89

Molar mass	g/mol	113.9
Melting point	°C	N/A
Boiling point (under 1.013 bar)	°C	-53.4
Temperature drift under 1.013 bar	K	3.06
Saturated fluid density at 25°C	kg/m³	1082
Saturated vapour density at boiling point	kg/m³	6.507
Vapour tension at:		
25°C	bar	15.27
50°C	Dai	27.51
Critical temperature	°C	64.18
Critical pressure	bar	37.34
Critical density	kg/m³	534.3
Latent heat of vaporisation at boiling point	kJ/kg	170.42
Thermal conductivity at 25°C		
Liquid	W/(m.K)	0.059
Vapour under 1.013 bar	W/(III.K)	0.016
Surface tension at 25°C	10 ⁻³ N/m	3.71
Water solubility in the fluid at 25°C	% weight	
Viscosity at 25°C		
Liquid	10 ⁻³ Pa.s	0.121
Vapour under 1.013 bar	10 ° Pa.5	0.013
Specific heat at 25°C		
Liquid	kJ/(kg.K)	1.501
Vapour under 1.013 bar	K)/(Kg.K)	0.840
Ratio Cp/Cv at 25°C under 1.013 bar		1.103
Flammability in air		Non-flammable
Flashing point		None
NF-EN 378 Classification		L1
Ozone Depletion Potential	(R-11=1)	0
GWP according to Regulation (EU) 2024/573 (F-		3811
Gas III)	$(CO_2 = 1)$	
GWP (AR4 / AR6)		3770 / 4015

Please contact your distributor or our **Climalife** sales department for more information. In addition, if the refrigeration system you want to install, or are working on, does not appear to be a typical installation, please do not hesitate to contact us for advice and information.

The information contained in this product sheet is the result of our studies and experience. It is provided in good faith, but should not, under any circumstance, be taken to constitute a guarantee on our part or an assumption of our responsibility. This is particularly the case when third party rights are at stake or in situations where a user of one of our products fails to observe applicable regulations.



