

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture
 Name : R-422D
 Product code : 100002900

1.2. Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses

Use of the substance/mixture : Refrigerant

1.3. Details of the supplier of the safety data sheet

Supplier

Dehon Service SAS
 26 Avenue du Petit Parc
 94683 VINCENNES Cedex
 France
 T 01 43 98 75 00, F 01 43 98 21 51
ContactFDS@climalife.dehon.com

Other

Climalife Kft Budepesta sucursală București Romania
 Bulevardul Hristo Botev, Nr. 28,
 Biroul NR 4, Modulul I
 București Sectorul 3
 Romania
ContactFDS@climalife.dehon.com

Other

Dehon Kälte-Fachvertriebs GmbH
 Robert-Bosch-Strasse 14
 40668 MEERBUSCH
 Germany
 T 00 49 2150 7073 0 , F 00 49 2150 7073 17
ContactFDS@climalife.dehon.com

Other

Dehon Service Belgium s.a/n.v.
 Avenue Carton de Wiart, 79
 1090 Bruxelles
 Belgium
 T 00 32 2 421 01 70, F 00 32 2 426 96 62
ContactFDS@climalife.dehon.com

Other

Friogas sa
 Poligono Industrial SEPES
 Parcela 10
 46500 SAGUNTO (Valencia)
 Spain
 T 00 34 9 6 266 36 32, F 00 34 9 6 266 50 25
ContactFDS@climalife.dehon.com

Other

Prochimac SA
 ZI Petits Champs 15
 CH-1400 Yverdon-les-Bains
 Switzerland
 T 00 41 32 727 36 00, F 00 41 32 727 36 19
ContactFDS@climalife.dehon.com

Other

Other

Climalife Hongrie Kft.
 Villányi út 47
 1118 Budapest
 Hungary
 T (36) 23 431 660
ContactFDS@climalife.dehon.com

Other

Climalife Supplied by Inventec Performance Chemicals Italia SRL
 Via del Lavoro, 10/G
 20874 Busnago MB
 Italia
 T +39 39-5973480, F +39 39-5973490
ContactFDS@climalife.dehon.com

Other

Dehon nordic service
 Östra Hamngatan 50B 3tr
 41109 GÖTEBORG
 Sweden
 T 00 46 735 01 90 50
ContactFDS@climalife.dehon.com

Other

Dehon Service Nerderland B.V.
 Van Konijnenburgweg 84
 NL-4612 PL Bergen Op Zoom
 Netherlands
 T 00 31 164 212 830, F 00 31 164 212 831
ContactFDS@climalife.dehon.com

Other

IDS Refrigeration Limited
 22 Apex Court, Woodlands, Bradley Stoke
 BS32 4JT Bristol
 United Kingdom
 T 00 44 1179 802520, F 00 44 1179 802521
ContactFDS@climalife.dehon.com

Other

Galco s.a/n.v.
 Avenue Carton de Wiart, 79
 1090 BRUSSELS
 Belgium
 T 00 32 2 421 01 84 , F 00 32 2 421 01 84 / 00 32 2 425 38 12
ContactFDS@climalife.dehon.com

Other

R-422D

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

Climalife Asia Corporation
Room 302-A82, No.3, Building 1509, Xin Zhen Road,
201101 Shanghai, Minhang District
China
T +86 21 6442 3972, F +86 21 6442 3952
ContactFDS@climalife.dehon.com

Galco Singapore Branch
135 Cecil Street #10-01
Singapore
ContactFDS@climalife.dehon.com

Other

Teknalys Middle East FZCO
B34BS33O203, Jebel Ali Freezone
Dubai
United Arab Emirates
ContactFDS@climalife.dehon.com

1.4. Emergency telephone number

Emergency number : +33 (0) 1 72 11 00 03

Country/Area	Organisation/Company	Address	Emergency number	Comment
Ireland	National Poisons Information Centre Beaumont Hospital	PO Box 1297 Beaumont Road 9 Dublin	+353 1 809 2566 (Healthcare professionals- 24/7) +353 1 809 2166 (public, 8am - 10pm, 7/7)	
United Kingdom	National Poisons Information Service (Birmingham Centre) City Hospital	Dudley Road B18 7QH	0344 892 0111	Only for healthcare professionals

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Press. Gas (Liq.) H280
Full text of hazard classes, H- and EUH-statements: see section 16

Adverse physicochemical, human health and environmental effects

Vapours are heavier than air and can cause suffocation by reducing oxygen available for breathing. Contact with the liquid may cause frostbite and serious damage to eyes.

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP) :



GHS04

Signal word (CLP) : Warning
Hazard statements (CLP) : H280 - Contains gas under pressure; may explode if heated.
Precautionary statements (CLP) : P403 - Store in a well-ventilated place.
Extra phrases : Greenhouse fluorinated gas falling within Kyoto Protocol (GWP=2729).

2.3. Other hazards

Contains no PBT and/or vPvB substances $\geq 0.1\%$ assessed in accordance with REACH Annex XIII

Component

Substance(s) not meeting the PBT criteria of REACH regulation, in accordance with Annex XIII	Pentafluoroethane (354-33-6), 1,1,1,2-Tetrafluoroethane (811-97-2), Isobutane (containing < 0,1 % 1,3-butadiene (203-450-8)) (75-28-5)
--	--

R-422D

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

Component

Substance(s) not meeting the vPvB criteria of REACH regulation, in accordance with Annex XIII	Pentafluoroethane (354-33-6), 1,1,1,2-Tetrafluoroethane (811-97-2), Isobutane (containing < 0,1 % 1,3-butadiene (203-450-8)) (75-28-5)
---	--

The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or substance(s) are not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Pentafluoroethane	CAS-No.: 354-33-6 EC-No.: 206-557-8 REACH-no: 01-2119485636-25	65.1	Press. Gas (Liq.), H280
1,1,1,2-Tetrafluoroethane	CAS-No.: 811-97-2 EC-No.: 212-377-0 REACH-no: 01-2119459374-33	31.5	Press. Gas (Liq.), H280
Isobutane (containing < 0,1 % 1,3-butadiene (203-450-8))	CAS-No.: 75-28-5 EC-No.: 200-857-2 EC Index-No.: 601-004-00-0 REACH-no: 01-2119485395-27	3.4	Flam. Gas 1A, H220 Press. Gas (Liq.), H280

Full text of H- and EUH-statements: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures after inhalation	: Move the affected person away from the contaminated area and into the fresh air. If you feel unwell, seek medical advice.
First-aid measures after skin contact	: In the event of contact with the liquid: treat resulting frostbite as a burn. Immediately remove contaminated clothing or footwear. Immediately rinse with plenty of water. If skin burns appear, call a doctor immediately.
First-aid measures after eye contact	: Rinse immediately and thoroughly, pulling the eyelids well away from the eye (15 minutes minimum). Consult an eye specialist immediately.
First-aid measures after ingestion	: Not specifically applicable (gas).

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects	: CNS depression. Narcosis. Cardiac disorders. Lack of oxygen: risk of death.
------------------	---

4.3. Indication of any immediate medical attention and special treatment needed

No additional information available

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media	: All extinguishing agents can be used.
Unsuitable extinguishing media	: None to our knowledge. If there is a fire close by, use suitable extinguishing agents.

R-422D

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

5.2. Special hazards arising from the substance or mixture

- Explosion hazard : pressure rise and possible bursting of container.
Hazardous decomposition products in case of fire : Toxic and corrosive fumes are released. fluorinated compounds. Hydrogen fluoride. Carbon oxides (CO, CO₂). Carbonyl fluoride.

5.3. Advice for firefighters

- Precautionary measures fire : Fight fire remotely due to the risk of explosion.
Firefighting instructions : Use water spray or fog for cooling exposed containers. Get the package away from the fire if this can be done without risk.
Protection during firefighting : Self-contained breathing apparatus. Complete protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

- General measures : Avoid contact with skin and eyes. Remove all sources of ignition. Do not smoke. Evacuate the danger area. Do not breathe smoke. Stop the leak.
No additional information available

6.2. Environmental precautions

No additional information available

6.3. Methods and material for containment and cleaning up

- Other information : Mechanically ventilate the spillage area.

6.4. Reference to other sections

For further information refer to section 8: "Exposure controls/personal protection".

SECTION 7: Handling and storage

7.1. Precautions for safe handling

- Precautions for safe handling : Avoid breathing mist, vapours. Do not get in eyes, on skin, or on clothing. Ensure good ventilation of the work station. Caution! Container under pressure. Handle and open container with care. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Avoid the build-up of electrostatic charge. Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure.
Hygiene measures : Do not drink, eat or smoke in the workplace.

7.2. Conditions for safe storage, including any incompatibilities

- Storage conditions : Store : in a cool, well-ventilated area, away from any source of heat, away from any source of ignition.
Incompatible materials : Strong oxidizing agents. Alkaline hydroxide. Alkaline earth metals. Finely divided metals (Al, Mg, Zn).
Packaging materials : Recommended materials Stainless steel, Carbon steel. Do not use : Alloys containing more than 2% magnesium, Plastic materials.

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

National occupational exposure and biological limit values

R-422D

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

Pentafluoroethane (354-33-6)	
EU - Indicative Occupational Exposure Limit (IOEL)	
IOEL TWA	4900 mg/m ³ (recommended)
	1000 ppm (recommended)
1,1,1,2-Tetrafluoroethane (811-97-2)	
EU - Indicative Occupational Exposure Limit (IOEL)	
IOEL TWA	4240 mg/m ³
	1000 ppm
United Kingdom - Occupational Exposure Limits	
Local name	1,1,1,2-Tetrafluoroethane (HFC 134a)
WEL TWA (OEL TWA)	4240 mg/m ³
	1000 ppm
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE
Isobutane (containing < 0,1 % 1,3-butadiene (203-450-8)) (75-28-5)	
EU - Indicative Occupational Exposure Limit (IOEL)	
IOEL TWA	1450 mg/m ³
	600 ppm
IOEL STEL	1810 mg/m ³
	750 ppm
Ireland - Occupational Exposure Limits	
Local name	Butane, all isomers: Isobutane
OEL STEL	1000 ppm
Remark	Advisory OELV (Advisory Occupational Exposure Limit Values)
Regulatory reference	Chemical Agents Code of Practice 2024

DNEL and PNEC

Pentafluoroethane (354-33-6)	
DNEL/DMEL (Workers)	
Long-term - systemic effects, inhalation	16444 mg/m ³
DNEL/DMEL (General population)	
Long-term - systemic effects, inhalation	1753 mg/m ³
PNEC (Water)	
PNEC aqua (freshwater)	0.1 mg/l
PNEC aqua (intermittent, freshwater)	1 mg/l
PNEC (Sediment)	
PNEC sediment (freshwater)	0.6 mg/kg dwt
1,1,1,2-Tetrafluoroethane (811-97-2)	
DNEL/DMEL (Workers)	
Long-term - systemic effects, inhalation	13936 mg/m ³

R-422D

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

1,1,1,2-Tetrafluoroethane (811-97-2)	
DNEL/DMEL (General population)	
Long-term - systemic effects, inhalation	2476 mg/m ³
PNEC (Water)	
PNEC aqua (freshwater)	0.1 mg/l
PNEC aqua (marine water)	0.01 mg/l
PNEC aqua (intermittent, freshwater)	1 mg/l
PNEC (Sediment)	
PNEC sediment (freshwater)	0.75 mg/kg dwt
PNEC (STP)	
PNEC sewage treatment plant	73 mg/l

8.2. Exposure controls

Personal protection equipment

Eye and face protection

Eye protection:

Safety glasses with side shields

Skin protection

Skin and body protection:

Majority cotton protective clothing

Hand protection:

cold-insulating gloves. Leather protective gloves. Nitrile-rubber protective gloves. VITON gloves

Respiratory protection

Respiratory protection:

In the event of insufficient ventilation: Gas mask with filter type AX. In a confined area : Self-contained breathing apparatus

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Gas
Colour	: Colourless.
Appearance	: Press. Gas (Liq.).
Molecular mass	: 109.94 g/mol
Odour	: slightly ethereal.
Odour threshold	: Not available
Melting point	: Not applicable
Freezing point	: Not applicable
Boiling point	: -43.21 °C
Flammability	: Non flammable.
Explosive properties	: Not explosive material according to EC criteria.
Oxidising properties	: Non oxidizing material according to EC criteria.
Lower explosion limit	: Not available
Upper explosion limit	: Not available
Flash point	: None
Auto-ignition temperature	: Not available
Decomposition temperature	: Not available
pH	: Not applicable
Viscosity, kinematic	: Not applicable
Solubility	: Insoluble in water.
Partition coefficient n-octanol/water (Log Kow)	: Not available
Vapour pressure	: 11.3 bar (25°C)

R-422D

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

Vapour pressure at 50°C	: 20.8 bar (50°C)
Critical pressure	: 39.05 bar
Density	: 1.15 g/cm ³ (25°C)
Relative density	: Not applicable
Relative vapour density at 20°C	: 3.9
Particle characteristics	: Not applicable

9.2. Other information

Information with regard to physical hazard classes

Critical temperature	: 79.6 °C
----------------------	-----------

Other safety characteristics

VOC content	: 100 %
-------------	---------

SECTION 10: Stability and reactivity

10.1. Reactivity

Decomposes on exposure to temperature rise.

10.2. Chemical stability

Stable at ambient temperature and under normal conditions of use.

10.3. Possibility of hazardous reactions

No information available. No polymerization.

10.4. Conditions to avoid

Avoid high temperatures. Avoid naked flame. Heating will cause a rise in pressure with a risk of bursting.

10.5. Incompatible materials

Strong oxidizing agents.

10.6. Hazardous decomposition products

On thermal decomposition (pyrolysis), releases : Hydrogen fluoride, Carbon oxides (CO, CO₂), Fluorinated hydrocarbons, Carbonyl halogenides.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity (oral)	: Not classified
Acute toxicity (dermal)	: Not classified
Acute toxicity (inhalation)	: Not classified

Pentafluoroethane (354-33-6)	
LC50 Inhalation - Rat [ppm]	800000 ppm/4h
1,1,1,2-Tetrafluoroethane (811-97-2)	
LC50 Inhalation - Rat [ppm]	> 500000 ppm/4h
Isobutane (containing < 0,1 % 1,3-butadiene (203-450-8)) (75-28-5)	
LC50 Inhalation - Rat	658 mg/l/4h
LC50 Inhalation - Rat [ppm]	260000 ppm (Mouse, Male, 4 h)
Skin corrosion/irritation	: Not classified pH: Not applicable
Additional information	: Contact with the liquid causes frostbite

R-422D

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

Pentafluoroethane (354-33-6)	
pH	Not applicable
1,1,1,2-Tetrafluoroethane (811-97-2)	
pH	Not applicable
Serious eye damage/irritation	: Not classified pH: Not applicable
Additional information	: Contact with the liquefied gas may cause severe ocular lesions
Pentafluoroethane (354-33-6)	
pH	Not applicable
1,1,1,2-Tetrafluoroethane (811-97-2)	
pH	Not applicable
Respiratory or skin sensitisation	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified
1,1,1,2-Tetrafluoroethane (811-97-2)	
NOAEL (chronic, oral, animal/male, 2 years)	300 mg/kg bodyweight rat
Reproductive toxicity	: Not classified
Pentafluoroethane (354-33-6)	
NOAEL (animal/male, F0/P)	245 mg/kg
NOAEL (animal/female, F0/P)	245 mg/kg
STOT-single exposure	: Not classified
STOT-repeated exposure	: Not classified
Pentafluoroethane (354-33-6)	
NOAEC (inhalation, rat, dust/mist/fume, 90 days)	50000 ppm
1,1,1,2-Tetrafluoroethane (811-97-2)	
NOAEC (inhalation, rat, gas, 90 days)	50000 ppm Animal: rat, Guideline: OECD Guideline 453 (Combined Chronic Toxicity / Carcinogenicity Studies)
Isobutane (containing < 0,1 % 1,3-butadiene (203-450-8)) (75-28-5)	
NOAEC (inhalation, rat, 28 days)	21.934 mg/l (Rat (Female, Male), Inhalation (Gas) , daily)
Aspiration hazard	: Not applicable
1,1,1,2-Tetrafluoroethane (811-97-2)	
Viscosity, kinematic	0.162 mm ² /s
Isobutane (containing < 0,1 % 1,3-butadiene (203-450-8)) (75-28-5)	
Viscosity, kinematic	269.643 mm ² /s

11.2. Information on other hazards

Endocrine disrupting properties

Adverse health effects caused by endocrine disrupting properties : The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or is not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %

R-422D

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

SECTION 12: Ecological information

12.1. Toxicity

Hazardous to the aquatic environment, short-term (acute) : Not classified

Hazardous to the aquatic environment, long-term (chronic) : Not classified

Pentafluoroethane (354-33-6)	
LC50 - Fish [1]	> 81.8 mg/l Test organisms (species): Oncorhynchus mykiss (previous name: Salmo gairdneri)
LC50 - Fish [2]	450 mg/l Test organisms (species): Oncorhynchus mykiss (previous name: Salmo gairdneri)
EC50 - Crustacea [1]	> 97.9 mg/l Test organisms (species): Daphnia magna
EC50 72h - Algae [1]	> 114 mg/l Test organisms (species): Raphidocelis subcapitata (previous names: Pseudokirchneriella subcapitata, Selenastrum capricornutum)
EC50 72h - Algae [2]	> 118 mg/l Test organisms (species): Raphidocelis subcapitata (previous names: Pseudokirchneriella subcapitata, Selenastrum capricornutum)
NOEC chronic fish	32 mg/l Test organisms (species): Duration: '30 d'

1,1,1,2-Tetrafluoroethane (811-97-2)	
LC50 - Fish [1]	450 mg/l Test organisms (species): Oncorhynchus mykiss (previous name: Salmo gairdneri)
EC50 - Crustacea [1]	980 mg/l 48 Hours (Daphnia magna)
EC50 72h - Algae [1]	> 118 mg/l Test organisms (species): Raphidocelis subcapitata (previous names: Pseudokirchneriella subcapitata, Selenastrum capricornutum)
EC50 72h - Algae [2]	> 114 mg/l Test organisms (species): Raphidocelis subcapitata (previous names: Pseudokirchneriella subcapitata, Selenastrum capricornutum)

Isobutane (containing < 0,1 % 1,3-butadiene (203-450-8)) (75-28-5)	
LC50 - Fish [1]	27.98 mg/l (estimated, QSAR)
EC50 - Crustacea [1]	16.33 mg/l (estimated, QSAR)
EC50 72h - Algae [1]	8.57 mg/l (estimated, QSAR)

12.2. Persistence and degradability

R-422D	
Persistence and degradability	Not established.

Pentafluoroethane (354-33-6)	
Persistence and degradability	5 % biodegradation after 28 days, Not readily biodegradable.

1,1,1,2-Tetrafluoroethane (811-97-2)	
Persistence and degradability	Photodegradation in the air :, Half-life in air : 9,7 y, 3 % biodegradation after 28 days.

Isobutane (containing < 0,1 % 1,3-butadiene (203-450-8)) (75-28-5)	
Persistence and degradability	< 60 % biodegradation after 28 days.

12.3. Bioaccumulative potential

Pentafluoroethane (354-33-6)	
Partition coefficient n-octanol/water (Log Kow)	1.48 (25°C)

R-422D

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

1,1,1,2-Tetrafluoroethane (811-97-2)

Partition coefficient n-octanol/water (Log Pow) 1.06

Isobutane (containing < 0,1 % 1,3-butadiene (203-450-8)) (75-28-5)

Partition coefficient n-octanol/water (Log Kow) 2.88

12.4. Mobility in soil

Pentafluoroethane (354-33-6)

Organic Carbon Normalized Adsorption Coefficient (Log Koc) 1.3 – 1.7

1,1,1,2-Tetrafluoroethane (811-97-2)

Organic Carbon Normalized Adsorption Coefficient (Log Koc) 1.5

12.5. Results of PBT and vPvB assessment

Component

Substance(s) not meeting the PBT criteria of REACH regulation, in accordance with Annex XIII Pentafluoroethane (354-33-6), 1,1,1,2-Tetrafluoroethane (811-97-2), Isobutane (containing < 0,1 % 1,3-butadiene (203-450-8)) (75-28-5)

Substance(s) not meeting the vPvB criteria of REACH regulation, in accordance with Annex XIII Pentafluoroethane (354-33-6), 1,1,1,2-Tetrafluoroethane (811-97-2), Isobutane (containing < 0,1 % 1,3-butadiene (203-450-8)) (75-28-5)

12.6. Endocrine disrupting properties

Adverse effects on the environment caused by endocrine disrupting properties : The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or is not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %.

12.7. Other adverse effects

Other adverse effects : ODP (R-11=1)=0.
Additional information : GWP (CO2=1/100 years) = 2 729

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Product/Packaging disposal recommendations : Methods of disposal of packaging. Reuse or recycle following decontamination. Destroy at an authorised site.
Additional information : The user's attention is drawn to the possible existence of specific european, national or local regulations regarding disposal.

SECTION 14: Transport information

In accordance with ADR / IMDG / IATA

ADR	IMDG	IATA
14.1. UN number or ID number		
UN 3163	UN 3163	UN 3163

R-422D

Safety Data Sheet


according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

ADR	IMDG	IATA
14.2. UN proper shipping name		
LIQUEFIED GAS, N.O.S. (Pentafluoroethane ; 1,1,1,2-Tetrafluoroethane ; isobutane (containing < 0,1 % 1,3-butadiene (203-450-8)) isobutane)	LIQUEFIED GAS, N.O.S. (Pentafluoroethane ; 1,1,1,2-Tetrafluoroethane ; isobutane (containing < 0,1 % 1,3-butadiene (203-450-8)) isobutane)	Liquefied gas, n.o.s. (Pentafluoroethane ; 1,1,1,2-Tetrafluoroethane ; isobutane (containing < 0,1 % 1,3-butadiene (203-450-8)) isobutane)
Transport document description		
UN 3163 LIQUEFIED GAS, N.O.S. (Pentafluoroethane ; 1,1,1,2-Tetrafluoroethane ; isobutane (containing < 0,1 % 1,3-butadiene (203-450-8)) isobutane), 2.2, (C/E)	UN 3163 LIQUEFIED GAS, N.O.S. (Pentafluoroethane ; 1,1,1,2-Tetrafluoroethane ; isobutane (containing < 0,1 % 1,3-butadiene (203-450-8)) isobutane), 2.2	UN 3163 Liquefied gas, n.o.s. (Pentafluoroethane ; 1,1,1,2-Tetrafluoroethane ; isobutane (containing < 0,1 % 1,3-butadiene (203-450-8)) isobutane), 2.2
14.3. Transport hazard class(es)		
2.2	2.2	2.2
		
14.4. Packing group		
Not applicable	Not applicable	Not applicable
14.5. Environmental hazards		
Dangerous for the environment: No	Dangerous for the environment: No Marine pollutant: No EmS-No. (Fire): F-C EmS-No. (Spillage): S-V	Dangerous for the environment: No
No supplementary information available		

14.6. Special precautions for user

Overland transport

Classification code (ADR) : 2A
Special provisions (ADR) : 274, 662
Limited quantities (ADR) : 120ml
Tank code (ADR) : PxBN(M)
Transport category (ADR) : 3
Hazard identification number (Kemler No.) : 20
Orange plates :



Tunnel restriction code (ADR) : C/E
EAC code : 2TE

Transport by sea

Special provisions (IMDG) : 274

Air transport

PCA Limited quantities (IATA) : Forbidden
PCA limited quantity max net quantity (IATA) : Forbidden
PCA packing instructions (IATA) : 200
PCA max net quantity (IATA) : 75kg
CAO packing instructions (IATA) : 200
CAO max net quantity (IATA) : 150kg

R-422D

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

14.7. Maritime transport in bulk according to IMO instruments

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU-Regulations

Other information, restriction and prohibition regulations : * Regulation (EC) No 517/2014 : Greenhouse fluorinated gas falling within Kyoto Protocol.

REACH Annex XVII (Restriction List)

EU restriction list (REACH Annex XVII)

Reference code	Applicable on
40.	Isobutane (containing < 0,1 % 1,3-butadiene (203-450-8))

REACH Annex XIV (Authorisation List)

Contains no substance(s) listed on REACH Annex XIV (Authorisation List)

REACH Candidate List (SVHC)

Contains no substance(s) listed on the REACH Candidate List

PIC Regulation (Prior Informed Consent)

Contains no substance(s) listed on the PIC list (Regulation EU 649/2012 concerning the export and import of hazardous chemicals)

POP Regulation (Persistent Organic Pollutants)

Contains no substance(s) listed on the POP list (Regulation EU 2019/1021 on persistent organic pollutants)

Ozone Regulation (1005/2009)

Contains no substance(s) listed on the Ozone Depletion list (Regulation EU 1005/2009 on substances that deplete the ozone layer)

Council Regulation (EC) for the control of dual-use items

Contains no substance subject to the COUNCIL REGULATION (EC) for the control of dual-use items

VOC Directive (2004/42)

VOC content : 100 %

Explosives Precursors Regulation (2019/1148)

Contains no substance(s) listed on the Explosives Precursors list (Regulation EU 2019/1148 on the marketing and use of explosives precursors)

Drug Precursors Regulation (273/2004)

Contains no substance(s) listed on the Drug Precursors list (Regulation EC 273/2004 on the manufacture and the placing on market of certain substances used in the illicit manufacture of narcotic drugs and psychotropic substances)

National regulations

Ensure all national/local regulations are observed.

15.2. Chemical safety assessment

No additional information available

SECTION 16: Other information

Indication of changes:

All chapters have been modified since the previous version.

Indication of changes

Section	Changed item	Comments
	Issue date	Added

R-422D

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

Indication of changes		
Section	Changed item	Comments
	Supersedes	Modified
	Revision date	Modified
	Adverse health effects caused by endocrine disrupting properties	Added
2.2	Precautionary statements (CLP)	Modified
3	Composition/information on ingredients	Modified
9	VOC content	Added
9	Molecular mass	Added
9	Additional information	Added
12.2	Persistence and degradability	Added
12.6	Adverse effects on the environment caused by endocrine disrupting properties	Added
15.1	REACH Annex XVII	Added

Other information : For more information regarding the use of this product, please refer to our technical information or contact the sales department in your region.

Full text of H- and EUH-statements:	
Flam. Gas 1A	Flammable gases, Category 1A
H220	Extremely flammable gas.
H280	Contains gas under pressure; may explode if heated.
Press. Gas (Liq.)	Gases under pressure : Liquefied gas

Safety Data Sheet (SDS), EU

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.