

**R-417A**
**100005900**
**SECTION 1 Identification of the substance/mixture and of the company/undertaking**
**1.1. Product identifier**
**Trade name** : R-417A

**1.2. Relevant identified uses of the substance or mixture and uses advised against**
**1.2.1 Relevant identified uses** : Refrigerant

**1.3. Details of the supplier of the safety data sheet**

 : DEHON SERVICE  
 26 Avenue du Petit Parc  
 94683 VINCENNES Cedex France  
 Tel : +33 (0) 1 43 98 75 00  
 Fax : +33 (0) 1 43 98 21 51

**e-mail** : ContactFDS@climalife.dehon.com

**1.4 Emergency telephone number** : EMERGENCY TELEPHONE NUMBER (24h/24) : + 33 (0) 1 72 11 00 03  
 Anti-poison Center : INRS/ORFILA (France) : +33 (0) 1 45 42 59 59  
 Anti-poison Centre (Belgium) : +32 70 245 245  
 Anti-poison Centre (Netherlands) : +31 30 274 8888  
 Anti-poison Centre (Spain) : +34 91 562 04 20  
 Anti-poison Centre (United Kingdom) : +44 870 600 6266  
 Poisons Information Centre (Hungary) : +36 80 201 199

**SECTION 2 Hazards identification**
**2.1. Classification of the substance or mixture**
**2.1.1. Regulation (EC) No 1272/2008 (CLP)**
**Physical hazards** : Gases under pressure - Liquefied gas (Press. Gas) - H280

**2.1.2 Directive EEC/67/548 or 1999/45/CE** : This product is not classified as a "hazardous preparation" according to European Community regulations

**2.2. Label elements**
**2.2.1 Labelling EC 1272/2008 (CLP)**
**Hazard pictograms**

**Signal words** : Warning

**Hazard statements** : H280 : Contains gas under pressure; may explode if heated

**Precautionary statements :**

 • **Storage** : P410 + P403 : Protect from sunlight. Store in a well-ventilated place

 - **Further data** : Contains : 46.6% Pentafluoroethane (R-125) / 50% 1,1,1,2-Tetrafluoroethane (R-134a) / 3.4% n-Butane (R600) .  
 Greenhouse fluorinated gas falling within Kyoto Protocol (GWP = 2346)

**2.3. Other hazards**

 : Liquefied gas :  
 Suffocation hazard by lack of oxygen  
 Contact with liquid may cause frostbite and serious damage to eyes

**DEHON SERVICE**

 26 Avenue du Petit Parc 94683 VINCENNES Cedex France  
 Tel : +33 (0) 1 43 98 75 00  
 Fax : +33 (0) 1 43 98 21 51



# MATERIAL SAFETY DATA SHEET

Page : 2 / 8

Version : 7

Date : 29 / 7 / 2015

Supersedes : 14 / 8 / 2013

**R-417A****100005900**

## SECTION 3 Composition/information on ingredients

3.1./3.2. Substance / Preparation : Preparation

Components contributing to the hazard :

Substance name	Contents	CAS No	EC No	Index No	Ref REACH	Classification
1,1,1,2-Tetrafluoroethane	: 50 %	811-97-2	212-377-0	-----	01-2119459374-33	Not classified. (DSD/DPD) Liquefied gas;H280
Pentafluoroethane	: 46.6 %	354-33-6	206-557-8	-----	01-2119485636-25	Not classified. (DSD/DPD) Liquefied gas;H280
n-Butane	: 3.4 %	106-97-8	203-448-7	601-004-00-0	01-2119474691-32	F+; R12 Flam. Gas 1;H220 Liquefied gas;H280

## SECTION 4 First aid measures

### 4.1. Description of first aid measures

**Inhalation** : Move the affected person away from the contaminated area and into the fresh air  
If the person feels unwell : Call a doctor

**Skin contact** : Immediately remove contaminated clothing or footwear  
Immediately rinse with plenty of water  
In the event of contact with the liquid: treat resulting frostbite as a burn  
If skin burns appear, call a doctor immediately

**Eye contact** : Rinse immediately and thoroughly, pulling the eyelids well away from the eye (15 minutes minimum)  
Consult an eye specialist immediately

**Ingestion** : Not specifically applicable (gas)

### 4.2. Most important symptoms and effects, both acute and delayed

**Inhalation** : Narcotic effect  
Headaches  
Dizziness  
Dizziness  
Cardiac disorders  
In the event of exposure to high concentrations :

**Skin contact** : Rapid evaporation of the liquid may cause frostbite  
Irritation  
Rednesses  
Itching  
Swelling.

**Eye contact** : Irritation  
Rapid evaporation of the liquid may cause frostbite  
Watering of the eyes  
Rednesses

**Ingestion** : Not applicable.

**4.3. Indication of any immediate medical attention and special treatment needed** : Do not administer adrenalin

## DEHON SERVICE

26 Avenue du Petit Parc 94683 VINCENNES Cedex France  
Tel : +33 (0) 1 43 98 75 00  
Fax : +33 (0) 1 43 98 21 51



# MATERIAL SAFETY DATA SHEET

Page : 3 / 8

Version : 7

Date : 29 / 7 / 2015

Supersedes : 14 / 8 / 2013

**R-417A****100005900**

## SECTION 5 Fire-fighting measures

### 5.1. Extinguishing media

**Suitable extinguishing media** : All extinguishing agents can be used

**Unsuitable extinguishing media** : None to our knowledge. If there is a fire close by, use suitable extinguishing agents

### 5.2. Special hazards arising from the substance or mixture

**Specific hazards** : Pressurized container. On heating there is a risk of bursting due to internal pressure build-up.  
On heating : Toxic and corrosive vapours are released

### 5.3. Advice for firefighters

**Specific fire fighting methods** : Cool down the containers exposed to heat with a water spray

**Protection of fire-fighters** : Complete protective clothing  
Self-contained breathing apparatus

## SECTION 6 Accidental release measures

**6.1. Personal precautions, protective equipment and emergency procedures** : Avoid contact with skin and eyes  
Do not breathe gas.  
Do not smoke  
Heavy vapours. Shut off low-level openings in the vicinity (ventilation shafts, drains...).  
Prevent the product from entering cellars, basements or pits  
Stop the leak.  
Remove all sources of ignition  
Mechanically ventilate the spillage area.

**6.2. Environmental precautions** : Contain the spilled material by bunding

**Clean up methods :**

### 6.3. Methods and material for containment and cleaning up

- **Recovery** : Recover as much product as possible

- **Cleaning/decontamination** : Allow the residual product to evaporate.

**6.4 Reference to other sections** : For further information refer to section 8 "Exposure controls/personal protection"

## SECTION 7 Handling and storage

### 7.1. Precautions for safe handling

**Technical measures** : Ventilation  
Use in a closed system

**Precautions** : Avoid contact with hot surfaces  
Avoid high temperatures.

**Industrial hygiene** : Do not drink, eat or smoke in the workplace

### 7.2. Conditions for safe storage, including any incompatibilities

#### Storage conditions

- **Recommended** : Store :  
- in a cool, well-ventilated area  
- at temperature not exceeding 45 °C  
- away from any source of ignition  
- away from any source of heat

**Incompatible products** : Alkaline earth metals  
Alkali metals  
Finely divided metals (Mg, Al, Zn)

## DEHON SERVICE

26 Avenue du Petit Parc 94683 VINCENNES Cedex France

Tel : +33 (0) 1 43 98 75 00

Fax : +33 (0) 1 43 98 21 51



# MATERIAL SAFETY DATA SHEET

Page : 4 / 8

Version : 7

Date : 29 / 7 / 2015

Supersedes : 14 / 8 / 2013

**R-417A****100005900**

## SECTION 7 Handling and storage (continued)

- Packaging :** : Pressurized metal container
- Packaging materials**
- **Recommended** : Ordinary steel  
Stainless steel
  - **Not suitable** : Plastic materials.  
Magnesium and its alloys.  
Zinc and its alloys.  
Alloys containing more than 2% magnesium
- 7.3. Specific end use(s)** : No data

## SECTION 8 Exposure controls/personal protection

### 8.1. Control parameters

**Engineering measures** : Ensure good ventilation of the work station

- 8.1.1. Occupational Exposure Limits** : 1,1,1,2-Tetrafluoroethane : United Kingdom : WEL - TWA (8h; mg/m<sup>3</sup>) : 4240  
1,1,1,2-Tetrafluoroethane : United Kingdom : WEL - TWA (8h; ppm) : 1000  
1,1,1,2-Tetrafluoroethane : Germany : MAK - TWA (8h; mg/m<sup>3</sup>) : 4200  
1,1,1,2-Tetrafluoroethane : Germany : MAK - TWA (8h; ppm) : 1000  
1,1,1,2-Tetrafluoroethane : Germany : TRK - STEL (15min; mg/m<sup>3</sup>) : 33600  
1,1,1,2-Tetrafluoroethane : Germany : TRK - STEL (15min; ppm) : 8000  
Pentafluoroethane : France : LEP - VME (8h; ppm) : 1000  
n-Butane : France : LEP - VME (8h; mg/m<sup>3</sup>) : 1900  
n-Butane : France : LEP - VME (8h; ppm) : 800  
n-Butane : United Kingdom : WEL - TWA (8h; mg/m<sup>3</sup>) : 1450  
n-Butane : United Kingdom : WEL - TWA (8h; ppm) : 600  
n-Butane : United Kingdom : WEL - STEL (15min; mg/m<sup>3</sup>) : 1850  
n-Butane : United Kingdom : WEL - STEL (15min; ppm) : 750  
n-Butane : Germany : MAK - TWA (8h; mg/m<sup>3</sup>) : 2400  
n-Butane : Germany : MAK - TWA (8h; ppm) : 1000  
n-Butane : Germany : MAK - STEL (15min; mg/m<sup>3</sup>) : 9600  
n-Butane : Germany : MAK - STEL (15min; ppm) : 4000  
n-Butane : Hungary : AK - TWA (8h; mg/m<sup>3</sup>) : 2350  
n-Butane : Hungary : AK - STEL (15min; mg/m<sup>3</sup>) : 9400  
n-Butane : USA (NIOSH) : REL - TWA (8h; mg/m<sup>3</sup>) : 1900  
n-Butane : USA (NIOSH) : REL - TWA (8h; ppm) : 800

### 8.2. Exposure controls

**Personal protection :**

- **Respiratory protection** : In the event of insufficient ventilation: Mask with AX canister  
In a confined area : Self-contained breathing apparatus (ARI)
- **Hand protection** : Leather or nitrile-rubber protective gloves
- **Eye protection** : Safety spectacles with side shields
- **Skin protection** : Majority cotton clothing

## DEHON SERVICE

26 Avenue du Petit Parc 94683 VINCENNES Cedex France  
Tel : +33 (0) 1 43 98 75 00  
Fax : +33 (0) 1 43 98 21 51

**R-417A**
**100005900**
**SECTION 9 Physical and chemical properties**
**9.1. Information on basic physical and chemical properties**
**9.1.a. Appearance**
**Physical state** : Compressed liquefied gas

**Colour** : Colourless

**9.1.b. Odour** : slightly ethereal.

**9.1.c. Odour threshold** : No information available

**9.1.d. pH** : Not applicable

**9.1.e. Melting point / Freezing point** : No information available

**9.1.f. Initial boiling point - boiling range** : -38 °C

**9.1.g. Flash point** : Not applicable

**9.1.h. Evaporation rate** : No information available

**9.1.i. Flammability** : Non flammable.

**9.1.j. Explosion limits (lower - upper)** : None.

**9.1.k. Vapour pressure** : 972 kPa at 20 °C

**9.1.l. Vapour density** : No information available

**9.1.m. Density** : 1.16 g/cm<sup>3</sup> at 20 °C

**9.1.n. Solubility**

-in water : Slightly soluble

**9.1.o. Partition coefficient : n-octanol / water** : Pentafluoroethane (R-125) : 1.48 (log Pow)  
 1,1,1,2-Tetrafluoroethane (R-134a) : 1.06 (log Pow)  
 n-butane : 2.8 (log Pow)

**9.1.p. Auto-ignition temperature** : No information available

**9.1.q. Thermal decomposition** : No information available

**9.1.r. Viscosity** : No information available

**9.1.s. Explosive Properties** : Not explosive material according to EC criteria

**9.1.t. Oxidising properties** : Non oxidizing material according to EC criteria

**9.2. Other information**
**Critical temperature** : +89.9 °C

**Critical pressure** : 40.95 bar absolute

**SECTION 10 Stability and reactivity**
**10.1. Reactivity** : None under normal conditions

**10.2. Chemical stability** : Stable at ambient temperature and under normal conditions of use

**10.3. Possibility of hazardous reactions** : No information available

**10.4. Conditions to avoid** : May decompose :  
 - on contact with hot surfaces and flames

**10.5. Incompatible materials** : - alkaline earth metals.  
 - alkali metals  
 - finely divided metals (Al, Mg, Zn)

**10.6. Hazardous decomposition products** : Carbon oxides (CO, CO<sub>2</sub>)  
 Hydrogen fluoride

**DEHON SERVICE**

26 Avenue du Petit Parc 94683 VINCENNES Cedex France

Tel : +33 (0) 1 43 98 75 00

Fax : +33 (0) 1 43 98 21 51

**R-417A**
**100005900**
**SECTION 11 Toxicological information**
**11.1. Information on toxicological effects**

• Acute toxicity	: No information available
<b>On ingredients</b>	
<b>n-Butane</b>	: Rat inhalation LC50 [mg/l/4h] : 658
<b>Pentafluoroethane</b>	: Rat inhalation LC50 [ppm/4h] : 800000
<b>1,1,1,2-Tetrafluoroethane</b>	: Rat inhalation LC50 [ppm/4h] : > 500000
• Skin corrosion/irritation	: No information available
• Serious eye damage/irritation	: No information available
• Respiratory or skin sensitisation	: No information available
• Germ cell mutagenicity	: No information available
• Carcinogenicity	: No information available
• Reproductive toxicity	: No information available
• STOT-single exposure	: No information available
• STOT-repeated exposure	: No information available
• Aspiration hazard	: No information available
<b>Other information</b>	: Contact with liquefied gas may cause severe ocular lesions Contact with liquefied gas may cause frostbite.

**SECTION 12 Ecological information**
**12.1. Toxicity**
**Effects on the aquatic environment**
**On ingredients**

<b>n-Butane</b>	: 48 Hour - EC50 - Daphnia magna [mg/l] : 14.22 : 96 Hours - LC50 - Fish [mg/l] : 24.11
<b>Pentafluoroethane</b>	: 48 Hour - EC50 - Daphnia magna [mg/l] : 100 (Results obtained on a similar product). : 72 Hours - EC50 - Algae [mg/l] : 114 (Results obtained on a similar product). : 96 Hours - LC50 - Fish [mg/l] : 100 (Results obtained on a similar product).
<b>1,1,1,2-Tetrafluoroethane</b>	: 6 Hours - EC50 - Bacteria (Methanogens) [mg/l] : > 730 : 48 Hour - EC50 - Daphnia magna [mg/l] : 930 : 96 Hours - LC50 - Fish [mg/l] : 450

**12.2. Persistence and degradability**
**12.3. Bioaccumulative potential**
**Octanol/water partition coefficient**
**12.4. Mobility in soil**
**Volatility**
**12.5. Results of PBT and vPvB assessment**
**12.6. Other adverse effects**
**Ozone depletion potential**
**Greenhouse effect**

: No information available
: Not potentially bioaccumulable.
: Pentafluoroethane (R-125) : 1.48 (log Pow) 1,1,1,2-Tetrafluoroethane (R-134a) : 1.06 (log Pow) n-butane : 2.08 (log Pow)
: Product is volatile from an aqueous solution
: No information available
: ODP (R-11=1)=0
: GWP (CO2=1/100 years) = 2346

**DEHON SERVICE**

26 Avenue du Petit Parc 94683 VINCENNES Cedex France  
 Tel : +33 (0) 1 43 98 75 00  
 Fax : +33 (0) 1 43 98 21 51

**R-417A**
**100005900**
**SECTION 13 Disposal considerations**
**13.1. Waste treatment methods**
**WASTE FROM PRODUCT :**

- Prohibition :** : Do not allow the product to be released into the environment
- Destruction/Disposal** : Consult the manufacturer or supplier for information regarding recovery and recycling of the product  
If recovery is not possible:  
Incinerate at a licensed installation.

**CONTAMINATED PACKAGING :**

- Decontamination/cleaning** : De-gas
- Destruction/Disposal** : Return to the supplier
- NOTE** : The user's attention is drawn to the possible existence of specific european, national or local regulations regarding disposal

**SECTION 14 Transport information**

- 14.1. UN number** : UN 3163
- 14.2. UN proper shipping name** : LIQUEFIED GAS, N.O.S. (1,1,1,2-Tetrafluoroethane, Pentafluoroethane, n-Butane )
- 14.3. Transport hazard class(es)**
- Rail/road (RID/ADR)** : Class : 2
- Sea transport** : Class : 2.2
- Air transport (OACI/IATA)** : Class : 2.2
- Hazard Label(s)**



- : 2.2
- 14.4. Packing group** : -
- 14.5. Environmental hazards** : Marine pollutant : NO  
Not classified as dangerous to the aquatic environment
- 14.6. Special precautions for user**
- Rail/road (RID/ADR)** : Classification code : 2A  
Hazard identification number : 20  
Tunnel restriction code : (C/E)
- Sea transport** : EmS Nr : F-C, S-V  
Segregation group : -
- Air transport (OACI/IATA)** : Cargo aircraft:  
Packing instruction: 200  
Quantity: 150 kg  
Passenger aircraft:  
Packing instruction: 200  
Quantity: 75 kg
- 14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code** : Not applicable

**DEHON SERVICE**

26 Avenue du Petit Parc 94683 VINCENNES Cedex France  
Tel : +33 (0) 1 43 98 75 00  
Fax : +33 (0) 1 43 98 21 51



# MATERIAL SAFETY DATA SHEET

Page : 8 / 8

Version : 7

Date : 29 / 7 / 2015

Supersedes : 14 / 8 / 2013

**R-417A****100005900**

## SECTION 15 Regulatory information

**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture** : Ensure all national/local regulations are observed.

**France** : Classified Installations : applicable

**15.2. Chemical safety assessment** : No information available

## SECTION 16 Other information

**Further information** : Product for industrial use only  
For more information regarding the use of this product, please refer to our technical information or contact the sales department in your region  
This safety data sheet has been written in conformity with the regulation (UE) 453/2010.

**Text of R-Phrases in § 3** : R12 : Extremely flammable.

**Text of H-Phrases in § 3** : H220 - Extremely flammable gas  
H280 - Contains gas under pressure; may explode if heated

**\* Update** : All chapters have been modified since the previous version

This sheet complements the technical sheets but does not replace them. The information given is based on our knowledge of the product, at the time of publication. It is given in good faith.

Besides, the attention of the user is drawn to the possible risks incurred by using the product for any other use than that for which it was intended.

In no way does this exempt the user from knowing and applying all the regulations controlling his activity. He alone will take on the responsibility for taking the precautions involved by the use of the product.

The aim of all the mandatory regulations mentioned is just to help the user to fulfil his obligations regarding the use of hazardous products.

This information must not be considered exhaustive. It does not exempt the user from ensuring that other obligations than those mentioned could apply, related to the storage and use of the product, this being his sole responsibility.

**End of document**

## DEHON SERVICE

26 Avenue du Petit Parc 94683 VINCENNES Cedex France

Tel : +33 (0) 1 43 98 75 00

Fax : +33 (0) 1 43 98 21 51