

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form	: Substance
Name	: PROPANE
EC-No.	: 200-827-9
CAS-No.	: 74-98-6
REACH registration No	: 01-2119486944-21
Product code	: 101306800
Synonyms	: NOVASPRAY propane / NOVEXPANS propane

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Title	Use descriptors
Use as a propellant in aerosol products	SU3, SU10, SU21, SU22, PC0, PC3, PC8, PC9a, PC9b, PC24, PC29, PC34, PC35, PC39, PROC2, PROC5, PROC7, PROC9, PROC11, ERC2, ERC8a
Use gas in mixtures as foaming agents in personal care products	SU21, PC39, PROC12
Foam blowing agent	SU12, PC32, PROC12, ERC3
Formulation of mixtures with gas in pressure receptacles	SU10, PROC1, PROC3, ERC2

Full text of use descriptors: see section 16

1.2.2. Uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet

Supplier

Dehon Service SAS
 26 Avenue du Petit Parc
 94683 VINCENNES Cedex - France
 T 01 43 98 75 00 - F 01 43 98 21 51
ContactFDS@climalife.dehon.com

Other

Climalife Kft Budepesta sucursală Bucuresti Romania
 Bulevardul Hristo Botev, Nr. 28,
 Biroul NR 4, Modulul I
 Bucuresti Sectorul 3 - Romania
ContactFDS@climalife.dehon.com

Other

Dehon Kälte-Fachvertriebs GmbH
 Robert-Bosch-Strasse 14
 40668 MEERBUSCH - Germany
 T 00 49 2150 7073 0 - F 00 49 2150 7073 17
ContactFDS@climalife.dehon.com

Other

Dehon Service Belgium s.a/n.v.
 Avenue Carton de Wiart, 79
 1090 Bruxelles - Belgium
 T 00 32 2 421 01 70 - F 00 32 2 426 96 62
ContactFDS@climalife.dehon.com

Other

Friogas sa
 Poligono Industrial SEPES
 Parcela 10
 46500 SAGUNTO (Valencia) - Spain
 T 00 34 9 6 266 36 32 - F 00 34 9 6 266 50 25
ContactFDS@climalife.dehon.com

Other

Climalife Hongrie Kft
 Villányi út 47
 1118 Budaörs - Hungary
 T (36) 23 431 660 - F (36) 23 431 661
ContactFDS@climalife.dehon.com

Other

Climalife Supplied by Inventec Performance Chemicals Italia SRL
 Via del Lavoro, 10/G
 20874 Busnago MB - Italia
 T +39 39-5973480 - F +39 39-5973490
ContactFDS@climalife.dehon.com

Other

Dehon nordic service
 Östra Hamngatan 50B 3tr
 41109 GÖTEBORG - Sweden
 T 00 46 44 21 58 80 - F 00 46 44 21 58 80
ContactFDS@climalife.dehon.com

Other

Dehon Service Nerderland B.V.
 Van Konijnenburgweg 84
 NL-4612 PL Bergen Op Zoom - Netherlands
 T 00 31 164 212 830 - F 00 31 164 212 831
ContactFDS@climalife.dehon.com

Other

IDS Refrigeration Limited
 22 Apex Court, Woodlands, Bradley Stoke
 BS32 4JT Bristol - United Kingdom
 T 00 44 1179 802520 - F 00 44 1179 802521
ContactFDS@climalife.dehon.com

PROPANE

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Other

Prochimac SA
Rue du Château 10
CH-2000 NEUCHÂTEL - Switzerland
T 00 41 32 727 36 00 - F 00 41 32 727 36 19
ContactFDS@climalife.dehon.com

Other

Galco s.a/n.v.
Avenue Carton de Wiart, 79
1090 BRUSSELS - Belgium
T 00 32 2 421 01 84 - F 00 32 2 421 01 84 / 00 32 2 425 38 12
ContactFDS@climalife.dehon.com

1.4. Emergency telephone number

Emergency number : +33 (0) 1 72 11 00 03

Country	Organisation/Company	Address	Emergency number	Comment
United Kingdom	National Poisons Information Service (Birmingham Centre) City Hospital	Dudley Road B18 7QH Birmingham	0344 892 0111	

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Flam. Gas 1 H220
Press. Gas (Liq.) H280

Full text of hazard classes and H-statements : see section 16

Adverse physicochemical, human health and environmental effects

Vapours are heavier than air and can cause suffocation by reducing oxygen available for breathing. Contact with the liquid may cause frostbite and serious damage to eyes.

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP) :



GHS02

Signal word (CLP) :

Danger

Hazard statements (CLP) :

H220 - Extremely flammable gas.
H280 - Contains gas under pressure; may explode if heated.

Precautionary statements (CLP) :

P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P377 - Leaking gas fire: Do not extinguish, unless leak can be stopped safely.
P381 - In case of leakage, eliminate all ignition sources.
P410+P403 - Protect from sunlight. Store in a well-ventilated place.

2.3. Other hazards

No additional information available

SECTION 3: Composition/information on ingredients

3.1. Substances

Name : PROPANE
CAS-No. : 74-98-6
EC-No. : 200-827-9

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
propane	(CAS-No.) 74-98-6 (EC-No.) 200-827-9 (EC Index-No.) 601-003-00-5 (REACH-no) 01-2119486944-21	>= 95	Flam. Gas 1, H220 Press. Gas (Liq.), H280
Isobutane (Impurity)	(CAS-No.) 75-28-5 (EC-No.) 200-857-2 (EC Index-No.) 601-004-00-0 (REACH-no) 01-2119485395-27	< 0.5	Flam. Gas 1, H220 Press. Gas (Liq.), H280

PROPANE

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

n-Butane (Impurity)	(CAS-No.) 106-97-8 (EC-No.) 203-448-7 (EC Index-No.) 601-004-00-0 (REACH-no) 01-2119474691-32	< 0.5	Flam. Gas 1, H220 Press. Gas (Liq.), H280
1,3-butadiene; buta-1,3-diene (Impurity)	(CAS-No.) 106-99-0 (EC-No.) 203-450-8 (EC Index-No.) 601-013-00-X	<= 0.01	Flam. Gas 1, H220 Press. Gas Carc. 1A, H350 Muta. 1B, H340

Full text of H-statements: see section 16

3.2. Mixtures

Not applicable

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures after inhalation	: Move the affected person away from the contaminated area and into the fresh air. If you feel unwell, seek medical advice.
First-aid measures after skin contact	: In the event of contact with the liquid: treat resulting frostbite as a burn. Rinse with plenty of water. Do not remove clothing (since it may stick to the skin). If skin burns appear, call a doctor immediately.
First-aid measures after eye contact	: Rinse immediately and thoroughly, pulling the eyelids well away from the eye (15 minutes minimum). Consult an eye specialist immediately.
First-aid measures after ingestion	: Not specifically applicable (gas).

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects	: Contains refrigerated gas; may cause cryogenic burns or injury. anoxia (asphyxia). Disturbances of consciousness. Lack of oxygen: risk of death.
------------------	--

4.3. Indication of any immediate medical attention and special treatment needed

No additional information available

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media	: Water spray. Dry powder. Carbon dioxide.
Unsuitable extinguishing media	: Strong water jet.

5.2. Special hazards arising from the substance or mixture

Fire hazard	: Extremely flammable gas. Heating will cause a rise in pressure with a risk of bursting. Vapours are heavier than air and can cause suffocation by reducing oxygen available for breathing. Hazardous gas/vapours are formed in the event of decomposition (see section 10).
-------------	---

5.3. Advice for firefighters

Firefighting instructions	: Use water spray or fog for cooling exposed containers.
Protection during firefighting	: Self-contained breathing apparatus. Complete protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures	: Do not attempt to take action without suitable protective equipment. Avoid contact with skin and eyes. Do not breathe smoke. Do not smoke. Evacuate personnel to a safe area. Ventilate spillage area. Stop leak without risks if possible.
------------------	---

6.1.1. For non-emergency personnel

No additional information available

6.1.2. For emergency responders

No additional information available

6.2. Environmental precautions

Product evaporates rapidly when in contact with the air. Prevent entry to sewers and public waters.

6.3. Methods and material for containment and cleaning up

Other information	: Mechanically ventilate the spillage area.
-------------------	---

6.4. Reference to other sections

For further information refer to section 8: "Exposure controls/personal protection". For disposal of solid materials or residues refer to section 13: "Disposal considerations".

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling	: Ensure good ventilation of the work station. Pressurised container. Protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use. Use non-sparking tools. Avoid the build-up of electrostatic charge.
-------------------------------	--

PROPANE

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Hygiene measures : Do not drink, eat or smoke in the workplace.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Keep container tight closed. Store : in a cool, well-ventilated area.

Incompatible products : Oxidizing agent. Strong acids. alkali metals.

Packaging materials : Original packaging.

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

PROPANE (74-98-6)	
Sweden - Occupational Exposure Limits	
Anmärkning (SE)	V (Vägledande kortidsgränsvärde ska användas som ett rekommenderat högsta värde som inte bör överskridas)
propane (74-98-6)	
EU - Occupational Exposure Limits	
IOELV TWA (mg/m ³)	1800
IOELV TWA (ppm)	1000 ppm
Austria - Occupational Exposure Limits	
MAK (mg/m ³)	1800 mg/m ³
MAK (ppm)	1000 ppm
MAK Short time value (mg/m ³)	3600 mg/m ³
MAK Short time value (ppm)	2000 ppm
Denmark - Occupational Exposure Limits	
Grænseværdie (langvarig) (mg/m ³)	1800 mg/m ³
Grænseværdie (langvarig) (ppm)	1000 ppm
Greece - Occupational Exposure Limits	
OEL TWA (mg/m ³)	1800 mg/m ³
OEL TWA (ppm)	1000 ppm
Norway - Occupational Exposure Limits	
Local name	Propan
Grænseverdier (AN) (mg/m ³)	900 mg/m ³
Grænseverdier (AN) (ppm)	500 ppm
Isobutane (75-28-5)	
Austria - Occupational Exposure Limits	
Local name	Butan (beide Isomeren): Isobutan (R 600a)
MAK (mg/m ³)	1900 mg/m ³
MAK (ppm)	800 ppm
MAK Short time value (mg/m ³)	3800 mg/m ³
MAK Short time value (ppm)	1600 ppm
Regulatory reference	BGBl. II Nr. 186/2015
Belgium - Occupational Exposure Limits	
Local name	Hydrocarbures aliphatiques sous forme gazeuse : (Alcanes C1-C4)
Limit value (ppm)	1000 ppm
Regulatory reference	Koninklijk besluit/Arrêté royal 11/03/2002
Finland - Occupational Exposure Limits	
Local name	i-Butaani (2-Metyylipropaani)
HTP-arvo (8h) (mg/m ³)	1900 mg/m ³

PROPANE

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

HTP-arvo (8h) (ppm)	800 ppm
HTP-arvo (15 min)	2400 mg/m ³
HTP-arvo (15 min) (ppm)	1000 ppm
Huomautus (FI)	liite 4 (HAPPEA SYRJÄYTTÄMÄLLÄ TUKEHDUTTAVAT KAASUT)
Regulatory reference	HTP-ARVOT 2016 (Sosiaali- ja terveystieteiden ministeriö)
Germany - Occupational Exposure Limits (TRGS 900)	
TRGS 900 Local name	Isobutan
Occupational exposure limit value (mg/m ³)	2400 mg/m ³
Occupational exposure limit value (ppm)	1000 ppm
Limitation of exposure peaks	4(II)
TRGS 900 Remark	DFG
TRGS 900 Regulatory reference	TRGS900
Portugal - Occupational Exposure Limits	
Local name	Butano, todos os isómeros
OEL STEL (ppm)	1000 ppm
Regulatory reference	Norma Portuguesa NP 1796:2014
Slovakia - Occupational Exposure Limits	
Local name	bután s obsahom ≥ 0,1% butadiénu (n-bután) (izo-bután)
NPHV (priemerná) (mg/m ³)	2400 mg/m ³
NPHV (priemerná) (ppm)	1000 ppm
Regulatory reference	Nariadenie vlády č. 355/2006 Z. z. (Zmena: 83/2015 Z. z.)
Switzerland - Occupational Exposure Limits	
Local name	iso-Butan
MAK (mg/m ³)	1900 mg/m ³
MAK (ppm)	800 ppm
KZGW (mg/m ³)	7600 mg/m ³
KZGW (ppm)	3200 ppm
Remark	ZNS ^{KT}
Regulatory reference	SUVA - Grenzwerte am Arbeitsplatz 2016
n-Butane (106-97-8)	
Austria - Occupational Exposure Limits	
Local name	Butan (beide Isomeren): n-Butan (R 600)
MAK (mg/m ³)	1900 mg/m ³
MAK (ppm)	800 ppm
MAK Short time value (mg/m ³)	3800 mg/m ³
MAK Short time value (ppm)	1600 ppm
Belgium - Occupational Exposure Limits	
Local name	Hydrocarbures aliphatiques sous forme gazeuse : (Alcanes C1-C4)
Limit value (ppm)	1000 ppm
Denmark - Occupational Exposure Limits	
Local name	n-Butan
Grænseværdie (langvarig) (mg/m ³)	1200 mg/m ³
Grænseværdie (langvarig) (ppm)	500 ppm
Finland - Occupational Exposure Limits	
Local name	n-Butaani

PROPANE

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

HTP-arvo (8h) (mg/m ³)	1900 mg/m ³
HTP-arvo (8h) (ppm)	800 ppm
HTP-arvo (15 min)	2400 mg/m ³
HTP-arvo (15 min) (ppm)	1000 ppm
France - Occupational Exposure Limits	
Local name	n-Butane
VME (mg/m ³)	1900 mg/m ³
VME (ppm)	800 ppm
Germany - Occupational Exposure Limits (TRGS 900)	
TRGS 900 Local name	Butan
Occupational exposure limit value (mg/m ³)	2400 mg/m ³
Occupational exposure limit value (ppm)	1000 ppm
TRGS 900 Remark	DFG
Greece - Occupational Exposure Limits	
OEL TWA (mg/m ³)	2350 mg/m ³
OEL TWA (ppm)	1000 ppm
United Kingdom - Occupational Exposure Limits	
Local name	Butane
WEL TWA (mg/m ³)	1450 mg/m ³
WEL TWA (ppm)	600 ppm
WEL STEL (mg/m ³)	1810 mg/m ³
WEL STEL (ppm)	750 ppm
Remark (WEL)	Carc (Capable of causing cancer and/or heritable genetic damage. See paragraphs 49–51), (only applies if Butane contains more than 0.1% of buta-1,3-diene)
Norway - Occupational Exposure Limits	
Local name	Butan
Grenseverdier (AN) (mg/m ³)	600 mg/m ³
Grenseverdier (AN) (ppm)	250 ppm
Switzerland - Occupational Exposure Limits	
Local name	Butane (les 2 isomères):n-Butane
MAK (mg/m ³)	1900 mg/m ³
MAK (ppm)	800 ppm

8.2. Exposure controls

Hand protection:

Leather protective gloves. Nitrile-rubber protective gloves. VITON gloves

Eye protection:

Safety glasses with side shields

Skin and body protection:

Majority cotton protective clothing

Respiratory protection:

In the event of insufficient ventilation: Gas mask with filter type AX. In a confined area : Self-contained breathing apparatus

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state : Gas
Appearance : Press. Gas (Liq.).

PROPANE

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Colour	: Colourless.
Odour	: slightly ethereal.
Odour threshold	: No data available
pH	: Not applicable
Relative evaporation rate (butylacetate=1)	: No data available
Melting point	: -188 °C
Freezing point	: No data available
Boiling point	: -42.1 °C
Flash point	: -104 °C
Auto-ignition temperature	: 450 °C
Decomposition temperature	: No data available
Flammability (solid, gas)	: Extremely flammable gas.
Vapour pressure	: 7.3 bar (20°C)
Critical pressure	: 42.6 bar
Relative vapour density at 20 °C	: 1.81
Relative density	: 0.51 (20°C)
Solubility	: Poorly soluble in water. Soluble in : Alcohol, Ethers, Chloroform.
Log Pow	: 2.3
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosive properties	: Not explosive material according to EC criteria.
Oxidising properties	: Non oxidizing material according to EC criteria.
Lower explosive limit (LEL)	: 2.2 vol %
Upper explosive limit (UEL)	: 9.5 vol %

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

Stable under normal conditions of use.

10.2. Chemical stability

Stable at ambient temperature and under normal conditions of use.

10.3. Possibility of hazardous reactions

No dangerous polymerization.

10.4. Conditions to avoid

Pressurised container. Protect from sunlight and do not expose to temperatures exceeding 50°C. Container under pressure. Do not drill or burn even after use. No flames, no sparks. Eliminate all sources of ignition.

10.5. Incompatible materials

React in contact of alkali metals, Light metals. zinc. Magnesium. Strong oxidizing agents.

10.6. Hazardous decomposition products

Hazardous decomposition products may be released during prolonged heating like smokes, carbon monoxide and dioxide. Hydrogen fluoride. Carbonyl halogenides.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral)	: Not classified
Acute toxicity (dermal)	: Not classified
Acute toxicity (inhalation)	: Not classified

Isobutane (75-28-5)

LC50 inhalation rat (mg/l)	658 mg/l/4h
Skin corrosion/irritation	: Not classified pH: Not applicable
Additional information	: Contact with the liquid causes frostbite
Serious eye damage/irritation	: Not classified pH: Not applicable
Additional information	: Contact with the liquefied gas may cause severe ocular lesions
Respiratory or skin sensitisation	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified

PROPANE

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Reproductive toxicity	: Not classified
STOT-single exposure	: Not classified
STOT-repeated exposure	: Not classified
Aspiration hazard	: Not classified

SECTION 12: Ecological information

12.1. Toxicity

Hazardous to the aquatic environment, short-term (acute)	: Not classified
Hazardous to the aquatic environment, long-term (chronic)	: Not classified

12.2. Persistence and degradability

propane (74-98-6)

Persistence and degradability	< 60 % biodegradation after 28 days.
-------------------------------	--------------------------------------

Isobutane (75-28-5)

Persistence and degradability	< 60 % biodegradation after 28 days.
-------------------------------	--------------------------------------

n-Butane (106-97-8)

Persistence and degradability	Readily biodegradable.
-------------------------------	------------------------

12.3. Bioaccumulative potential

PROPANE (74-98-6)

Log Pow	2.3
---------	-----

12.4. Mobility in soil

No additional information available

12.5. Results of PBT and vPvB assessment

Component

propane (74-98-6)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII
Isobutane (75-28-5)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII
n-Butane (106-97-8)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII

12.6. Other adverse effects

Other adverse effects : Ozone depletion factor ODP (R-11=1) = 0. Total global warming potential (GWP) : 3.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Regional legislation (waste)	: Switzerland : OTD : RS 814.600 / OMoD : RS 814.610.
Product/Packaging disposal recommendations	: Methods of disposal of packaging. Reuse or recycle following decontamination. Destroy at an authorised site.
Additional information	: The user's attention is drawn to the possible existence of specific european, national or local regulations regarding disposal. Refer to manufacturer or supplier for information on recovery or recycling.
Ecology - waste materials	: Must not be discharged to atmosphere. Refer to manufacturer or supplier for information on recovery or recycling.

SECTION 14: Transport information





In accordance with ADR / IATA / IMDG / RID

ADR	IMDG	IATA	RID
14.1. UN number			
UN 1978	UN 1978	UN 1978	UN 1978
14.2. UN proper shipping name			
PROPANE	PROPANE	Propane	PROPANE

PROPANE

Safety Data Sheet


according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Transport document description			
UN 1978 PROPANE, 2.1, (B/D)	UN 1978 PROPANE, 2.1	UN 1978 Propane, 2.1	UN 1978 PROPANE, 2.1
14.3. Transport hazard class(es)			
2.1	2.1	2.1	2.1
			
14.4. Packing group			
Not applicable	Not applicable	Not applicable	Not applicable
14.5. Environmental hazards			
Dangerous for the environment : No	Dangerous for the environment : No Marine pollutant : No	Dangerous for the environment : No	Dangerous for the environment : No
No supplementary information available			

14.6. Special precautions for user

Overland transport

Classification code (ADR) : 2F
Special provisions (ADR) : 392, 652, 657, 662, 674
Limited quantities (ADR) : 0
Tank code (ADR) : PxBN(M)
Transport category (ADR) : 2
Hazard identification number (Kemler No.) : 23
Orange plates :



Tunnel restriction code (ADR) : B/D
EAC code : 2YE

Transport by sea

EmS-No. (Fire) : F-D
EmS-No. (Spillage) : S-U

Air transport

PCA Limited quantities (IATA) : Forbidden
PCA limited quantity max net quantity (IATA) : Forbidden
PCA packing instructions (IATA) : Forbidden
PCA max net quantity (IATA) : Forbidden
CAO packing instructions (IATA) : 200
CAO max net quantity (IATA) : 150kg
Special provisions (IATA) : A1

Rail transport

Classification code (RID) : 2F
Special provisions (RID) : 392, 657, 662, 674
Limited quantities (RID) : 0
Tank codes for RID tanks (RID) : PxBN(M)
Transport category (RID) : 2
Colis express (express parcels) (RID) : CE3
Hazard identification number (RID) : 23

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable

PROPANE

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

No REACH Annex XVII restrictions

PROPANE is not on the REACH Candidate List

PROPANE is not on the REACH Annex XIV List

PROPANE is not subject to Regulation (EU) No 649/2012 of the European Parliament and of the Council of 4 July 2012 concerning the export and import of hazardous chemicals.

PROPANE is not subject to Regulation (EU) No 2019/1021 of the European Parliament and of the Council of 20 June 2019 on persistent organic pollutants

15.1.2. National regulations

Ensure all national/local regulations are observed.

Germany

Reference to AwSV : Water hazard class (WGK) 1, Slightly hazardous to water (ID No. 560)

12th Ordinance Implementing the Federal Immission Control Act - 12.BImSchV : Is not subject of the 12. BImSchV (Hazardous Incident Ordinance)

Netherlands

SZW-lijst van kankerverwekkende stoffen : The substance is not listed

SZW-lijst van mutagene stoffen : The substance is not listed

NIET-limitatieve lijst van voor de voortplanting giftige stoffen – Borstvoeding : The substance is not listed

NIET-limitatieve lijst van voor de voortplanting giftige stoffen – Vruchtbaarheid : The substance is not listed

NIET-limitatieve lijst van voor de voortplanting giftige stoffen – Ontwikkeling : The substance is not listed

Denmark

Class for fire hazard : Class I-1

Store unit : 1 liter

Classification remarks : F+ <Flam. Gas 1; Press. Gas (Liq.)>; Emergency management guidelines for the storage of flammable liquids must be followed

Danish National Regulations : Young people below the age of 18 years are not allowed to use the product

Switzerland

Swiss National Regulations : ORRChim RS 814.81.

15.2. Chemical safety assessment

No additional information available

SECTION 16: Other information

Indication of changes:

Section	Changed item	Change	Comments
1.1	Article number	Modified	
1.3	Supplier	Modified	
3.1	Concentration	Modified	

Other information : For more information regarding the use of this product, please refer to our technical information or contact the sales department in your region.

Full text of H- and EUH-statements:

Carc. 1A	Carcinogenicity, Category 1A
Flam. Gas 1	Flammable gases, Category 1
Muta. 1B	Germ cell mutagenicity, Category 1B
Press. Gas	Gases under pressure
Press. Gas (Liq.)	Gases under pressure : Liquefied gas
H220	Extremely flammable gas.
H280	Contains gas under pressure; may explode if heated.
H340	May cause genetic defects.

PROPANE

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

H350	May cause cancer.
Full text of use descriptors	
ERC2	Formulation into mixture
ERC3	Formulation into solid matrix
ERC8a	Widespread use of non-reactive processing aid (no inclusion into or onto article, indoor)
PC0	Other
PC24	Lubricants, greases, release products
PC29	Pharmaceuticals
PC3	Air care products
PC32	Polymer preparations and compounds
PC34	Textile dyes, and impregnating products
PC35	Washing and cleaning products
PC39	Cosmetics, personal care products
PC8	Biocidal products
PC9a	Coatings and paints, thinners, paint removers
PC9b	Fillers, putties, plasters, modelling clay
PROC1	Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions
PROC11	Non-industrial spraying
PROC12	Use of blowing agents in manufacture of foam
PROC2	Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions
PROC3	Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition
PROC5	Mixing or blending in batch processes
PROC7	Industrial spraying
PROC9	Transfer of substance or mixture into small containers (dedicated filling line, including weighing)
SU10	Formulation [mixing] of preparations and/or re-packaging (excluding alloys)
SU12	Manufacture of plastics products, including compounding and conversion
SU21	Consumer uses: Private households (= general public = consumers)
SU22	Professional uses: Public domain (administration, education, entertainment, services, craftsmen)
SU3	

SDS EU (REACH Annex II)

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.