

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## Opteon™ XL40 (R-454A) Refrigerant

Version	Revision Date:	SDS Number:	Date of last issue: 22.10.2019
4.0	02.03.2020	1354839-00037	Date of first issue: 27.02.2017

---

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

Trade name	:	Opteon™ XL40 (R-454A) Refrigerant
Product code	:	D15438149
SDS-Identcode	:	130000143546

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Substance/Mixture	:	Refrigerant
Recommended restrictions on use	:	For professional and industrial installation and use only., Do not use product for anything outside of the above specified uses

#### 1.3 Details of the supplier of the safety data sheet

Company	:	Chemours Netherlands B.V. Baanhoekweg 22 3313 LA Dordrecht Netherlands
Telephone	:	+31-(0)-78-630-1011
Telefax	:	+31-78-6163737
E-mail address of person responsible for the SDS	:	sds-support@chemours.com

#### 1.4 Emergency telephone number

+(44)-870-8200418 (CHEMTREC - Recommended)

---

### SECTION 2: Hazards identification

#### 2.1 Classification of the substance or mixture

##### Classification (REGULATION (EC) No 1272/2008)

Flammable gases, Category 1B	H221: Flammable gas.
Gases under pressure, Liquefied gas	H280: Contains gas under pressure; may explode if heated.

#### 2.2 Label elements

##### Labelling (REGULATION (EC) No 1272/2008)



# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## Opteon™ XL40 (R-454A) Refrigerant

Version 4.0      Revision Date: 02.03.2020      SDS Number: 1354839-00037      Date of last issue: 22.10.2019  
Date of first issue: 27.02.2017

Hazard pictograms	:	 
Signal word	:	Danger
Hazard statements	:	H221 Flammable gas. H280 Contains gas under pressure; may explode if heated.
Precautionary statements	:	<b>Prevention:</b> P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. <b>Response:</b> P377 Leaking gas fire: Do not extinguish, unless leak can be stopped safely. P381 In case of leakage, eliminate all ignition sources. <b>Storage:</b> P410 + P403 Protect from sunlight. Store in a well-ventilated place.

### Additional Labelling

Contains fluorinated greenhouse gases. (HFC-32)

### 2.3 Other hazards

This mixture contains no substance considered to be persistent, bioaccumulating and toxic (PBT).  
This mixture contains no substance considered to be very persistent and very bioaccumulating (vPvB).  
Vapours are heavier than air and can cause suffocation by reducing oxygen available for breathing.  
Misuse or intentional inhalation abuse may cause death without warning symptoms, due to cardiac effects.  
Rapid evaporation of the product may cause frostbite.  
May displace oxygen and cause rapid suffocation.

## SECTION 3: Composition/information on ingredients

### 3.2 Mixtures

#### Components

Chemical name	CAS-No. EC-No. Index-No. Registration number	Classification	Concentration (% w/w)
2,3,3,3-Tetrafluoropropene*	754-12-1 468-710-7 01-0000019665-61	Flam. Gas 1B; H221 Press. Gas Liquefied gas; H280	65
Difluoromethane*	75-10-5 200-839-4	Flam. Gas 1B; H221 Press. Gas Liquefied	35

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## Opteon™ XL40 (R-454A) Refrigerant

Version	Revision Date:	SDS Number:	Date of last issue: 22.10.2019
4.0	02.03.2020	1354839-00037	Date of first issue: 27.02.2017

	01-2119471312-47	gas; H280	
--	------------------	-----------	--

\* Voluntarily-disclosed non-hazardous substance  
For explanation of abbreviations see section 16.

### SECTION 4: First aid measures

#### 4.1 Description of first aid measures

- General advice : In the case of accident or if you feel unwell, seek medical advice immediately.  
When symptoms persist or in all cases of doubt seek medical advice.
- Protection of first-aiders : No special precautions are necessary for first aid responders.
- If inhaled : If inhaled, remove to fresh air.  
Get medical attention if symptoms occur.
- In case of skin contact : Thaw frosted parts with lukewarm water. Do not rub affected area.  
Get medical attention immediately.
- In case of eye contact : Get medical attention immediately.
- If swallowed : Ingestion is not considered a potential route of exposure.

#### 4.2 Most important symptoms and effects, both acute and delayed

- Symptoms : May cause cardiac arrhythmia.
- Other symptoms potentially related to misuse or inhalation abuse are  
Cardiac sensitisation  
Anaesthetic effects  
Light-headedness  
Dizziness  
confusion  
Lack of coordination  
Drowsiness  
Unconsciousness
- Risks : Contact with liquid or refrigerated gas can cause cold burns and frostbite.

#### 4.3 Indication of any immediate medical attention and special treatment needed

- Treatment : Because of possible disturbances of cardiac rhythm, catecholamine drugs, such as epinephrine, that may be used in situations of emergency life support should be used with special caution.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## Opteon™ XL40 (R-454A) Refrigerant

Version	Revision Date:	SDS Number:	Date of last issue: 22.10.2019
4.0	02.03.2020	1354839-00037	Date of first issue: 27.02.2017

---

### SECTION 5: Firefighting measures

#### 5.1 Extinguishing media

Suitable extinguishing media : Water spray  
Alcohol-resistant foam  
Carbon dioxide (CO<sub>2</sub>)  
Dry chemical

Unsuitable extinguishing media : None known.

#### 5.2 Special hazards arising from the substance or mixture

Specific hazards during fire-fighting : Vapours may form flammable mixture with air  
Exposure to combustion products may be a hazard to health.  
If the temperature rises there is danger of the vessels bursting due to the high vapor pressure.

Hazardous combustion products : Hydrogen fluoride  
Fluorine compounds  
Carbon oxides  
carbonyl fluoride

#### 5.3 Advice for firefighters

Special protective equipment for firefighters : Wear self-contained breathing apparatus for firefighting if necessary. Use personal protective equipment.

Specific extinguishing methods : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.  
Fight fire remotely due to the risk of explosion.  
Use water spray to cool unopened containers.  
Leaking gas fire: Do not extinguish, unless leak can be stopped safely.  
Remove undamaged containers from fire area if it is safe to do so.  
Evacuate area.

---

### SECTION 6: Accidental release measures

#### 6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Evacuate personnel to safe areas.  
Only trained personnel should re-enter the area.  
Remove all sources of ignition.  
Avoid skin contact with leaking liquid (danger of frostbite).  
Ventilate the area.  
Follow safe handling advice and personal protective equipment recommendations.

#### 6.2 Environmental precautions

Environmental precautions : Prevent further leakage or spillage if safe to do so.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## Opteon™ XL40 (R-454A) Refrigerant

Version	Revision Date:	SDS Number:	Date of last issue: 22.10.2019
4.0	02.03.2020	1354839-00037	Date of first issue: 27.02.2017

---

Retain and dispose of contaminated wash water.

### 6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Ventilate the area.  
Non-sparking tools should be used.  
Suppress (knock down) gases/vapours/mists with a water spray jet.  
Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which regulations are applicable.  
Sections 13 and 15 of this SDS provide information regarding certain local or national requirements.

### 6.4 Reference to other sections

See sections: 7, 8, 11, 12 and 13.

---

## SECTION 7: Handling and storage

### 7.1 Precautions for safe handling

Technical measures : Use equipment rated for cylinder pressure. Use a backflow preventative device in piping. Close valve after each use and when empty.

Local/Total ventilation : If sufficient ventilation is unavailable, use with local exhaust ventilation.  
If advised by assessment of the local exposure potential, use only in an area equipped with explosion-proof exhaust ventilation.

Advice on safe handling : Handle in accordance with good industrial hygiene and safety practice, based on the results of the workplace exposure assessment  
Keep container tightly closed.  
Wear cold insulating gloves/ face shield/ eye protection.  
Prevent backflow into the gas tank.  
Open the valves slowly to prevent pressure surges.  
Close valve after each use and when empty. Do NOT change or force fit connections.  
Prevent the intrusion of water into the gas tank.  
Keep away from heat and sources of ignition.  
Take precautionary measures against static discharges.  
Take care to prevent spills, waste and minimize release to the environment.

Avoid breathing gas.  
Valve protection caps and valve outlet threaded plugs must remain in place unless container is secured with valve outlet piped to use point.  
Use a check valve or trap in the discharge line to prevent hazardous back flow into the cylinder.  
Use a pressure reducing regulator when connecting cylinder

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## Opteon™ XL40 (R-454A) Refrigerant

Version	Revision Date:	SDS Number:	Date of last issue: 22.10.2019
4.0	02.03.2020	1354839-00037	Date of first issue: 27.02.2017

---

to lower pressure (<3000 psig) piping or systems.  
Never attempt to lift cylinder by its cap.  
Do not drag, slide or roll cylinders.  
Use a suitable hand truck for cylinder movement.

Hygiene measures : If exposure to chemical is likely during typical use, provide eye flushing systems and safety showers close to the working place. When using do not eat, drink or smoke. Wash contaminated clothing before re-use.

### 7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers : Cylinders should be stored upright and firmly secured to prevent falling or being knocked over. Separate full containers from empty containers. Do not store near combustible materials. Avoid area where salt or other corrosive materials are present. Keep in properly labelled containers. Keep tightly closed. Keep in a cool, well-ventilated place. Keep away from direct sunlight. Store in accordance with the particular national regulations. Keep away from heat and sources of ignition.

Advice on common storage : Do not store with the following product types:  
Self-reactive substances and mixtures  
Organic peroxides  
Oxidizing agents  
Flammable liquids  
Flammable solids  
Pyrophoric liquids  
Pyrophoric solids  
Self-heating substances and mixtures  
Substances and mixtures, which in contact with water, emit flammable gases  
Explosives  
Acutely toxic substances and mixtures  
Substances and mixtures with chronic toxicity

Storage period : > 10 yr

Recommended storage temperature : < 52 °C

Further information on storage stability : The product has an indefinite shelf life when stored properly.

### 7.3 Specific end use(s)

Specific use(s) : No data available

---

## SECTION 8: Exposure controls/personal protection

### 8.1 Control parameters

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## Opteon™ XL40 (R-454A) Refrigerant

Version 4.0      Revision Date: 02.03.2020      SDS Number: 1354839-00037      Date of last issue: 22.10.2019  
Date of first issue: 27.02.2017

### Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

Substance name	End Use	Exposure routes	Potential health effects	Value
2,3,3,3-Tetrafluoropropene	Workers	Inhalation	Long-term systemic effects	950 mg/m <sup>3</sup>
Difluoromethane	Workers	Inhalation	Long-term systemic effects	7035 mg/m <sup>3</sup>
	Consumers	Inhalation	Long-term systemic effects	750 mg/m <sup>3</sup>

### Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

Substance name	Environmental Compartment	Value
2,3,3,3-Tetrafluoropropene	Fresh water	0.1 mg/l
	Intermittent use/release	1 mg/l
	Fresh water sediment	1.77 mg/kg dry weight (d.w.)
	Soil	1.54 mg/kg dry weight (d.w.)
	Marine water	0.01 mg/l
	Marine sediment	0.178 mg/kg dry weight (d.w.)
Difluoromethane	Fresh water	0.142 mg/l
	Intermittent use/release	1.42 mg/l
	Fresh water sediment	0.534 mg/kg

## 8.2 Exposure controls

### Engineering measures

Minimize workplace exposure concentrations.

If sufficient ventilation is unavailable, use with local exhaust ventilation.

If advised by assessment of the local exposure potential, use only in an area equipped with explosion-proof exhaust ventilation.

### Personal protective equipment

Eye protection : Wear the following personal protective equipment:  
Chemical resistant goggles must be worn.  
Face-shield  
Equipment should conform to BS EN 166

Hand protection

Material : Impervious gloves

Remarks

: Choose gloves to protect hands against chemicals depending on the concentration and quantity of the hazardous substance and specific to place of work. For special applications, we recommend clarifying the resistance to chemicals of the aforementioned protective gloves with the glove manufacturer. Wash hands before breaks and at the end of workday. Breakthrough time is not determined for the product. Change gloves often!

Skin and body protection

: Wear the following personal protective equipment:  
If assessment demonstrates that there is a risk of explosive

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## Opteon™ XL40 (R-454A) Refrigerant

Version	Revision Date:	SDS Number:	Date of last issue: 22.10.2019
4.0	02.03.2020	1354839-00037	Date of first issue: 27.02.2017

atmospheres or flash fires, use flame retardant antistatic protective clothing.

- |                        |   |  |
|------------------------|---|--|
| Respiratory protection | : | If adequate local exhaust ventilation is not available or exposure assessment demonstrates exposures outside the recommended guidelines, use respiratory protection. Equipment should conform to BS EN 14387 |
| Filter type            | : | Organic gas and low boiling vapour type (AX)   |
| Protective measures    | : | Wear cold insulating gloves/ face shield/ eye protection.  |

### SECTION 9: Physical and chemical properties

#### 9.1 Information on basic physical and chemical properties

- |  |   |  |
|--|---|--|
| Appearance                                       | : | Liquefied gas  |
| Colour   | : | clear, colourless  |
| Odour  | : | slight, ether-like   |
| Odour Threshold                                  | : | No data available  |
| pH   | : | No data available  |
| Melting point/freezing point                     | : | No data available  |
| Initial boiling point and boiling range          | : | -48.3 °C   |
| Flash point                                      | : | Not applicable   |
| Evaporation rate                                 | : | > 1<br>(CCL4=1.0)  |
| Flammability (solid, gas)                        | : | Flammable  |
| Upper explosion limit / Upper flammability limit | : | Upper flammability limit<br>< 15 %(V)<br>Method: ASTM E681 |
| Lower explosion limit / Lower flammability limit | : | Lower flammability limit<br>> 8 %(V)<br>Method: ASTM E681  |
| Vapour pressure                                  | : | 15,244 hPa (25 °C)   |
| Relative vapour density                          | : | 2.83<br>(Air = 1.0)  |
| Relative density                                 | : | 0.98 (25 °C)   |



# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## Opteon™ XL40 (R-454A) Refrigerant

Version 4.0      Revision Date: 02.03.2020      SDS Number: 1354839-00037      Date of last issue: 22.10.2019  
Date of first issue: 27.02.2017

---

### Solubility(ies)

Water solubility : No data available

Partition coefficient: n-octanol/water : Not applicable

Auto-ignition temperature : 457 °C

Decomposition temperature : No data available

### Viscosity

Viscosity, kinematic : Not applicable

Explosive properties : Not explosive

Oxidizing properties : The substance or mixture is not classified as oxidizing.

## 9.2 Other information

Particle size : Not applicable

---

## SECTION 10: Stability and reactivity

### 10.1 Reactivity

Not classified as a reactivity hazard.

### 10.2 Chemical stability

Stable if used as directed. Follow precautionary advice and avoid incompatible materials and conditions.

### 10.3 Possibility of hazardous reactions

Hazardous reactions : Vapours may form flammable mixture with air  
Can react with strong oxidizing agents.  
Flammable gas.

### 10.4 Conditions to avoid

Conditions to avoid : Heat, flames and sparks.

### 10.5 Incompatible materials

Materials to avoid : Avoid impurities (e.g. rust, dust, ash), risk of decomposition.  
Incompatible with acids and bases.  
Incompatible with oxidizing agents.  
Oxygen  
Peroxides  
peroxide compounds  
Powdered metals

### 10.6 Hazardous decomposition products

No hazardous decomposition products are known.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## Opteon™ XL40 (R-454A) Refrigerant

Version 4.0      Revision Date: 02.03.2020      SDS Number: 1354839-00037      Date of last issue: 22.10.2019  
Date of first issue: 27.02.2017

### SECTION 11: Toxicological information

#### 11.1 Information on toxicological effects

Information on likely routes of exposure : Inhalation  
Skin contact  
Eye contact

#### Acute toxicity

Not classified based on available information.

#### Components:

##### **2,3,3,3-Tetrafluoropropene:**

Acute inhalation toxicity : LC50 (Rat): > 405800 ppm  
Exposure time: 4 h  
Test atmosphere: gas  
Method: OECD Test Guideline 403

No observed adverse effect concentration (Dog): 120000 ppm  
Test atmosphere: gas  
Remarks: Cardiac sensitisation

Lowest observed adverse effect concentration (Dog): > 120000 ppm  
Test atmosphere: gas  
Remarks: Cardiac sensitisation

Cardiac sensitisation threshold limit (Dog): > 559,509 mg/m3  
Test atmosphere: gas  
Remarks: Cardiac sensitisation

##### **Difluoromethane:**

Acute inhalation toxicity : LC50 (Rat): > 520000 ppm  
Exposure time: 4 h  
Test atmosphere: gas

Lowest observed adverse effect concentration (Dog): > 350000 ppm  
Symptoms: Cardiac sensitisation

No observed adverse effect concentration (Dog): 350000 ppm  
Symptoms: Cardiac sensitisation

Cardiac sensitisation threshold limit (Dog): > 735,000 mg/m3  
Symptoms: Cardiac sensitisation

#### Skin corrosion/irritation

Not classified based on available information.

#### Components:

##### **2,3,3,3-Tetrafluoropropene:**

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## Opteon™ XL40 (R-454A) Refrigerant

Version 4.0      Revision Date: 02.03.2020      SDS Number: 1354839-00037      Date of last issue: 22.10.2019  
Date of first issue: 27.02.2017

---

|||Result : No skin irritation

### Difluoromethane:

|||Species : Not tested on animals  
|||Result : No skin irritation

### Serious eye damage/eye irritation

Not classified based on available information.

### Components:

#### 2,3,3,3-Tetrafluoropropene:

|||Result : No eye irritation

### Difluoromethane:

|||Species : Not tested on animals  
|||Result : No eye irritation

### Respiratory or skin sensitisation

#### Skin sensitisation

Not classified based on available information.

#### Respiratory sensitisation

Not classified based on available information.

### Components:

#### 2,3,3,3-Tetrafluoropropene:

|||Exposure routes : Skin contact  
|||Result : negative

### Difluoromethane:

|||Exposure routes : Skin contact  
|||Species : Not tested on animals  
|||Result : negative

|||Species : Not tested on animals  
|||Result : negative

### Germ cell mutagenicity

Not classified based on available information.

### Components:

#### 2,3,3,3-Tetrafluoropropene:

|||Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)  
Method: OECD Test Guideline 471  
Result: positive  
  
Test Type: Chromosome aberration test in vitro

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## Opteon™ XL40 (R-454A) Refrigerant

Version 4.0      Revision Date: 02.03.2020      SDS Number: 1354839-00037      Date of last issue: 22.10.2019  
Date of first issue: 27.02.2017

Genotoxicity in vivo : Method: OECD Test Guideline 473  
Result: negative

: Test Type: Mammalian erythrocyte micronucleus test (in vivo cyto-genetic assay)  
Species: Mouse  
Application Route: inhalation (gas)  
Method: OECD Test Guideline 474  
Result: negative

Test Type: In vivo mammalian alkaline comet assay  
Species: Rat  
Application Route: inhalation (gas)  
Method: OECD Test Guideline 489  
Result: negative

Test Type: Mammalian erythrocyte micronucleus test (in vivo cyto-genetic assay)  
Species: Rat  
Application Route: inhalation (gas)  
Method: OECD Test Guideline 474  
Result: negative

Germ cell mutagenicity- Assessment : Weight of evidence does not support classification as a germ cell mutagen.

### Difluoromethane:

Germ cell mutagenicity- Assessment : Weight of evidence does not support classification as a germ cell mutagen.

### Carcinogenicity

Not classified based on available information.

### Components:

#### 2,3,3,3-Tetrafluoropropene:

Result : negative

Carcinogenicity - Assessment : Weight of evidence does not support classification as a carcinogen

### Reproductive toxicity

Not classified based on available information.

### Components:

#### 2,3,3,3-Tetrafluoropropene:

Effects on fertility : Test Type: Two-generation reproduction toxicity study  
Species: Rat  
Application Route: inhalation (gas)  
Method: OECD Test Guideline 416  
Result: negative

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## Opteon™ XL40 (R-454A) Refrigerant

Version 4.0      Revision Date: 02.03.2020      SDS Number: 1354839-00037      Date of last issue: 22.10.2019  
Date of first issue: 27.02.2017

Effects on foetal development : Test Type: Prenatal development toxicity study (teratogenicity)  
Species: Rat  
Application Route: inhalation (gas)  
Method: OECD Test Guideline 414  
Result: negative

Reproductive toxicity - Assessment : Weight of evidence does not support classification for reproductive toxicity, No effects on or via lactation

### Difluoromethane:

Reproductive toxicity - Assessment : Weight of evidence does not support classification for reproductive toxicity, Based on data from similar materials

### STOT - single exposure

Not classified based on available information.

### Components:

#### 2,3,3,3-Tetrafluoropropene:

Exposure routes : inhalation (gas)  
Assessment : No significant health effects observed in animals at concentrations of 20000 ppmV/4h or less

### STOT - repeated exposure

Not classified based on available information.

### Components:

#### 2,3,3,3-Tetrafluoropropene:

Exposure routes : inhalation (gas)  
Assessment : No significant health effects observed in animals at concentrations of 250 ppmV/6h/d or less.

### Difluoromethane:

Assessment : No significant health effects observed in animals at concentrations of 250 ppmV/6h/d or less.

### Repeated dose toxicity

### Components:

#### 2,3,3,3-Tetrafluoropropene:

Species : Rat, male and female  
NOAEL : 50000 ppm  
LOAEL : >50000 ppm  
Application Route : inhalation (gas)  
Exposure time : 13 Weeks  
Method : OECD Test Guideline 413

### Difluoromethane:

Species : Rat

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## Opteon™ XL40 (R-454A) Refrigerant

Version 4.0      Revision Date: 02.03.2020      SDS Number: 1354839-00037      Date of last issue: 22.10.2019  
Date of first issue: 27.02.2017

NOAEL : 49100 ppm  
Application Route : inhalation (gas)  
Exposure time : 90 d  
Remarks : No significant adverse effects were reported

### Aspiration toxicity

Not classified based on available information.

### Components:

#### 2,3,3,3-Tetrafluoropropene:

No aspiration toxicity classification

## SECTION 12: Ecological information

### 12.1 Toxicity

#### Components:

##### 2,3,3,3-Tetrafluoropropene:

Toxicity to fish : LC50 (Cyprinus carpio (Carp)): > 197 mg/l  
Exposure time: 96 h  
Method: OECD Test Guideline 203

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 100 mg/l  
Exposure time: 48 h  
Method: OECD Test Guideline 202

Toxicity to algae/aquatic plants : EC50 (Selenastrum capricornutum (green algae)): > 100 mg/l  
Exposure time: 72 h  
Method: OECD Test Guideline 201

NOEC (Selenastrum capricornutum (green algae)): > 75 mg/l  
Exposure time: 3 d  
Method: OECD Test Guideline 201

##### Difluoromethane:

Toxicity to fish : LC50 (Fish): 1,507 mg/l  
Exposure time: 96 h

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia (water flea)): 652 mg/l  
Exposure time: 48 h

Toxicity to algae/aquatic plants : EC50 (algae): 142 mg/l  
Exposure time: 96 h

Toxicity to fish (Chronic toxicity) : NOEC: 65.8 mg/l  
Exposure time: 30 d  
Species: Fish

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## Opteon™ XL40 (R-454A) Refrigerant

Version 4.0      Revision Date: 02.03.2020      SDS Number: 1354839-00037      Date of last issue: 22.10.2019  
Date of first issue: 27.02.2017

---

### 12.2 Persistence and degradability

#### Components:

##### **2,3,3,3-Tetrafluoropropene:**

Biodegradability : Result: Not readily biodegradable.  
Method: OECD Test Guideline 301F

##### **Difluoromethane:**

Biodegradability : Result: Not readily biodegradable.  
Biodegradation: 5 %  
Exposure time: 28 d  
Method: OECD Test Guideline 301D

### 12.3 Bioaccumulative potential

#### Components:

##### **2,3,3,3-Tetrafluoropropene:**

Bioaccumulation : Remarks: Bioaccumulation is unlikely.

Partition coefficient: n-octanol/water : log Pow: 2 (25 °C)

##### **Difluoromethane:**

Partition coefficient: n-octanol/water : log Pow: 0.714

### 12.4 Mobility in soil

No data available

### 12.5 Results of PBT and vPvB assessment

#### Product:

Assessment : This mixture contains no substance considered to be persistent, bioaccumulating and toxic (PBT).. This mixture contains no substance considered to be very persistent and very bioaccumulating (vPvB)..

### 12.6 Other adverse effects

#### **Global warming potential**

Regulation (EU) No 517/2014 on fluorinated greenhouse gases

#### Product:

100-year global warming potential: 239

---

## SECTION 13: Disposal considerations

### 13.1 Waste treatment methods

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## Opteon™ XL40 (R-454A) Refrigerant

Version	Revision Date:	SDS Number:	Date of last issue: 22.10.2019
4.0	02.03.2020	1354839-00037	Date of first issue: 27.02.2017

- Product** : Dispose of in accordance with local regulations. According to the European Waste Catalogue, Waste Codes are not product specific, but application specific. Waste codes should be assigned by the user, preferably in discussion with the waste disposal authorities.
- Contaminated packaging** : Empty containers should be taken to an approved waste handling site for recycling or disposal. Empty pressure vessels should be returned to the supplier. Empty containers retain residue and can be dangerous. Do not pressurize, cut, weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks, or other sources of ignition. They may explode and cause injury and/or death. If not otherwise specified: Dispose of as unused product.

### SECTION 14: Transport information

#### 14.1 UN number

- |                  |  |
|------------------|--|
| ADN              | : UN 3161                                |
| ADR              | : UN 3161                                |
| RID              | : UN 3161                                |
| IMDG             | : UN 3161                                |
| IATA (Cargo)     | : UN 3161                                |
| IATA (Passenger) | : UN 3161<br>Not permitted for transport |

#### 14.2 UN proper shipping name

- |                  |   |
|------------------|---|
| ADN              | : LIQUEFIED GAS, FLAMMABLE, N.O.S.<br>(2,3,3,3-Tetrafluoropropene, Difluoromethane) |
| ADR              | : LIQUEFIED GAS, FLAMMABLE, N.O.S.<br>(2,3,3,3-Tetrafluoropropene, Difluoromethane) |
| RID              | : LIQUEFIED GAS, FLAMMABLE, N.O.S.<br>(2,3,3,3-Tetrafluoropropene, Difluoromethane) |
| IMDG             | : LIQUEFIED GAS, FLAMMABLE, N.O.S.<br>(2,3,3,3-Tetrafluoropropene, Difluoromethane) |
| IATA (Cargo)     | : Liquefied gas, flammable, n.o.s.<br>(2,3,3,3-Tetrafluoropropene, Difluoromethane) |
| IATA (Passenger) | : LIQUEFIED GAS, FLAMMABLE, N.O.S.<br>Not permitted for transport                   |

#### 14.3 Transport hazard class(es)

- |      |       |
|------|-------|
| ADN  | : 2   |
| ADR  | : 2   |
| RID  | : 2   |
| IMDG | : 2.1 |



# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## Opteon™ XL40 (R-454A) Refrigerant

Version 4.0      Revision Date: 02.03.2020      SDS Number: 1354839-00037      Date of last issue: 22.10.2019  
Date of first issue: 27.02.2017

---

**IATA (Cargo)** : 2.1  
**IATA (Passenger)** : Not permitted for transport

### 14.4 Packing group

**ADN**  
Packing group : Not assigned by regulation  
Classification Code : 2F  
Hazard Identification Number : 23  
Labels : 2.1

**ADR**  
Packing group : Not assigned by regulation  
Classification Code : 2F  
Hazard Identification Number : 23  
Labels : 2.1  
Tunnel restriction code : (B/D)

**RID**  
Packing group : Not assigned by regulation  
Classification Code : 2F  
Hazard Identification Number : 23  
Labels : 2.1 ((13))

**IMDG**  
Packing group : Not assigned by regulation  
Labels : 2.1  
EmS Code : F-D, S-U

**IATA (Cargo)**  
Packing instruction (cargo aircraft) : 200  
Packing group : Not assigned by regulation  
Labels : Flammable Gas  
**IATA (Passenger)** : Not permitted for transport

### 14.5 Environmental hazards

**ADN**  
Environmentally hazardous : no

**ADR**  
Environmentally hazardous : no

**RID**  
Environmentally hazardous : no

**IMDG**  
Marine pollutant : no

### 14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

### 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

**Remarks** : Not applicable for product as supplied.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## Opteon™ XL40 (R-454A) Refrigerant

Version 4.0      Revision Date: 02.03.2020      SDS Number: 1354839-00037      Date of last issue: 22.10.2019  
Date of first issue: 27.02.2017

---

### SECTION 15: Regulatory information

#### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, preparations and articles (Annex XVII) : Not applicable

REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59). : Not applicable

REACH - List of substances subject to authorisation (Annex XIV) : Not applicable

Regulation (EC) No 1005/2009 on substances that deplete the ozone layer : Not applicable

Regulation (EU) 2019/1021 on persistent organic pollutants (recast) : Not applicable

Regulation (EC) No 649/2012 of the European Parliament and the Council concerning the export and import of dangerous chemicals : Not applicable

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.

P2	FLAMMABLE GASES	Quantity 1 10 t	Quantity 2 50 t
----	-----------------	--------------------	--------------------

#### Other regulations:

Take note of Directive 94/33/EC on the protection of young people at work or stricter national regulations, where applicable.

#### 15.2 Chemical safety assessment

Chemical Safety Assessments have been carried out for these substances.

---

### SECTION 16: Other information

Other information : Opteon™ and any associated logos are trademarks or copyrights of The Chemours Company FC, LLC. Chemours™ and the Chemours Logo are trademarks of The Chemours Company. Before use read Chemours safety information. For further information contact the local Chemours office or nominated distributors.

Items where changes have been made to the previous version are highlighted in the body of this document by two vertical lines.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## Opteon™ XL40 (R-454A) Refrigerant

Version	Revision Date:	SDS Number:	Date of last issue: 22.10.2019
4.0	02.03.2020	1354839-00037	Date of first issue: 27.02.2017

### Full text of H-Statements

H221 : Flammable gas.  
H280 : Contains gas under pressure; may explode if heated.

### Full text of other abbreviations

Flam. Gas : Flammable gases  
Press. Gas : Gases under pressure

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - European Agreement concerning the International Carriage of Dangerous Goods by Road; AICS - Australian Inventory of Chemical Substances; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

### Further information

Sources of key data used to compile the Safety Data Sheet : Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agency, <http://echa.europa.eu/>

### Classification of the mixture:

Flam. Gas 1B H221  
Press. Gas Liquefied gas H280

### Classification procedure:

Based on product data or assessment  
Based on product data or assessment

Items where changes have been made to the previous version are highlighted in the body of this document by two vertical lines.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



## Opteon™ XL40 (R-454A) Refrigerant

Version	Revision Date:	SDS Number:	Date of last issue: 22.10.2019
4.0	02.03.2020	1354839-00037	Date of first issue: 27.02.2017

---

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

GB / EN