



Refrigerants

R-454C

GUARANTEED COMMERCIAL SPECIFICATIONS

STANDARD SPECIFICATION *	LIMIT VALUE
Composition	
R-32	21.5 % (+1% -1%)
R-1234yf	78.5 % (+1% -1%)
Purity	≥ 99.5 % weight
Water content	≤ 10 ppm weight
Total Acidity (HCL)	≤ 1 ppm weight
Non condensable content (gas phase)	≤ 1.5 % volume

^{*} données producteur

MAIN APPLICATIONS

R-454C is a non-azeotropic blend containing hydrofluorocarbons (HFCs) and hydrofluoroolefins (HFOs) with a GWP < 150.

It can be used in new commercial and industrial low and medium temperature refrigeration systems, in direct expansion for condensing units, cold rooms and stand-alone systems that were usually using R-404A.

OILS

Use a polyol ester (POE) oil.

Consult **Climalife** regarding the viscosity of the oil selected for your system and the most suitable for your application.

PRECAUTIONS OF USE

Refer to the Safety Data Sheet *.

REGULATION

The use and implementation of R-454C are governed by the European Regulation No 517/2014.

The recovery of R-454C is mandatory under the European Regulation No 517/2014.

(Refer to regulations enforced in each country.)

^{*} Find the Safety Data Sheets (SDS) directly on our website www.climalife.dehon.com.





Fluides Frigorigènes

PHYSICAL PROPERTIES OF R-454C

Molar mass	g/mol	90.8
Melting point	°C	N/A
Boilng point (at 1.013 bar)	°C	-45.56
Temperature glide at 1.013 bar	K	7.81
Saturated liquid density at 25°C	kg/m³	1042
Vapour density at boiling point	kg/m³	4.910
Vapour pressure at:		
25°C	bar	11.90
50°C		21.64
Critical temperature	°C	85.64
Critical pressure	bar	43.19
Critical density	kg/m³	462
Latent heat of vaporisation at boiling point	kJ/kg	227.34
Thermal conductivity at 25°C		
Liquid	W/m.K	0.076
Vapour at 1.013 bar		0.014
Surface tension at 25°C	10⁻³N/m	5.68
Viscosity at 25°C		
Liquid	10 ⁻³ Pa.s	0.129
Vapour at 1.013 bar		0.012
Specific heat at 25°C		
Liquid	kJ/(kg.K)	1.539
Vapour at 1.013 bar		0.892
Cp/Cv ratio at 25°C under 1.013 bar		1.126
Flammability in air		Mildly flammable
Flash point		0
Classification NF-EN 378		A2L
ASHRAE		0
Ozone Depletion Potential		0
GWP IPCC-AR4 / IPCC-AR5		148 / 146

Please contact your distributor or **Climalife** sales department for more information. In addition, if the refrigeration system you want to install, or are working on, does not appear to be a typical installation, please do not hesitate to contact us for advice and information.

The information contained in this product sheet is the result of our studies and experience. It is provided in good faith, but should not, under any circumstance, be taken to constitute a guarantee on our part or an assumption of our responsibility. This is particularly the case when third party rights are at stake or in situations where a user of one of our products fails to observe applicable regulations.



