

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Product form : Mixture  
 Name : Solstice® L40X (R-455A)  
 Product code : 100145100

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

##### 1.2.1. Relevant identified uses

Use of the substance/mixture : Refrigerant

##### 1.2.2. Uses advised against

No additional information available

#### 1.3. Details of the supplier of the safety data sheet

##### Supplier

Dehon Service SAS  
 26 Avenue du Petit Parc  
 94683 VINCENNES Cedex - France  
 T 01 43 98 75 00 - F 01 43 98 21 51  
[ContactFDS@climalife.dehon.com](mailto:ContactFDS@climalife.dehon.com)

##### Other

Climalife Kft Budepesta sucursală Bucuresti Romania  
 Bulevardul Hristo Botev, Nr. 28,  
 Biroul NR 4, Modulul I  
 Bucuresti Sectorul 3 - Romania  
[ContactFDS@climalife.dehon.com](mailto:ContactFDS@climalife.dehon.com)

##### Other

Dehon Kälte-Fachvertriebs GmbH  
 Robert-Bosch-Strasse 14  
 40668 MEERBUSCH - Germany  
 T 00 49 2150 7073 0 - F 00 49 2150 7073 17  
[ContactFDS@climalife.dehon.com](mailto:ContactFDS@climalife.dehon.com)

##### Other

Dehon Service Belgium s.a/n.v.  
 Avenue Carton de Wiart, 79  
 1090 Bruxelles - Belgium  
 T 00 32 2 421 01 70 - F 00 32 2 426 96 62  
[ContactFDS@climalife.dehon.com](mailto:ContactFDS@climalife.dehon.com)

##### Other

Friogas sa  
 Poligono Industrial SEPES  
 Parcela 10  
 46500 SAGUNTO (Valencia) - Spain  
 T 00 34 9 6 266 36 32 - F 00 34 9 6 266 50 25  
[ContactFDS@climalife.dehon.com](mailto:ContactFDS@climalife.dehon.com)

##### Other

Prochimac SA  
 ZI Petits Champs 15  
 CH-1400 Yverdon-les-Bains - Switzerland  
 T 00 41 32 727 36 00 - F 00 41 32 727 36 19  
[ContactFDS@climalife.dehon.com](mailto:ContactFDS@climalife.dehon.com)

#### 1.4. Emergency telephone number

Emergency number : +33 (0) 1 72 11 00 03

##### Other

Climalife Hongrie Kft  
 Villányi út 47  
 1118 Budaörs - Hungary  
 T (36) 23 431 660 - F (36) 23 431 661  
[ContactFDS@climalife.dehon.com](mailto:ContactFDS@climalife.dehon.com)

##### Other

Climalife Supplied by Inventec Performance Chemicals Italia SRL  
 Via del Lavoro, 10/G  
 20874 Busnago MB - Italia  
 T +39 39-5973480 - F +39 39-5973490  
[ContactFDS@climalife.dehon.com](mailto:ContactFDS@climalife.dehon.com)

##### Other

Dehon nordic service  
 Östra Hamngatan 50B 3tr  
 41109 GÖTEBORG - Sweden  
 T 00 46 44 21 58 80 - F 00 46 44 21 58 80  
[ContactFDS@climalife.dehon.com](mailto:ContactFDS@climalife.dehon.com)

##### Other

Dehon Service Nerderland B.V.  
 Van Konijnenburgweg 84  
 NL-4612 PL Bergen Op Zoom - Netherlands  
 T 00 31 164 212 830 - F 00 31 164 212 831  
[ContactFDS@climalife.dehon.com](mailto:ContactFDS@climalife.dehon.com)

##### Other

IDS Refrigeration Limited  
 22 Apex Court, Woodlands, Bradley Stoke  
 BS32 4JT Bristol - United Kingdom  
 T 00 44 1179 802520 - F 00 44 1179 802521  
[ContactFDS@climalife.dehon.com](mailto:ContactFDS@climalife.dehon.com)

# Solstice® L40X (R-455A)

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Country	Organisation/Company	Address	Emergency number	Comment
United Kingdom	National Poisons Information Service (Birmingham Centre) City Hospital	Dudley Road B18 7QH Birmingham	0344 892 0111	

## SECTION 2: Hazards identification

### 2.1. Classification of the substance or mixture

#### Classification according to Regulation (EC) No. 1272/2008 [CLP]

Flam. Gas 1B H221

Press. Gas (Liq.) H280

Full text of hazard classes and H-statements : see section 16

#### Adverse physicochemical, human health and environmental effects

Vapours are heavier than air and can cause suffocation by reducing oxygen available for breathing. Contact with the liquid may cause frostbite and serious damage to eyes.

### 2.2. Label elements

#### Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP)



GHS02

Signal word (CLP)

: Danger

Hazard statements (CLP)

: H221 - Flammable gas.  
H280 - Contains gas under pressure; may explode if heated.

Precautionary statements (CLP)

: P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P377 - Leaking gas fire: Do not extinguish, unless leak can be stopped safely.  
P381 - In case of leakage, eliminate all ignition sources.  
P410+P403 - Protect from sunlight. Store in a well-ventilated place.

Extra phrases

: Greenhouse fluorinated gas falling within Kyoto Protocol (GWP=148).

UFI

: FY10-90KM-600U-D2UJ

### 2.3. Other hazards

No additional information available

## SECTION 3: Composition/information on ingredients

### 3.1. Substances

Not applicable

### 3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
2,3,3,3-Tetrafluoroprop-1-ene substance with a Community workplace exposure limit	(CAS-No.) 754-12-1 (EC-No.) 468-710-7 (REACH-no) 01-0000019665-61	75.5	Flam. Gas 1B, H221 Press. Gas (Liq.), H280
Difluoromethane substance with a Community workplace exposure limit	(CAS-No.) 75-10-5 (EC-No.) 200-839-4 (REACH-no) 01-2119471312-47	21.5	Flam. Gas 1B, H221 Press. Gas (Liq.), H280

# Solstice® L40X (R-455A)

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Carbon dioxide substance with national workplace exposure limit(s) (GB)	(CAS-No.) 124-38-9 (EC-No.) 204-696-9	3	Press. Gas (Liq.), H280
---	--	---	-------------------------

Full text of H-statements: see section 16

### SECTION 4: First aid measures

#### 4.1. Description of first aid measures

- First-aid measures after inhalation : Move the affected person away from the contaminated area and into the fresh air. If you feel unwell, seek medical advice.
- First-aid measures after skin contact : In the event of contact with the liquid: treat resulting frostbite as a burn. Rinse with plenty of water. Do not remove clothing (since it may stick to the skin). If skin burns appear, call a doctor immediately.
- First-aid measures after eye contact : Rinse immediately and thoroughly, pulling the eyelids well away from the eye (15 minutes minimum). Consult an eye specialist immediately.
- First-aid measures after ingestion : Not specifically applicable (gas).

#### 4.2. Most important symptoms and effects, both acute and delayed

- Symptoms/effects : CNS depression. Narcosis. Cardiac disorders. Lack of oxygen: risk of death.

#### 4.3. Indication of any immediate medical attention and special treatment needed

No additional information available

### SECTION 5: Firefighting measures

#### 5.1. Extinguishing media

- Suitable extinguishing media : Water spray, dry chemical powder, alcohol-resistant foam, carbon dioxide (CO<sub>2</sub>).
- Unsuitable extinguishing media : Strong water jet.

#### 5.2. Special hazards arising from the substance or mixture

- Fire hazard : Extremely flammable gas. Heating will cause a rise in pressure with a risk of bursting. Vapours are heavier than air and can cause suffocation by reducing oxygen available for breathing. Hazardous gas/vapours are formed in the event of decomposition (see section 10).
- Hazardous decomposition products in case of fire : Thermal decomposition generates : Carbon oxides (CO, CO<sub>2</sub>), Hydrogen halogenides, Carbonyl halogenides, fluorinated compounds.

#### 5.3. Advice for firefighters

- Firefighting instructions : Use water spray or fog for cooling exposed containers.
- Protection during firefighting : Self-contained breathing apparatus. Complete protective clothing.

### SECTION 6: Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

- General measures : Do not attempt to take action without suitable protective equipment. Avoid contact with skin and eyes. Do not breathe smoke. Do not smoke. Evacuate personnel to a safe area. Ventilate spillage area. Stop leak without risks if possible.

##### 6.1.1. For non-emergency personnel

No additional information available

##### 6.1.2. For emergency responders

No additional information available

# Solstice® L40X (R-455A)

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

### 6.2. Environmental precautions

Product evaporates rapidly when in contact with the air. Prevent entry to sewers and public waters.

### 6.3. Methods and material for containment and cleaning up

Other information : Mechanically ventilate the spillage area.

### 6.4. Reference to other sections

For further information refer to section 8: "Exposure controls/personal protection". For disposal of solid materials or residues refer to section 13 : "Disposal considerations".

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

Precautions for safe handling : Pressurised container. Protect from sunlight and do not expose to temperatures exceeding 50°C. Ensure good ventilation of the work station. Do not pierce or burn, even after use. Use non-sparking tools. Do not use joint paste that may contain peroxides.

Hygiene measures : Do not drink, eat or smoke in the workplace.

### 7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Keep container tight closed. Store : in a cool, well-ventilated area. Store in original container.

Incompatible materials : Strong oxidizing agents. Finely divided aluminium. Magnesium and its alloys. Zinc and its alloys.

### 7.3. Specific end use(s)

No additional information available

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

#### 8.1.1 National occupational exposure and biological limit values

Difluoromethane (75-10-5)	
EU - Indicative Occupational Exposure Limit (IOEL)	
IOEL TWA	2200 (recommended)
IOEL TWA [ppm]	1000 ppm (recommended)

2,3,3,3-Tetrafluoroprop-1-ene (754-12-1)	
EU - Indicative Occupational Exposure Limit (IOEL)	
IOEL TWA [ppm]	500 ppm (recommended)

Carbon dioxide (124-38-9)	
United Kingdom - Occupational Exposure Limits	
WEL TWA (OEL TWA) [1]	9150 mg/m <sup>3</sup>
WEL TWA (OEL TWA) [2]	5000 ppm
WEL STEL (OEL STEL)	27400 mg/m <sup>3</sup>
WEL STEL (OEL STEL) [ppm]	15000 ppm

#### 8.1.2. Recommended monitoring procedures

No additional information available

# Solstice® L40X (R-455A)

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

### 8.1.3. Air contaminants formed

No additional information available

### 8.1.4. DNEL and PNEC

No additional information available

### 8.1.5. Control banding

No additional information available

## 8.2. Exposure controls

### 8.2.1. Appropriate engineering controls

No additional information available

### 8.2.2. Personal protection equipment

#### 8.2.2.1. Eye and face protection

##### Eye protection:

Safety glasses with side shields

#### 8.2.2.2. Skin protection

##### Skin and body protection:

Majority cotton protective clothing

##### Hand protection:

cold-insulating gloves

#### 8.2.2.3. Respiratory protection

##### Respiratory protection:

In the event of insufficient ventilation: Gas mask with filter type AX. In a confined area : Self-contained breathing apparatus

#### 8.2.2.4. Thermal hazards

No additional information available

### 8.2.3. Environmental exposure controls

No additional information available

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state	: Gas
Appearance	: Press. Gas (Liq.).
Colour	: Colourless.
Odour	: slightly ethereal.
Odour threshold	: No data available
pH	: Not applicable
Relative evaporation rate (butylacetate=1)	: No data available
Melting point	: Not applicable
Freezing point	: No data available
Boiling point	: -52.03 °C
Flash point	: Not applicable
Critical temperature	: 85.61 °C
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Flammability (solid, gas)	: Extremely flammable gas.
Vapour pressure	: 13.85 bar (25°C)

# Solstice® L40X (R-455A)

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Vapour pressure at 50 °C	: 24.43 bar (50°C)
Critical pressure	: 46.54 bar
Relative vapour density at 20 °C	: 4.747
Relative density	: No data available
Density	: 1.033 g/cm <sup>3</sup> (25°C)
Solubility	: No data available
Partition coefficient n-octanol/water (Log Pow)	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosive properties	: Not explosive material according to EC criteria.
Oxidising properties	: Non oxidizing material according to EC criteria.
Lower explosive limit (LEL)	: 11.8 vol %
Upper explosive limit (UEL)	: 12.9 vol %

### 9.2. Other information

No additional information available

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

Stable under normal conditions of use.

### 10.2. Chemical stability

Stable at ambient temperature and under normal conditions of use.

### 10.3. Possibility of hazardous reactions

No dangerous polymerization.

### 10.4. Conditions to avoid

Pressurised container. Protect from sunlight and do not expose to temperatures exceeding 50°C. Container under pressure. Do not drill or burn even after use. No flames, no sparks. Eliminate all sources of ignition.

### 10.5. Incompatible materials

Do not use joint paste that may contain peroxides. Strong oxidizing agents. Finely divided aluminium. Magnesium. zinc.

### 10.6. Hazardous decomposition products

Hazardous decomposition products may be released during prolonged heating like smokes, carbon monoxide and dioxide. Hydrogen fluoride. Carbonyl halogenides.

## SECTION 11: Toxicological information

### 11.1 Information on toxicological effects

Acute toxicity (oral)	: Not classified
Acute toxicity (dermal)	: Not classified
Acute toxicity (inhalation)	: Not classified

#### Difluoromethane (75-10-5)

LC50 Inhalation - Rat [ppm]	> 520000 ppm/4h
-----------------------------	-----------------

#### 2,3,3,3-Tetrafluoroprop-1-ene (754-12-1)

LC50 Inhalation - Rat [ppm]	> 400000 ppm/4h
-----------------------------	-----------------

Skin corrosion/irritation	: Not classified pH: Not applicable
---------------------------	--

# Solstice® L40X (R-455A)

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Additional information	: Contact with the liquid causes frostbite
Serious eye damage/irritation	: Not classified pH: Not applicable
Additional information	: Contact with the liquefied gas may cause severe ocular lesions
Respiratory or skin sensitisation	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified
Reproductive toxicity	: Not classified
STOT-single exposure	: Not classified
STOT-repeated exposure	: Not classified

### Difluoromethane (75-10-5)

NOAEC (inhalation, rat, gas, 90 days)	50000 ppmv/6h/day
---------------------------------------	-------------------

Aspiration hazard : Not classified

## SECTION 12: Ecological information

### 12.1. Toxicity

Hazardous to the aquatic environment, short-term (acute)	: Not classified
Hazardous to the aquatic environment, long-term (chronic)	: Not classified

### 2,3,3,3-Tetrafluoroprop-1-ene (754-12-1)

LC50 - Fish [1]	> 197 mg/l <i>Cyprinus carpio</i> (Common carp)
EC50 - Crustacea [1]	> 83 mg/l ( <i>Daphnia magna</i> )
EC50 72h - Algae [1]	> 100 mg/l ( <i>scenedesmus capricornutum</i> )

### 12.2. Persistence and degradability

#### 2,3,3,3-Tetrafluoroprop-1-ene (754-12-1)

Persistence and degradability	Not readily biodegradable.
-------------------------------	----------------------------

### 12.3. Bioaccumulative potential

#### Difluoromethane (75-10-5)

Partition coefficient n-octanol/water (Log Pow)	0.21
---	------

#### 2,3,3,3-Tetrafluoroprop-1-ene (754-12-1)

Partition coefficient n-octanol/water (Log Pow)	2.15
---	------

#### Carbon dioxide (124-38-9)

Partition coefficient n-octanol/water (Log Pow)	0.83
---	------

### 12.4. Mobility in soil

No additional information available

# Solstice® L40X (R-455A)

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

### 12.5. Results of PBT and vPvB assessment

#### Component

2,3,3,3-Tetrafluoroprop-1-ene (754-12-1)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII
--	---

### 12.6. Other adverse effects

Other adverse effects : Ozone depletion factor ODP (R-11=1) = 0. Total global warming potential (GWP) : 148.




## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

- Product/Packaging disposal recommendations : Methods of disposal of packaging. Reuse or recycle following decontamination. Destroy at an authorised site.
- Additional information : The user's attention is drawn to the possible existence of specific european, national or local regulations regarding disposal. Refer to manufacturer or supplier for information on recovery or recycling.
- Ecology - waste materials : Must not be discharged to atmosphere. Refer to manufacturer or supplier for information on recovery or recycling.

## SECTION 14: Transport information

In accordance with ADR / IMDG / IATA

ADR	IMDG	IATA
<b>14.1. UN number</b>		
UN 3161	UN 3161	UN 3161
<b>14.2. UN proper shipping name</b>		
LIQUEFIED GAS, FLAMMABLE, N.O.S. (2,3,3,3-Tetrafluoroprop-1-ene ; Difluoromethane ; Carbon dioxide)	LIQUEFIED GAS, FLAMMABLE, N.O.S. (2,3,3,3-Tetrafluoroprop-1-ene ; Difluoromethane ; Carbon dioxide)	Liquefied gas, flammable, n.o.s. (2,3,3,3-Tetrafluoroprop-1-ene ; Difluoromethane ; Carbon dioxide)
<b>Transport document description</b>		
UN 3161 LIQUEFIED GAS, FLAMMABLE, N.O.S. (2,3,3,3-Tetrafluoroprop-1-ene ; Difluoromethane ; Carbon dioxide), 2.1, (B/D)	UN 3161 LIQUEFIED GAS, FLAMMABLE, N.O.S. (2,3,3,3-Tetrafluoroprop-1-ene ; Difluoromethane ; Carbon dioxide), 2.1	UN 3161 Liquefied gas, flammable, n.o.s. (2,3,3,3-Tetrafluoroprop-1-ene ; Difluoromethane ; Carbon dioxide), 2.1
<b>14.3. Transport hazard class(es)</b>		
2.1	2.1	2.1
		
<b>14.4. Packing group</b>		
Not applicable	Not applicable	Not applicable
<b>14.5. Environmental hazards</b>		
Dangerous for the environment : No	Dangerous for the environment : No Marine pollutant : No	Dangerous for the environment : No



# Solstice® L40X (R-455A)

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

No supplementary information available

### 14.6. Special precautions for user

#### Overland transport

Classification code (ADR) : 2F  
Special provisions (ADR) : 274, 662  
Limited quantities (ADR) : 0  
Tank code (ADR) : PxBN(M)  
Transport category (ADR) : 2  
Hazard identification number (Kemler No.) : 23  
Orange plates :

23

3161

Tunnel restriction code (ADR) : B/D  
EAC code : 2YE

#### Transport by sea

Special provisions (IMDG) : 274  
Limited quantities (IMDG) : 0  
EmS-No. (Fire) : F-D  
EmS-No. (Spillage) : S-U

#### Air transport

PCA Limited quantities (IATA) : Forbidden  
PCA limited quantity max net quantity (IATA) : Forbidden  
PCA packing instructions (IATA) : Forbidden  
PCA max net quantity (IATA) : Forbidden  
CAO packing instructions (IATA) : 200  
CAO max net quantity (IATA) : 150kg  
Special provisions (IATA) : A1

### 14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable

## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### 15.1.1. EU-Regulations

Contains no REACH substances with Annex XVII restrictions

Contains no substance on the REACH candidate list

Contains no REACH Annex XIV substances

Contains no substance subject to Regulation (EU) No 649/2012 of the European Parliament and of the Council of 4 July 2012 concerning the export and import of hazardous chemicals.

Contains no substance subject to Regulation (EU) No 2019/1021 of the European Parliament and of the Council of 20 June 2019 on persistent organic pollutants

#### 15.1.2. National regulations

Ensure all national/local regulations are observed.

### 15.2. Chemical safety assessment

No additional information available

# Solstice® L40X (R-455A)

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

### SECTION 16: Other information

#### Indication of changes:

Section	Changed item	Change	Comments
2	Classification and labelling	Modified	
9.1	Explosive limits	Modified	

Other information : For more information regarding the use of this product, please refer to our technical information or contact the sales department in your region.

#### Full text of H- and EUH-statements:

Flam. Gas 1B	Flammable gases, Category 1B
Press. Gas (Liq.)	Gases under pressure : Liquefied gas
H221	Flammable gas.
H280	Contains gas under pressure; may explode if heated.

Safety Data Sheet (SDS), EU

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.